

M.V. "LIZZIE & ANNIE"

(Continued)

WEAR AND TEAR REPAIRS: A few defective shell rivets dealt with and one hatchway wood fore and after renewed; steering gear chains removed, annealed and refitted, and other minor repairs effected.

MACHINERY: New cast iron propeller now fitted, outside fastenings to sea connections examined and found in good order.

W.P. Watson

N.B.—If this Report is copied by Copying Press, especial care must be taken that the copying paper is not so much damped as to spread the ink, or to cause it to show through to the other side.

When Anchors or Cables are supplied, the particulars are to be reported in the following form :—

ANCHORS.

Number of Certificate.	Anchors.*	WEIGHT, EX. STOCK.			WEIGHT OF STOCK.			TEST PER CERTIFICATE.			WEIGHT REQUIRED BY RULE.			Description of Anchor.	Makers.	Where and when tested and Superintendent.
		Cwts.	qrs.	lbs.	Cwts.	qrs.	lbs.	Tons	Cwts.	qrs.	lbs.	Cwts.	qrs.	lbs.		
	1st Bower															
	2nd "															
	3rd "															
	Collective Weight															
	Stream.....															
	Kedge															

* When a bower anchor is supplied it must be clearly stated whether it is a 1st, 2nd, or 3rd bower.

CHAIN CABLES.

Number of Certificate.	Length and size supplied.		Test per Certificate.		WEIGHT OF CHAIN CABLE.		Length and size per rule.		Description.	Makers of Cables.	Where and when tested and Superintendent.
	Length.	Diam.	Statutory.	Breaking.	Supplied.	Per Rule.	Length.	Diam.			
	Fathoms.	Inches.	Tons.	Tons.	Cwts. qrs. lbs.	Cwts. qrs. lbs.	Fathoms.	Inches.			
22804	30 2/3	7/8	9 1/2	18 1/2	14.1.7	12-3-0	-	11/16	Short link.	Not stated.	Low Walker 15. 7. 47. R.J.Vogan.
Iron Stream Chain } or Steel Wire }											

(7/8" dia. short-link c.c. supplied when ship reclassified 14. 2. 47)

THE SURVEYORS ARE REQUESTED NOT TO WRITE ACROSS THIS MARGIN