

LIST OF SPARE GEAR FOR TURBINES ETC.

			DIA.	LENGTH OVERALL	NO. OFF.
Turbine Bearings.	Studs & Nuts.		3/4"	2 1/2"	2
Turbine Horizontal Joint.	Bolts & Nuts (a)		1 1/2"	6 3/4"	2
" " "	" " (b)		1 1/2"	7 3/4"	1
" " "	" " (c)		1 1/2"	7 3/4"	1
" " "	" " (d)		1 1/2"	7-5/16"	1
" " "	Studs & Nuts (e)		1 1/2"	5 1/2"	2
Turbine Bearings.	Studs & Nuts		7/8"	2 3/4"	2
" Thrust Block Collar	" "		7/8"	3 1/2"	2
" Horizontal Joint.	Bolts & Nuts (a)		1 1/2"	7 3/4"	1
" " "	" " (b)		1 1/2"	6-13/16"	10
" " "	" " (c)		1 1/2"	6-15/16"	1
" " "	Studs " (d)		1 1/2"	5 1/4"	1
Turbine Bearings.	Studs & Nuts.		1 1/2"	3 3/4"	2
" Thrust Block Collar	" "		1 1/2"	4 3/4"	2
" Horizontal Joint	Bolts & Nuts P.		1 1/2"	7 3/4"	1
" " "	" " Q.		1 1/2"	6-5/16"	14
" " "	" " R.		1 1/2"	6 1/2"	2
In Gear Wheel Bearings.	Studs & Nuts		1 1/2"	5 3/4"	2
Reduction Pinion "	" "		1 1/2"	5"	2
" " "	" "		1 1/2"	3 7/8"	2
Coupling.	Bolts & Nuts.	J	3-13/16"	14 1/2"	9
Condenser	Collar Bolts and Nuts	U	7/8" & 1"	5-3/16"	6
"	Collar Bolts & Cap Nuts	X	7/8" & 1"	5-3/16"	3
"	Bolts and Nuts.	V	7/8"	4 1/4"	3
"	Studs and Nuts	V	7/8"	3 1/2"	3
Liary Condenser	Collar Bolts & Nuts	O	3/4"	4 3/4"	6
"	Collar Bolts & Cap Nuts	R	3/4"	4 3/4"	3
"	Bolts & Nuts	U	3/4"	3 3/4"	3
"	Studs & Nuts	V	3/4"	2 3/4"	3
ling Bolts. Thrust shaft to Gear Wheel		K	3-13/16"	23 1/2"	2
mediate Shaft Q.					1
st Shaft H.					1

DING



© 2018

Lloyd's Register
Foundation

50 Tubes for Oil Coolers.

1 Gauge Glass Stand complete with fittings.

2 - 3" Valve lids for check valves on D.E.Boiler.

1 - 2½" " " " " " S.E. "

3 Springs for Safety Valve on D.E. Boiler.

2 " " " " " S.E. "

1 " " " " " superheater D.E.Boiler.

1 " " " " " S.E. "

1 " " Exhaust to Atmosphere F.529.

1 " " Relief Valve on Ballast Pump. F.362 & 3.

1 " " " " " Feed Discharge.F.240 & 242.

1 " " " " " Fire Pump Disc.F.566.

1 " " Aulas Reducing Valve. F.550

2 Glasses for O.P.Settling Tank Gauges.

4 Joints " " " " "

1 spring settling tank residue disch. F.876-7

1 Spring O.P.Filling Relief Valve. F.1393-4

1 Spring Relief Valve on Drainage System. F.1470.

1 " " " " " " F.1471.

1 Spring for Relief Valve on F.L.Discharge F.452.

1 " " Reducing Valve. F.1321.

1 " " " " " F.1045.

1 Glass for F.L.Observation Chests. F.1292-3.

1 " " " " " F.1296-7.

1 " " " " " F.1294-5.

1 " " " " " F.1298

2 Joints " " " " " F.1292-3

2 " " " " " F.1296-7

2 " " " " " F.1294-5

2 " " " " " F.1298.

1 Spring for Relief Valve on Exhaust Range. F.1046-7.

1 " " " " " " F.1048-9

1 " " Automatic Bypass valve on F.L.Range. F.1006.



© 2018

Lloyd's Register
Foundation

- 1 Spring for Bypass Valve on F.L.Range. F.1358.
- 1 " " Relief Valve on F.W. & W.W. Pumps. P.1412.-13.
- 1 Spring for Aux.Exhaust to L.P.Turbine. F.546-7.
- 50 Boiler Tubes. Plain.
- 6 Boiler Stay Tubes.
- 2 Manhole Doors.
- 1 Glass for F.980 on observation tank.
- 2 Leather Joints for F.980 on observation tank.
- 1 Glass for F.951 & 2. " " "
- 2 Leather Joints " " " "
- 1 Glass for F.829-30 on storage and settling tanks.
- 2 Leather Joints " " " " " "

