

REPORT ON ELECTRIC FITTINGS.

(OTHER THAN FOR THE PROPULSION OF THE VESSEL)

Date of writing Report 14.10.30 When handed in at Local Office 15 Oct. 30 Port of **HULL**

No. in Survey held at **HULL** Date, First Survey 3 Oct. Last Survey 13 Oct. 1930

Reg. Book. 61105 on the **STEAM TRAWLER "GEORGE AUNGER"** Tons { Gross 363.06 Net 173.42

Built at **Beverley** By whom built **Cook, Welton & Gemmell** Ltd. No. 554 When built 1930

Owners **The Bunch Steam Fishing Co. Ltd.** Port belonging to **Grimsby**

Electric Light Installation fitted by **Humber Electrical Co. Ltd.** Contract No. When fitted 1930

Is the Vessel fitted for carrying Petroleum in bulk **no**

System of Distribution **Two wire**

Pressure of supply for Lighting 100 volts, Heating ☒ volts, Power ☒ volts.

Direct or Alternating Current, Lighting **Direct** Power ☒

If alternating current system, state frequency of periods per second ☒

Has the Automatic Governor been tested and found efficient when the whole load is suddenly thrown on or off **Yes**

Generators, do they comply with the requirements regarding rating **Yes**, are they compound wound **Yes**

are they over compounded 5 per cent. **Yes**, if not compound wound state distance between each generator

Where more than one generator is fitted are they arranged to run in parallel ☒ is an adjustable regulating resistance fitted in

series with each shunt field **Yes**

Are all terminals accessible, clearly marked, and furnished with sockets **Yes**, are they so spaced or shielded that they cannot be accidentally earthed,

short circuited, or touched **Yes** Are the lubricating arrangements of the generators as per Rule

Position of Generators **Starboard side of engine room.**

is the ventilation in way of the generators satisfactory **Yes**, are they clear of all inflammable material **Yes**

if situated near unprotected woodwork or other combustible material, state distance of same horizontally from or vertically above the generators

☒ and ☒ are the generators protected from mechanical injury and damage from water, steam or oil **Yes**

are their axes of rotation fore and aft **Yes**

Earthing, are the bedplates and frames of the generating plant efficiently earthed **Yes** are the prime movers and

their respective generators in metallic contact **Yes - direct coupled.**

Main Switch Boards, where placed **Beside generator in engine room.**

If the generators and main switchboard are not placed in the same compartment, is each generator provided with

a fuse on each insulated pole as near as possible to the terminals of the generator, additional to that provided on the main switchboard ☒

Switchboards, are they placed in accessible positions, free from inflammable gases and acid fumes **Yes**

are they protected from mechanical injury and damage from water, steam or oil **Yes**, if situated near unprotected

woodwork or other combustible material, state distance of same horizontally from or vertically above the switchboards ☒ and ☒

are they constructed wholly of durable, non-ignitable non-absorbent materials **Yes**, is all insulation of high dielectric strength and of

permanently high insulation resistance **Yes**, if semi-insulating material is used, are all conducting parts insulated from the slab

with mica or micanite or other non-hygroscopic insulating material, and the slab similarly insulated from its framework ☒

and is the frame effectively earthed **Yes** Are the fittings as per Rule regarding:— spacing or shielding of live parts

Yes, accessibility of all parts **Yes**, absence of fuses on back of board **Yes**, proportion of omnibus

bars **Yes**, individual fuses to voltmeter, pilot or earth lamp **Yes**, connections of switches **Yes**

Main Switchgear, description of switchgear for each generator and each outgoing circuit, and arrangement of equalizer switches **S.P. linked**

switch for generator. Outgoing circuits controlled by S.P.

switches and protected by fuses on each pole.


Instruments on main switchboard **One** ammeters **One** voltmeters ☒ synchronising device for paralleling purposes.

Earth Testing, state what means are provided at the main switchboard for indicating the state of the insulation of the system

Earth lamps with separate switches.

Switches, Circuit Breakers and Fusible Cut-outs, do these comply with the requirements of the Rules **Yes**

Joint Boxes Section and Distribution Boards, is the construction, protection, insulation, material, and position of these as per rule **Yes.**



© 2019

Lloyd's Register Foundation

Cables: Single, twin, concentric, or multicore

are the cables insulated and protected as per Tables IV or V of the Rules

Yes

Fall of Pressure, state maximum between bus bars and any point of the installation under maximum load

1 Volt

Cable Sockets and other connections, are the ends of all cables having a sectional area of 0.04 square inch and above provided with soldering sockets

Yes

Paper Insulated Cables. If cables are paper covered, is the dielectric at the exposed ends of the conductor protected from moisture by being suitably sealed with insulating compound

None

Cable Runs, are the cables fixed as far as possible in accessible positions not exposed to drip or accumulation of water or oil, or to high temperature from boilers, steam pipes, uptakes or other hot objects, or to avoidable risk of mechanical damage

Yes

Support and Protection of Cables, state how the cables are supported and protected

L.C. cables with brass clips.

Armoured cables with L.C. clips.

If cables are run in wood casings, are the casings and caps secured by screws, are the cap screws of brass, are the cables run in separate grooves. If armoured and lead covered cables are secured by metal clips, are the clips spaced as per Table VIII

Yes

Refrigerated Chambers, if lights are fitted, are the cables and fittings in accordance with the special requirements

None

Joints in Cables, state if any, and how made, insulated, and protected

No joints

Watertight Glands and Deck Tubes, are all cables passing through decks and watertight bulkheads provided with deck tubes or watertight glands

Yes

Bushes in Beams and Non-watertight Partitions, where unarmoured cables pass through beams and non-watertight partitions, are the holes efficiently bushed, state the material of which the bushes are made

Yes

Lead

Earthing Connections, state what earthing connections are fitted and their respective sectional areas

Through earth lamps

are their connections made as per Rule

Yes

Alternative Lighting, are the groups of lights in the propelling machinery space arranged as per Rule

Yes

Emergency Supply, state position and method of control of the emergency supply and how the generator is driven

None

Navigation Lamps, are these separately wired, controlled by separate switch and separate fuses, are the fuses double pole

Yes

Yes

Yes

are the switches and fuses grouped in a position accessible only to the officers on watch

Yes

has each navigation lamp an automatic indicator as per Rule

No

Secondary Batteries, are they constructed and fitted as per Rule

Fittings, are all fittings on weather decks, in stokeholds and engine rooms and wherever exposed to drip or condensed moisture, watertight

Yes

are any fittings placed in spaces in which goods are liable to be stacked in close proximity to them; if so, how are they protected

None

are any fittings placed in spaces where inflammable or explosive dust or gases are liable to be present, if so, how are they protected

None

how are the cables led

where are the controlling switches situated

Searchlight Lamps, No. of, whether fixed or portable, are their fittings as per Rule

Arc Lamps, other than searchlight lamps, No. of, are their live parts insulated from the frame or case, are their fittings as per Rule

Motors, are their working parts readily accessible, are the coils self-contained and readily removable for replacement

are the brushes, brush holders, terminals and lubricating arrangements as per Rule, are the motors placed in well-ventilated compartments in which inflammable gases cannot accumulate and clear of all inflammable material

are they protected from mechanical injury and damage from water, steam or oil, are their axes of rotation fore and aft


if situated near unprotected woodwork or other combustible material, are the motors of the totally enclosed, pipe ventilated, forced draught, drip or flame proof type, if not of this type, state distance of the combustible material horizontally or vertically above the motors and

Control Gear and Resistances, are the generator field and motor speed regulators, starters and controllers constructed and fitted as per Rule

Lightning Conductors, where lightning conductors are required, are these fitted as per Rule

Ships carrying Oil having a Flash Point less than 150° F. Have the special requirements of the Rules been complied with regarding switches, joint boxes, section and distribution boards, protection of cables, method of distribution, lead of cables, lights and fittings

If portable lamps for use in dangerous spaces are supplied, are they of a type approved by the Home Office



© 2019

Lloyd's Register Foundation

PARTICULARS OF GENERATING PLANT.

DESCRIPTION OF GENERATOR.	No. of	RATED AT				DRIVEN BY	WHERE DRIVEN BY AN INTERNAL COMBUSTION ENGINE.	
		Kilowatts.	Volts.	Ampères.	Revs. per Min.		Fuel Used.	Flash Point of Fuel.
MAIN ...	One	5	100	50	400	Steam engine		
AUXILIARY ...								
EMERGENCY ...								
ROTARY TRANSFORMER								

GENERATOR, LIGHTING AND HEATING CONDUCTORS.

DESCRIPTION.	CONDUCTORS.		COMPOSITION OF STRAND.		TOTAL MAXIMUM CURRENT. AMPERES.		Approximate Length. (Lead and Return.) Feet.	Insulated with	HOW PROTECTED.
	No. per Pole.	Total Effective Area per Pole Sq. Ins.	No.	Diameter.	In Circuit.	Rule.			
MAIN GENERATOR ...	2	0.064	19	16 WG	50		24	V.I.R.	173.42
EQUALISER CONNECTIONS ...									
AUXILIARY GENERATOR ...									
EMERGENCY GENERATOR ...									
ROTARY TRANSFORMER { MOTOR GENERATOR ...									2.0
ENGINE ROOM ...	2	0.0018	3	20 "	3.5		20	"	L.C. armoured
BOILER ROOM ...	2	"	"	"	1.5		40	"	"
AUXILIARY SWITCHBOARDS ...									
ACCOMODATION ...	2	0.012	7	18 "	12.0		150	"	"
Navigation Main ...	2	0.007	7	20 "	4.0		150	"	"
WIRELESS ...									
SEARCHLIGHT ...									
MASTHEAD LIGHT ...	2	0.0018	3	20 "	1.0		180	"	"
SIDE LIGHTS ...	2	"	3	20 "	1.0		30	"	L.C.
COMPASS LIGHTS ...									
POOP LIGHTS ...									
CARGO LIGHTS ...									
ARC LAMPS ...									
HEATERS ...									

MOTOR CONDUCTORS.

DESCRIPTION.	No. of Motors.	CONDUCTORS.		COMPOSITION OF STRAND.		TOTAL MAXIMUM CURRENT. AMPERES.		Approximate Length. (Lead and Return.) Feet.	Insulated with	HOW PROTECTED.
		No. Per Pole.	Total Effective Area per Pole Sq. Ins.	No.	Diameter.	In Circuit.	Rule.			
BALLAST PUMP ...										
MAIN BILGE PUMP ...										
GENERAL SERVICE PUMP ...										
EMERGENCY BILGE PUMP ...										
SANITARY PUMP ...										
CIRC. SEA WATER PUMPS ...										
CIRC. FRESH WATER PUMPS ...										
AIR COMPRESSOR ...										
FRESH WATER PUMP ...										
ENGINE TURNING GEAR ...										
ENGINE REVERSING GEAR ...										
LUBRICATING OIL PUMPS ...										
OIL FUEL TRANSFER PUMP ...										
WINDLASS ...										
WINCHES, FORWARD ...										
WINCHES, AFT ...										
STEERING GEAR—										
(a) MOTOR GENERATOR ...										
(b) MAIN MOTOR ...										
WORKSHOP MOTOR ...										
VENTILATING FANS ...										



© 2019

Lloyd's Register Foundation

All Conductors are of annealed copper conforming to British Standard Specification No. 7.

The Insulated Conductors are guaranteed to withstand the immersion and resistance tests specified in the Rules.

The foregoing is a correct description.

FOR THE HUNTER ELECTRICAL ENGINEERING CO.

W. B. Shuttleworth, Proprietor.

Electrical Engineers.

Date

COMPASSES.

Distance between electric generators or motors and standard compass

68 ft.

Distance between electric generators or motors and steering compass

The nearest cables to the compasses are as follows:—

A cable carrying 0.5 Amperes To feet from standard compass feet from steering compass.

A cable carrying 0.5 Amperes To feet from standard compass feet from steering compass.

A cable carrying 0.5 Amperes To feet from standard compass feet from steering compass.

Have the compasses been adjusted with and without the electric installation at work at full power

Yes

Has the effect of switching on and off circuits, motors and other electro-magnetic apparatus within the vicinity of the compasses been noted

Yes

The maximum deviation due to electric currents was found to be

no

degrees on

any

course in the case of the standard

compass, and no degrees on

any

course in the case of the steering compass.

COOK, WELTON & GEMMELL LTD.

A. D. Camper

Builder's Signature.

Date

4/10/30.

Is this installation a duplicate of a previous case

Yes

If so, state name of vessel

500.0 Gallon

General Remarks (State quality of workmanship, opinions as to class, &c.)

The electrical installation of this vessel has been fitted on board under special survey, tried under working conditions and found in good order.

It is eligible, in my opinion, to have record of "Electric Light".

It is submitted that this vessel is eligible for THE RECORD. Elec Light.

20/10/30

Total Capacity of Generators 5 Kilowatts.

The amount of Fee ... £ 3 : 0 : 15 Oct 1930.

Travelling Expenses (if any) £ : : 11.11.1930

b. Moffatt.

Surveyor to Lloyd's Register of Shipping.

Committee's Minute

TUE. 21 OCT 1930

Assigned

Elec Light



© 2019

Lloyd's Register Foundation