

May 3rd 1920

REPORT ON ELECTRIC LIGHTING INSTALLATION. No. 93

Port of Wilmington N.C. Date of First Survey 22nd Nov 1919 Date of Last Survey 13th Mar 1920 No. of Visits 16
 No. in Reg. Book on the Iron or Steel S.S. "City of Omaha" Port belonging to Wilmington N.C.
 Built at Wilmington N.C. By whom George A. Fuller Co. When built 1919-20
 Owners U.S. Shipping Board Owners' Address 140 North Broad Street Philadelphia
 Yard No. 1447 Electric Light Installation fitted by George A. Fuller Co. When fitted 1920

DESCRIPTION OF DYNAMO, ENGINE, ETC.

2 General Electric Marine Generating sets consisting of G.E. 8"x6" single cylinder double acting engine and G.E. Generator on continuous base.

Capacity of Dynamo 130 Amperes at 115 Volts, whether continuous or alternating current continuous

Where is Dynamo fixed Starboard side of engine room Whether single or double wire system is used double

Position of Main Switch Board Engine room having switches to groups & subpanels of lights, etc., as below

Positions of auxiliary switch boards and numbers of switches on each Forward deck house 8 circuit. Side deck house 6 circuit and Poop 4 circuits.

If fuses are fitted on main switch board to the cables of main circuit Yes and on each auxiliary switch board to the cables of auxiliary circuits Yes and at each position where a cable is branched or reduced in size Yes and to each lamp circuit Yes

If vessel is wired on the double wire system are fuses fitted to both flow and return wires or cables of all circuits including lamp circuits

Are the fuses of non-oxidizable metal Yes and constructed to fuse at an excess of 25 per cent over the normal current

Are all fuses fitted in easily accessible positions Yes Are the fuses of standard dimensions Yes If wire fuses are used are permanent instructions fitted on or near each switch board giving particulars of proper size of fuse for each circuit none used

Are all switches and fuses constructed of incombustible materials and fitted on incombustible bases Yes

Total number of lights provided for 223 arranged in the following groups:—

Group	Number of lights	Watts each	Candle power	Current (Amperes)
A	4	100 Watts	requiring a total current of	Amperes
B	208	50 "	requiring a total current of	Amperes
C	6	15 "	requiring a total current of	Amperes
D	5	10 "	requiring a total current of	Amperes
E			requiring a total current of	Amperes
2 Mast head light with 2 lamps each of 16 candle power requiring a total current of Amperes				
2 Side light with 2 lamps each of 16 candle power requiring a total current of Amperes				
9 x 4 Cargo lights of 50 Watts candle power, whether incandescent or arc lights <u>incandescent</u>				

If arc lights, what protection is provided against fire, sparks, etc. ✓

Where are the switches controlling the masthead and side lights placed Pilot room

DESCRIPTION OF CABLES.

Main cable carrying 120 Amperes, comprised of 2 wires, each 00 B.S. S.W.G. diameter, ✓ 2.172 square inches total sectional area

Branch cables carrying 20 Amperes, comprised of 2 wires, each 4 B.S. S.W.G. diameter, ✓ .06536 square inches total sectional area

Branch cables carrying 15 Amperes, comprised of 2 wires, each 6 B.S. S.W.G. diameter, ✓ .0510 square inches total sectional area

Leads to lamps carrying 5 Amperes, comprised of 2 wires, each 14 B.S. S.W.G. diameter, ✓ .05202 square inches total sectional area

Cargo light cables carrying 2 Amperes, comprised of 2 wires, each 14 B.S. S.W.G. diameter, ✓ .10456 square inches total sectional area

DESCRIPTION OF INSULATION, PROTECTION, ETC.


All wires and cables rubber insulated, braided and enclosed in iron conduits.

Joints in cables, how made, insulated, and protected Soldered, wound with rubber and friction tape and schellack

Are all the joints of cables thoroughly soldered, and the flux used not containing acids or other corrosive substances Yes Are all joints in accessible positions, none being made in bunkers, cargo spaces, or spaces which may at any time be used for carrying cargo, stores, or baggage

Are there any joints in or branches from the cable leading from dynamo to main switch board No

How are the cables led through the ship, and how protected in iron conduits



DESCRIPTION OF INSULATION, PROTECTION, ETC.—continued.

Are they in places always accessible *no* — *main feeders pass through cargo spaces but protected*
 What special protection has been provided for the cables in open alleyways or where exposed to weather or moisture *Conduit*
 What special protection has been provided for the cables near galleys or oil lamps or other sources of heat *Conduit*
 What special protection has been provided for the cables near boiler casings *Conduit*
 What special protection has been provided for the cables in engine room *Conduit*
 How are cables carried through beams *none through beams* through bulkheads, &c. *Conduits*
 How are cables carried through decks *Conduits*
 Are any cables run through coal bunkers *no* or cargo spaces *yes* or spaces which may be used for carrying cargo, stores, or baggage *yes*
 If so, how are they protected *in conduits*
 Are any lamps fitted in coal bunkers or spaces which may at times be used for cargo, coals, or baggage *in midship cargo space shelter deck*
 If so, how are the lamp fittings and cable terminals specially protected *in water tight globes*
 Where are the main switches and fuses for these lights fitted
 If in the spaces, how are they specially protected
 Are any switches or fuses fitted in bunkers *no*
 Cargo light cables, whether portable or permanently fixed *Portable* How fixed
 In vessels fitted on the single wire system, how is the dynamo terminal fixed to the hull of vessel
 How are the returns from the lamps connected to the hull
 Are all the joints with the hull in accessible positions
 Is the installation supplied with a voltmeter *1*, and with an amperemeter *2*, fixed *Switchboard*

VESSELS BUILT FOR CARRYING PETROLEUM.

In vessels built for carrying petroleum, are all switches and fuses fitted in positions not liable to the accumulation of petroleum vapour or gas *yes*
 Are any switches, fuses, or joints of cables fitted in the pump room or companion
 How are the lamps specially protected in places liable to the accumulation of vapour or gas *Water tight and vapour proof fittings*

The copper used is guaranteed to have a conductivity of not less than that of the Engineering Standards Committee's standard, and the wires are protected by tinning from the sulphur compounds present in the insulating material.
 Insulation of cables is guaranteed to have a resistance of not less than *200* megohms per statute mile at 60° Fahrenheit after 24 hours' immersion in water, the test being made after one minute's electrification at not less than 500 volts and while the cable is still immersed.

The foregoing statements are a correct description of the Electric Light installation fitted by us on this vessel and we declare that it is at this date in good order and safe working condition.

George A. Fuller Company
Sorenso corius
 Vice-President.

Electrical Engineers

Date *March 24 1920*

COMPASSES.

Distance between dynamo or electric motors and standard compass *125 feet*
 Distance between dynamo or electric motors and steering compass *115 feet*

The nearest cables to the compasses are as follows:—

A cable carrying	<i>20</i> Amperes	<i>25</i> feet from standard compass	feet from steering compass
A cable carrying	Amperes	feet from standard compass	feet from steering compass
A cable carrying	Amperes	feet from standard compass	feet from steering compass

Have the compasses been adjusted with and without the electric installation at work at full power
 The maximum deviation due to electric currents, etc., was found to be _____ degrees on _____ course in the case of the standard compass and _____ degrees on _____ course in the case of the steering compass.

George A. Fuller Company
Sorenso corius
 Vice-President.

Builder's Signature.

Date *March 29 1920*

GENERAL REMARKS.

This vessel has been fitted with an electric light installation as above and the workmanship is good. On completion it was tried under full working conditions and found satisfactory

It is submitted that this vessel is eligible for
 THE RECORD. ELEC. LIGHT. *2/5/20*

Geo. Allan
 Surveyor to Lloyd's Register of Shipping.

Committee's Minute

Eles dt

New York MAY - 8/1920

THE SURVEYORS ARE REQUESTED NOT TO WRITE ACROSS THIS MARGIN.



© 2021

Lloyd's Register Foundation