

WEB FRAMES. Inches in Ship. Inches in Ship. Inches per Rule. Inches per Rule. FORGINGS or CASTINGS. Inches in Ship. Inches per Rule. Or as Approved. KEEL, Bar, depth and thickness. STEM, moulding and thickness. STERN-POST for Rudder do. do. RUDDER-AND Table 22. Speed. Main-Piece, diameter at head. RUDDER, how constructed. Thickness of or Single Plate. Manufacturer's name or trade mark of the Iron or Steel (state process of manufacture of Steel) used for Frames, Floors, Beams, Keelsons, Tie and Stringer Plates, Plating, &c. PLATING. STRAKES. AS IN SHIP. PER RULE OR AS APPROVED. EDGES. BUTTS. RIVETING. Upper Deck. Stringer Plate. Second Deck. Stringer Plate. FRAMES extend in one length from. REVERSED FRAMES on floors and frames extend from. MASTS, SPARS, &c. LOWER MASTS. Bowsprit. Topmasts, Yards and Remainder of Spars. Rigging, Material and Size, Shrouds. Sails.

EQUIPMENT No. LETTER ANCHORS. TONNAGE U.D.K. OR PLATING No. FOR TRAWLERS. CHAIN CABLES. HAWSERS AND WARPS. Boats. Steering Gear, Steam. Steering Gear, Hand. Pumps, Number. Windlass is. Engine Room Skylights. Coal Bunker Openings. Number of Scuppers, and numbers and dimensions of Freeing Ports, &c. Ceiling in Holds, thickness and material. Cargo Hatchways. State size No. 1 Hatch (Forward). Number of Web Plates, Shifting Beams and Fore and Afters to each Hatch. Bulwarks, height above deck and description. Correspondence. Workmanship. Is the riveted work properly closed? Are the liners between the frames and plates solid single pieces? Are the butts of Plating, Stringers, &c., properly shifted and strapped? Have all the upper and weather decks been tested as required by the Rules (Sec. 26, par. 20)? Have all the gutterways been tested as required by the Rules (Sec. 26, par. 20)? General Remarks. Committee's Minute. Character assigned. Sigsbee & Co. Long Range Machy aft. C. R. D. Lloyd's Register of Shipping.

GEN

PARTICULARS OF LONGITUDINAL FRAMING.

FRAMING.		AMIDSHIPS.			ENDS.			AMIDSHIPS.			ENDS.			RIVETING.								
		In Ship.			In Ship.			Per Rule or as approved.			Per Rule or as approved.			Rivets in Longitudinal Frames.			Spacing of Rivets on each side of Transverses and Bulkheads.			Rivets in Brackets to Bulkheads.		
		Ins.	Ins.	Ins.	Ins.	Ins.	Ins.	Ins.	Ins.	Ins.	Ins.	Ins.	Ins.	Ins.	Ins.	Ins.	Ins.	Ins.	Ins.	Ins.	Ins.	
Framing of K, L or R																						
Frames in Bridge 'tween Decks		6	3	.42				6	3	.42				3/4	4 1/2							
Frames from Uppermost Continuous Deck		7 1/2	3 1/2	.40	7 1/2	3 1/2	.40	7 1/2	3 1/2	.40	7 1/2	3 1/2	.40	7 1/2	3 1/2	.40	7 1/2	3 1/2	.40	7 1/2	3 1/2	
Framing from Awning, Shelter or Upper Deck to Margin Plate.		No. 1																				
		" 2																				
		" 3	8		.42	8		.42	8		.42	8		.42								
		" 4	9		.42				9		.42											
		" 5			.42						.42											
		" 6	10		.42				10		.42											
		" 7			.42						.42											
		" 8			.42						.42											
		" 9			.42						.42											
		" 10			.42						.42											
		" 11	12	3 1/2	.46	12	3 1/2	.46	12	3 1/2	.46	12	3 1/2	.46	12	3 1/2	.46	12	3 1/2	.46	12	3 1/2
		" 12	15	3 1/2	.46	15	3 1/2	.46	15	3 1/2	.46	15	3 1/2	.46	15	3 1/2	.46	15	3 1/2	.46	15	3 1/2
		" 13			.46			.46			.46						.46			.46		
		" 14			.46			.46			.46						.46			.46		
		" 15			.46			.46			.46						.46			.46		
		" 16			.46			.46			.46						.46			.46		
Spacing of Longitudinal Frames		22 1/2 30			21 1/2 30			22 1/2 30			21 1/2 30											
Double Bottoms L, L or C					7 1/2 3 1/2 .50			7 1/2 3 1/2 .50			7 1/2 3 1/2 .50			7 1/2 3 1/2 .50								
Spacing of Longitudinals					30			30			30			30								
Transverses.																						
In Bridge 'tween Decks		15 .38			15 .38			15 .38			15 .38			15 .38			15 .38					
Face Angles		3 4 .44			3 4 .44			3 4 .44			3 4 .44			3 4 .44			3 4 .44					
Lugs to Shell		3 1/2 3 1/2			3 1/2 3 1/2			3 1/2 3 1/2			3 1/2 3 1/2			3 1/2 3 1/2			3 1/2 3 1/2					
In Awning, Shelter or Upper 'tween Decks.		18 .40			18 .40			18 .40			18 .40			18 .40			18 .40					
Face Angles		3 1/2 4 .44			3 1/2 4 .44			3 1/2 4 .44			3 1/2 4 .44			3 1/2 4 .44			3 1/2 4 .44					
Lugs to Shell		3 1/2 3 1/2			3 1/2 3 1/2			3 1/2 3 1/2			3 1/2 3 1/2			3 1/2 3 1/2			3 1/2 3 1/2					
In Hold.		34 .46			34 .46			34 .46			34 .46			34 .46			34 .46					
Face Angles		4 6 .68			4 6 .68			4 6 .68			4 6 .68			4 6 .68			4 6 .68					
Lugs to Shell		6 6 .50			6 6 .50			6 6 .50			6 6 .50			6 6 .50			6 6 .50					
Brackets		3 4 .44			3 4 .44			3 4 .44			3 4 .44			3 4 .44			3 4 .44					
Spacing of Transverse Frames		9 .6			9 .2 7 .0			9 .6			9 .2 7 .0			9 .6			9 .2 7 .0					
Longitudinal Beams of K, L or C		6 3 .38			6 3 .38			6 3 .38			6 3 .38			6 3 .38			6 3 .38					
Bridge Deck		6 3 .38			6 3 .38			6 3 .38			6 3 .38			6 3 .38			6 3 .38					
Awg. or Shltr. Dk.		7 1/2 3 1/2 .40			7 1/2 3 1/2 .40			7 1/2 3 1/2 .40			7 1/2 3 1/2 .40			7 1/2 3 1/2 .40			7 1/2 3 1/2 .40					
Upper		8 .42			8 .42			8 .42			8 .42			8 .42			8 .42					
Second		8 .42			8 .42			8 .42			8 .42			8 .42			8 .42					
Third		8 .42			8 .42			8 .42			8 .42			8 .42			8 .42					

PARTICULARS FOR RECORD in the REGISTER BOOK.—Length of Poop 107 ft., R.Q.D. ft., Bridge 34.5 ft., Forecastle 33 ft. (in feet and tenths). When the Poop is joined to the B.D., this should be distinctly stated

No. and Material of Decks (if Iron or Steel) and whether wholly or partially covered with wood, and No. of tiers of Beams (this information is to be given as it should appear in the Register Book) 2 DKS (STL) AND WEB FRAMES LONGITUDINAL FRAMING
Official No. 220 864; Signal Letters M.C.B.N. State if Machinery is fitted aft MCHY Aft.
How are the surfaces preserved from oxidation? Inside Paint and Part Cement Outside Paint.

Where Fitted.		Length.	Water Capacity.	Where Fitted.		Length.	Water Capacity.
		Feet.	Tons.			Feet.	Tons.
Double bottom, aft,		64	209	Fore peak tank,		22	229
Double bottom, under Engines and Boilers,				After peak tank,		17.5	130
Double bottom, if under Engines only, Including dwarf Cylinders,				Deep tank, aft,			
Double bottom, if under Boilers only,				Deep tank, forward,			
Double bottom, forward,				Other tanks, if fitted,			
Total capacity of double bottom			209.	(If necessary, furnish further information by sketch.)			

* The wells are not to be included in the lengths of the tanks.

State whether the above have been tested as required by the Rules. Yes

Order for Special Survey No. 41
Date 5.3.18.
No. 24. in builder's yard.

DATES of Surveys held while building
1920—April 9.15; May 7.21; June 1.5.12.15.23.24; July 10.21.30; August 3.10.23; September 21.22.24.28.29; October 2.6.11.14.15.16.20.21.22.25.27.28.29; November 3.10.13.15.20.23.

Surveyor's Signature

Wm Stewart

Lloyd's Register Foundation