

For Scantling Purposes only

# Lloyd's Register of Shipping.

## SURVEYS FOR FREEBOARD.

(COMPUTATION FOR STEAMER, SAILING SHIP, TANKER.)

Index. No. \_\_\_\_\_  
(For London Office only).

Ship's Name <b>Viking</b>	Official Number	Nationality and Port of Registry	Gross Tonnage	Date of Build	Port of Survey
Moulded Dimensions: Length <b>350.0</b> Breadth <b>41.83</b> Depth <b>17.25</b>					Date of Survey <b>18-1-44</b>
Moulded displacement at moulded draught = 85 per cent. of moulded depth					Surveyor's Signature
Coefficient of fineness for use with Tables <b>.68</b>					Particulars of Classification <b>At Sheth's</b> <b>Sheth's</b> <b>For Fresh Water</b>

<b>Depth for Freeboard (D).</b> Moulded depth ... <b>13.25</b> Upper plate ... <b>.03</b> Height on exposed deck $\frac{L-S}{L} =$ Depth for Freeboard (D) = <b>13.28</b>	<b>Depth correction.</b> (a) Where D is greater than Table depth (D - Table depth) R = (b) Where D is less than Table depth (if allowed) (Table depth - D) R = <b>(23.33 - 13.28) × 2.692 = -27.05</b> If restricted by superstructures	<b>Round of Beam correction.</b> Moulded Breadth (B) Standard Round of Beam = $\frac{B \times 12}{50} =$ Ship's Round of Beam = Difference Restricted to Correction = $\frac{\text{Diff}}{4} \times (1 - \frac{S_1}{L}) =$ <b>Nil</b>
--	---	---

## DEDUCTION FOR SUPERSTRUCTURES.

	Mean Covered Length (S)	Equivalent Enclosed Length (S <sub>1</sub> )	Height	Height Correction	Effective Length (E)
enclosed ...					
overhang ...					
enclosed ...					
overhang ...					
enclosed ...					
overhang aft ...					
overhang forward ...					
enclosed ...					
overhang ...					
ft ...					
forward ...					
opening aft ...					
forward					
total ...					

Standard Height of Superstructure **7.00**

" " R.Q.D. **✓**

Deduction for complete superstructure **38.67**

Percentage covered  $\frac{S}{L} =$

" "  $\frac{S_1}{L} =$  **100.00**

" "  $\frac{E}{L} =$

Percentage from Table, Line A.  
(corrected for absence of forecastle (if required))

Percentage from Table, Line B.  
(corrected for absence of forecastle (if required))

Interpolation for bridge less than 2L (if required)

Deduction = **-38.67**

## SHEER CORRECTION.

	Standard Ordinate	S M	Product	Actual Ordinate	Effective Ordinate	S M	Product
...		1				1	
P. ...		4				4	
...		2				2	
...		4				4	
...		2				2	
...		4				4	
...		1				1	

Mean actual sheer aft =

Mean standard sheer aft =

Mean actual sheer forward =

Mean standard sheer forward =

Length of enclosed superstructure forward of amidships =

" " aft of " =

Correction =  $\frac{\text{Difference between sums of products}}{18} \left( \frac{75-S}{2L} \right) =$

deducted on account of midship superstructure.

**-1.00**

If limited to maximum allowance of 1½ ins. per 100 ft.

Correction for Tropical Freeboard.  
Correction for Winter and Winter North Atlantic Freeboard.

Depth to Freeboard Deck = **13.28**

Summer freeboard = **.85**

Moulded draught (d) = **14.13**

Correction for Tropical freeboard and addition for

freeboard =  $\frac{d}{4}$  inches = **3.53**

Winter North Atlantic Freeboard (if required) =

Deduction for Fresh Water.

Displacement in salt water at summer load water line

$\Delta =$

Tons per inch immersion at summer load water line

T =

Deduction =  $\frac{\Delta}{40 T}$  inches

=

TABULAR FREEBOARD corrected for Flush Deck (if required)

Correction for coefficient

	+	-
Depth Correction ...		<b>27.05</b>
Deduction for superstructures ...		<b>38.67</b>
Sheer correction ...		<b>1.00</b>
Round of Beam correction ...		
Correction for Thickness of Deck amidships ...		
Other corrections, scantlings, etc. ...		
	<b>-66.72</b>	<b>-66.72</b>

Summer Freeboard = **10.22**

SUMMER FREEBOARD amidships from Centre of Disc to top of Deck Line, Wood, Steel, Deck:—

Tropical Fresh Water Line above Centre of Disc ...

Fresh Water Line " " ...

Tropical Line " " ...

Winter Line below " " ...

Winter North Atlantic Line " " ...

Tropical Fresh Water Freeboard ...

Fresh Water " " ...

Tropical " " ...

Winter " " ...

Winter North Atlantic " " ...

© 2020

Lloyd's Register Foundation

002138-002150-0090