

Length 175.4
Breadth 27.12

Proportions—Depth to Length—Uppermost continuous deck to top of keel 13.46
Do. Long Bridge to top of keel 10.6

Port of Registry
If surveyed while building,
Building.

TELEGRAPHIC ADDRESS, "REGISTER, GLASGOW."

TELEPHONE: CENTRAL 6490 (4 LINES).



Lloyd's Register of Shipping.

342, Argyle Street, Glasgow, c.2.



17th December, 1930

Sir,

I beg to acquaint you that the S.S. "WALLACE ROSE", No.93063 in the Register Book, has arrived here to have her machinery fitted, and I shall be glad to be informed, for the information of the Surveyors, what remains to be done to complete the survey for classification.

I am, Sir,

Your obedient servant,

J. L. Warlow

Secretary to the
Glasgow Committee.

The Secretary,

LONDON.

DOUBLE BOTTOM.

Solid Floors, thickness and spacing 18 x 22

" " Are Frame and Reversed Frame joggled? not joggled.

Bracket Floors, breadth and thickness at

Spacing

Bridge Deck, Angle, E or F

Spacing

INCHES

amidships 30

angle 3

angle 3

ness one

(e) and 24

nk side 16

n. from 16

cantling none

tem. 20 x 20

base line 37

thickness

stake 54

garding double Yes

ning in

midships 5

e, Angle, 5

or 1

1

1

1

1

1

1

1


1

1

1

1

4 1/2



© 2020

002188-002150-0108

Lloyd's Register
Foundation

Referred to the Chief Ship Surveyor,
and the Chief Engineer Surveyor.

18 DEC 1930

WKS

OFF, reduced and

© 2020

Lloyd's Register
Foundation

REGISTERED

Length

Breadth

Depth

FRAMES, Space

"

"

SIDE FRAMING

Frame Amidst

"

Reversed Fra

"

Depth of Fra

Frames in Up

" See

" Th

Framing in P
Diameter and

State if Fram

PANTING ARR

STRENGTHEN
WARD. Se

SINGLE BOTT
Floors, Deph

Height base

Middle Line

"

"

"

Side Keelsons

"

"

DOUBLE BOTT

Solid Floors,

"

Bracket Floo