

REPORT ON ELECTRIC FITTINGS.

(OTHER THAN FOR THE PROPULSION OF THE VESSEL)

-1 MAR 1933

Date of writing Report 27/2/ 1933 When handed in at Local Office 28/2/ 1933 Port of Leith

No. in Survey held at Burntisland Date, First Survey 13/1/33 Last Survey 27/2/ 1933
Reg. Book.77416 on the LONDON QUEEN Tons { Gross 781
Net 429

Built at BURNTISLAND By whom built THE BURNTISLAND SHIPBUILDING CO. LTD. Yard No. 174 When built 1933

Owners THE LONDON & CHANNEL ISLANDS STEAMSHIP CO. LTD. Port belonging to LONDON.

Electric Light Installation fitted by THE BURNTISLAND SHIPBUILDING CO. LTD. Contract No. 174 When fitted 1933

Is the Vessel fitted for carrying Petroleum in bulk No.

System of Distribution **TWO WIRE.**

Pressure of supply for Lighting 110 volts, Heating — volts, Power — volts.

Direct or Alternating Current, Lighting **DIRECT CURRENT** Power —

If alternating current system, state frequency of periods per second

Has the Automatic Governor been tested and found efficient when the whole load is suddenly thrown on or off **YES**

Generators, do they comply with the requirements regarding rating **YES**, are they compound wound **YES**
are they over compounded 5 per cent. **YES**, if not compound wound state distance between each generator —

Where more than one generator is fitted are they arranged to run in parallel —, is an adjustable regulating resistance fitted in series with each shunt field **YES**

Are all terminals accessible, clearly marked, and furnished with sockets **YES**, are they so spaced or shielded that they cannot be accidentally earthed, short circuited, or touched **YES** Are the lubricating arrangements of the generators as per Rule **YES**

Position of Generators **STARBOARD SIDE OF ENGINE ROOM.**
is the ventilation in way of the generators satisfactory **YES**, are they clear of all inflammable material **YES**
if situated near unprotected woodwork or other combustible material, state distance of same horizontally from or vertically above the generators **3 FEET** and —, are the generators protected from mechanical injury and damage from water, steam or oil **YES**
are their axes of rotation fore and aft **YES**

Earthing, are the bedplates and frames of the generating plant efficiently earthed **BOLTED DIRECT TO EARTH.** are the prime movers and their respective generators in metallic contact **YES**

Main Switch Boards, where placed **STARBOARD SIDE OF ENGINE ROOM.**
If the generators and main switchboard are not placed in the same compartment, is each generator provided with a fuse on each insulated pole as near as possible to the terminals of the generator, additional to that provided on the main switchboard

Switchboards, are they placed in accessible positions, free from inflammable gases and acid fumes **YES**
are they protected from mechanical injury and damage from water, steam or oil **YES**, if situated near unprotected woodwork or other combustible material, state distance of same horizontally from or vertically above the switchboards **6 FEET** and —
are they constructed wholly of durable, non-ignitable non-absorbent materials **YES**, is all insulation of high dielectric strength and of permanently high insulation resistance **YES**, if semi-insulating material is used, are all conducting parts insulated from the slab with mica or micanite or other non-hygroscopic insulating material, and the slab similarly insulated from its framework
and is the frame effectively earthed **YES** Are the fittings as per Rule regarding: — spacing or shielding of live parts **YES**, accessibility of all parts **YES**, absence of fuses on back of board **YES**, proportion of omnibus bars **YES**, individual fuses to voltmeter, pilot or earth lamp **YES**, connections of switches **YES**

Main Switchgear, description of switchgear for each generator and each outgoing circuit, and arrangement of equalizer switches **DOUBLE POLE MAIN SWITCH (KNIFE TYPE) AND SINGLE POLE CIRCUIT SWITCHES (KNIFE TYPE) FOR OUTGOING CIRCUITS.**

Instruments on main switchboard 1 ammeter 1 voltmeter — synchronising device for paralleling purposes.

Earth Testing, state what means are provided at the main switchboard for indicating the state of the insulation of the system **TWO EARTH LAMPS**

Switches, Circuit Breakers and Fusible Cut-outs, do these comply with the requirements of the Rules **YES**Joint Boxes Section and Distribution Boards, is the construction, protection, insulation, material, and position of these as per rule **YES**

Cables: Single, twin, concentric, or multicore TWIN are the cables insulated and protected as per Tables IV or V of the Rules YES

Fall of Pressure, state maximum between bus bars and any point of the installation under maximum load 3 VOLTS

Cable Sockets and other connections, are the ends of all cables having a sectional area of 0.04 square inch and above provided with soldering sockets YES

Paper Insulated Cables. If cables are paper covered, is the dielectric at the exposed ends of the conductor protected from moisture by being suitably sealed with insulating compound YES

Cable Runs, are the cables fixed as far as possible in accessible positions not exposed to drip or accumulation of water or oil, or to high temperature from boilers, steam pipes, uptakes or other hot objects, or to avoidable risk of mechanical damage YES

Support and Protection of Cables, state how the cables are supported and protected STEEL WIRE ARMoured AND CLIPPED UP TO THE DECK.

If cables are run in wood casings, are the casings and caps secured by screws YES, are the cap screws of brass YES, are the cables run in separate grooves YES. If armoured and lead covered cables are secured by metal clips, are the clips spaced as per Table VIII YES

Refrigerated Chambers, if lights are fitted, are the cables and fittings in accordance with the special requirements YES

Joints in Cables, state if any, and how made, insulated, and protected YES

Watertight Glands and Deck Tubes, are all cables passing through decks and watertight bulkheads provided with deck tubes or watertight glands YES

Bushes in Beams and Non-watertight Partitions, where unarmoured cables pass through beams and non-watertight partitions, are the holes efficiently bushed YES state the material of which the bushes are made LEAD TAPE

Earthing Connections, state what earthing connections are fitted and their respective sectional areas SWITCH BOARD FRAME AND GENERATOR BEDPLATE BOLTED DIRECT TO EARTH.

are their connections made as per Rule YES

Alternative Lighting, are the groups of lights in the propelling machinery space arranged as per Rule YES

Emergency Supply, state position and method of control of the emergency supply and how the generator is driven YES

Navigation Lamps, are these separately wired YES, controlled by separate switch and separate fuses YES, are the fuses double pole YES, are the switches and fuses grouped in a position accessible only to the officers on watch YES, has each navigation lamp an automatic indicator as per Rule YES

Secondary Batteries, are they constructed and fitted as per Rule YES

Fittings, are all fittings on weather decks, in stokeholds and engine rooms and wherever exposed to drip or condensed moisture, watertight YES, are any fittings placed in spaces in which goods are liable to be stacked in close proximity to them; if so, how are they protected YES, are any fittings placed in spaces where inflammable or explosive dust or gases are liable to be present, if so, how are they protected YES, how are the cables led YES, where are the controlling switches situated YES

Searchlight Lamps, No. of YES, whether fixed or portable YES, are their fittings as per Rule YES

Arc Lamps, other than searchlight lamps, No. of YES, are their live parts insulated from the frame or case YES, are their fittings as per Rule YES

Motors, are their working parts readily accessible YES, are the coils self-contained and readily removable for replacement YES, are the brushes, brush holders, terminals and lubricating arrangements as per Rule YES, are the motors placed in well-ventilated compartments in which inflammable gases cannot accumulate and clear of all inflammable material YES, are they protected from mechanical injury and damage from water, steam or oil YES, are their axes of rotation fore and aft YES, if situated near unprotected woodwork or other combustible material, are the motors of the totally enclosed, pipe ventilated, forced draught, drip or flame proof type YES, if not of this type, state distance of the combustible material horizontally or vertically above the motors YES and YES

Control Gear and Resistances, are the generator field and motor speed regulators, starters and controllers constructed and fitted as per Rule YES

Lightning Conductors, where lightning conductors are required, are these fitted as per Rule YES

Ships carrying Oil having a Flash Point less than 150° F. Have the special requirements of the Rules been complied with regarding switches, joint boxes, section and distribution boards, protection of cables, method of distribution, lead of cables, lights and fittings YES

If portable lamps for use in dangerous spaces are supplied, are they of a type approved by the Home Office YES

PARTICULARS OF GENERATING PLANT.									
DESCRIPTION OF GENERATOR.	No. of	RATED AT				DRIVEN BY	WHERE DRIVEN BY AN INTERNAL COMBUSTION ENGINE.		
		Kilowatts.	Volts.	Ampères.	Revs. per Min.		Fuel Used.	Flash Point of Fuel.	
MAIN	1	3	110	27	475	OPEN TYPE ENGINE.			
AUXILIARY									
EMERGENCY									
ROTARY TRANSFORMER									

GENERATOR, LIGHTING AND HEATING CONDUCTORS.									
DESCRIPTION.	CONDUCTORS.		COMPOSITION OF STRAND.		TOTAL MAXIMUM CURRENT. AMPERES.		Approximate Length. (Lead and Return.) Feet.	Insulated with	HOW PROTECTED.
	No. per Pole.	Total Effective Area per Pole Sq. Ins.	No.	Diameter.	In Circuit.	Rule.			
MAIN GENERATOR	1	.0225	7	.064		46	13	RUBBER	L.C. & W.A.
EQUALISER CONNECTIONS									
AUXILIARY GENERATOR...									
EMERGENCY GENERATOR									
ROTARY TRANSFORMER } MOTOR GENERATOR...									
ENGINE ROOM... ..	1	.0045	7	.029	3.5		15	RUBBER	L.C. & W.A.
BOILER ROOM... ..									
AUXILIARY SWITCHBOARDS									
ACCOMMODATION									
SALOON	1	.0070	7	.036	6.5		124	RUBBER	WIRE ARMOUR
ENGINEER'S ACCON.	1	.0030	3	.036	3.0		39	"	"
NAVIGATION.	1	.0030	3	.036	3.3		144	"	"
WIRELESS									
SEARCHLIGHT									
MASTHEAD LIGHT	1	.0020	3	.029	.36		35	"	"
SIDE LIGHTS	1	.0020	3	.029	.36		30	RUBBER	LEAD COVERED.
COMPASS LIGHTS	1	.0020	3	.029	.18		10	"	"
POOP LIGHTS									
CARGO LIGHTS	1	.0020	3	.029	1.5		30	RUBBER	L.C. & W.A.
ARC LAMPS									
HEATERS									

MOTOR CONDUCTORS.										
DESCRIPTION.	No. of Motors.	CONDUCTORS.		COMPOSITION OF STRAND.		TOTAL MAXIMUM CURRENT. AMPERES.		Approximate Length. (Lead and Return.) Feet.	Insulated with	HOW PROTECTED.
		No. Per Pole.	Total Effective Area per Pole Sq. Ins.	No.	Diameter.	In Circuit.	Rule.			
BALLAST PUMP										
MAIN BILGE LINE PUMPS										
GENERAL SERVICE PUMP										
EMERGENCY BILGE PUMP										
SANITARY PUMP										
CIRC. SEA WATER PUMPS										
CIRC. FRESH WATER PUMPS...										
AIR COMPRESSOR										
FRESH WATER PUMP										
ENGINE TURNING GEAR...										
ENGINE REVERSING GEAR										
LUBRICATING OIL PUMPS										
OIL FUEL TRANSFER PUMP...										
WINDLASS										
WINCHES, FORWARD										
WINCHES, AFT										
STEERING GEAR—										
(a) MOTOR GENERATOR...										
(b) MAIN MOTOR										
WORKSHOP MOTOR										
VENTILATING FANS										

All Conductors are of annealed copper conforming to British Standard Specification No. 7.

The Insulated Conductors are guaranteed to withstand the immersion and resistance tests specified in the Rules.

The foregoing is a correct description.

FOR THE BURNTISLAND SHIPBUILDING COMPANY LTD.

A. L. H. H.
MANAGING DIRECTOR.

Electrical Engineers.

Date 27-2-33.

COMPASSES.

Distance between electric generators or motors and standard compass

104 FEET

Distance between electric generators or motors and steering compass

The nearest cables to the compasses are as follows:—

A cable carrying 18 Ampères 12" feet from standard compass — feet from steering compass.

A cable carrying Ampères feet from standard compass feet from steering compass.

A cable carrying Ampères feet from standard compass feet from steering compass.

Have the compasses been adjusted with and without the electric installation at work at full power YES

Has the effect of switching on and off circuits, motors and other electro-magnetic apparatus within the vicinity of the compasses been noted YES

The maximum deviation due to electric currents was found to be NIL degrees on ANY course in the case of the standard compass, and — degrees on — course in the case of the steering compass.

FOR THE BURNTISLAND SHIPBUILDING COMPANY LTD.

A. L. H. H.
MANAGING DIRECTOR.

Builder's Signature.

Date 27-2-33.

Is this installation a duplicate of a previous case No If so, state name of vessel ✓

General Remarks (State quality of workmanship, opinions as to class, &c.)

This installation has been efficiently fitted on board in accordance with the rules. The materials & workmanship are sound & good & the installation was found satisfactory under full load & working conditions.

It is submitted that
this vessel is eligible for
THE RECORD.

Elec. Light

27/2/33

Total Capacity of Generators 2½ Kilowatts.

The amount of Fee ... £ 5 : 0 : 0 When applied for, 28-2-19-33.

Travelling Expenses (if any) £ : : When received, 18-3-19-33.

Chas. R. Rouchiffe

Surveyor to Lloyd's Register of Shipping.

Committee's Minute

Assigned

Elec. Light



© 2020

Lloyd's Register
Foundation