

Do all the Frames extend to the top height in the Poop? Raised Quarter Deck? *Yes.* Bridge House? *Yes.*
 To what height do the Reverse Frames extend? *Bulb angle frames.*
 Has the Poop or Raised Quarter Deck an efficient Iron Bulkhead at the fore end? *yes*
 Give particulars of the means for closing the openings in Bulkhead *none*
 Is the Poop or Raised Quarter Deck connected with the Bridge House? *yes* Has the Bridge House an efficient Bulkhead? *yes*
 Give particulars of the means for closing the openings in Bulkhead *none*
 What is the thickness of the Bridge Front plating? *.26* and Coaming plate? *.30*
 Give scantlings and spacing of the Stiffeners *7x3x40 B.A. spaced 30" apart.*
 Are bracket plates fitted at each end of the Stiffeners? *Stiffeners lagged.* Are hor'l. brackets fitted connecting Bridge B...
 Has the Bridge House an efficient Iron Bulkhead at the after end? *yes*
 How are the openings closed? *none*
 Is the Forecastle at least as high as the main or top-gallant rail? *yes.* Has the Forecastle an efficient Iron Bulkhead? *yes.*
 Are the Engine and Boiler openings covered by a Bridge, Poop, Raised Quarter Deck, or enclosed by a Strong Iron or Steel Deckhouse? *yes.*
 If the openings are not so protected are the exposed parts of the Casings efficiently constructed?
 Give thickness of plating; scantlings and spacing of Stiffeners *Coaming .30. Plating .25. Stiffeners 7x3x40 B.A. spaced 30" apart.*
 What is the height of the exposed Casings? *6'-9"* Are suitable means provided for closing all openings in the Casings?
 Are the Weather Deck Hatchways efficiently constructed and at least equal to the requirements of Section 28 of the Rules for 1904-5? Give particulars below:—

Position and Size.	No. 1. MAIN DECK.		No. 2 Q. DECK.		Ship.	Rule.	Ship.	Rule.	Ship.	Rule.	Ship.	Rule.
	Ship.	Rule.	Ship.	Rule.								
COAMING.												
Height above top of DECK	34'-10"	16'-0"	34'-10"	16'-0"								
Thickness	Sides	.45	.44	.45	.44							
	Ends	.45	.44	.45	.44							
SHIFTING BEAMS OR WEB PLATES.	Number	7	as appd	7	as appd							
	Section and Scantlings	14x34 PIT.	"	14x34 PIT.	"							
	Material	4x3x40 L.	"	4x3x40 L.	"							
* FORE AND AFTERS.	Number											
	Section and Scantlings											
	Material											
HATCHES Thickness	2 1/2"	- do -	2 1/2"	- do -								
Remarks												

* When the Fore and Afters are of wood the depth should be stated from the underside of the hatches.



(If the sill of the lowest side scuttle will be less than 6 inches above the Indian Summer Load Line if assigned under the tables, state vertical distance from top of deck at side amidships to lower edge of lowest side scuttle.)

The following information is to be given in all Cases of vessels dealt with under Paras. 11, 12 (under 15 feet Moulded depth) and under Shelter Deck Rules.

What is the thickness of the Bridge Sheerstrake? *.30* Strake between Main and Bridge Sheerstrakes? *.30 & .50 at break.*

Delete the words { The Crew are, ~~berthed~~, berthed in the bridge house.
 that do not apply { The arrangements to enable them to get backwards and forwards from their quarters are, ~~satisfactory~~.

Length of Bulwarks in well *44'-6"*
 Area of Freeing Ports required by Para. 11 (e) each side of vessel = *11.0* Sq. ft.
 Ft. Tenths. Ft. Tenths. No. } Freeing Ports (each side of vessel) = *11.97* Sq. ft.
 $2.66 \times 1.5 \times 3$
 Total deficiency or excess = *1.02* Sq. ft.
 $11.0 - 11.97 = 1.02$



Show hereon line of Floors or Tank Top with position of any Breaks in same; also height of Peak

State any special features in the construction of the Vessel

The approved plan of Mid & Longitudinal forwarded herewith. Freeboard request

Owners

Address

Fee £ 2 : 2 : 0

Received by me

13/12/1911



© 2020

Lloyd's Register Foundation