

without T.O

Lloyd's Register of Shipping

SURVEYS AND FREEBOARD

Computation of Freeboard for Steamer, Sailing Ship, Tanker

Port of Survey

(Type of Superstructures.)

Date of Survey

Ship's Name

Nationality and Port of Registry

Official Number

Gross Tonnage

Date of Build

Name of Surveyor

Moulded Dimensions: Length

Breadth

Depth

Moulded displacement at moulded draught = 85 per cent. of moulded depth

tons

Coefficient of fineness for use with Tables

Particulars of Classification

Depth for Freeboard (D)

Moulded depth 14.25

Stringer plate 0.04

Sheathing on exposed deck

$$T \left(\frac{L-S}{L} \right) =$$

Depth for Freeboard (D) =

Depth correction

(a) Where D is greater than Table depth
(D-Table depth) R =

(b) Where D is less than Table depth (if allowed)
(Table depth-D) R =

If restricted by superstructures

Round of Beam correction

Moulded Breadth (B)

$$\text{Standard Round of Beam} = \frac{B \times 12}{50} =$$

Ship's Round of Beam =

Difference

Restricted to

$$\text{Correction} = \frac{\text{Diff}^{\circ}}{4} \times \left(1 - \frac{S_1}{L} \right) =$$

DEDUCTION FOR SUPERSTRUCTURES.

	Mean Covered Length (S)	Equivalent Enclosed Length (S ₁)	Height	Height Correction	Effective Length (E)
Poop enclosed					
„ overhang					
R.Q.D. enclosed					
„ overhang					
Bridge enclosed					
„ overhang aft					
„ overhang forward					
F'cle enclosed					
„ overhang					
Trunk aft					
„ forward					
Tonnage opening aft					
„ „ forward					
Total					

Standard Height of Superstructure

„ „ R.Q.D.

Deduction for complete superstructure

Percentage covered $\frac{S}{L} =$

„ „ $\frac{S_1}{L} =$

„ „ $\frac{E}{L} =$

Percentage from Table, Line A.

(corrected for absence of forecastle (if required))

Percentage from Table, Line B.

(corrected for absence of forecastle (if required))

Interpolation for bridge less than 2L (if required)

Deduction =

SHEER CORRECTION.

Station	Standard Ordinate	S M	Product	Actual Ordinate	Effective Ordinate	S M	Product
P.		1		+18		1	
„ from A.P.		4				4	
„ „		2				2	
amidships		4				4	
„ from F.P.		2				2	
„ „		4				4	
P.		1				1	
Total				+18			

$$\text{Correction} = \frac{\text{Difference between sums of products}}{18} \left(.75 - \frac{S}{2L} \right) =$$

If limited on account of midship superstructure.

If limited to maximum allowance of 1½ ins. per 100 ft.

Deduction for Tropical Freeboard.

Addition for Winter and Winter North Atlantic Freeboard.

Depth to Freeboard Deck = 14.29
Summer freeboard = +.17
Moulded draught (d) = 14.46

Deduction for Tropical freeboard and addition for

Winter freeboard = $\frac{d}{4}$ inches =

Addition for Winter North Atlantic Freeboard (if required) =

Deduction for Fresh Water.

Displacement in salt water at summer load water line

Δ =

Tons per inch immersion at summer load water line

T =

$$\text{Deduction} = \frac{\Delta}{40 T} \text{ inches}$$

TABULAR FREEBOARD corrected for Flush Deck (if required)

Correction for coefficient

Depth Correction
Deduction for superstructures
Sheer correction
Round of Beam correction
Correction for Thickness of Deck amidships
Other corrections, scantlings, etc.

Summer Freeboard =

SUMMER FREEBOARD amidships from Centre of Disc to top of Deck Line, Wood, Steel, Deck:-

Tropical Fresh Water Line above Centre of Disc
Fresh Water Line „ „
Tropical Line „ „
Winter Line below „ „
Winter North Atlantic Line „ „

Tropical Fresh Water Freeboard
Fresh Water „ „
Tropical „ „
Winter „ „
Winter North Atlantic „ „

Summer Mld. Draught = 14'-5 1/2"