

22 AUG 1925

Index No. **31800**
(For London Office only.)

Lloyd's Register of Shipping.

SURVEYS FOR FREEBOARD.—STEAM SHIPS.

PARTICULARS RELATING TO ALL STEAM SHIPS EITHER FLUSH DECKED, OR WITH TOP GALLANT FORECASTLES, SHORT POOPS AND BRIDGE HOUSES DISCONNECTED, OR WITH TOP GALLANT FORECASTLES HAVING LONG POOPS, OR RAISED QUARTER DECKS CONNECTED WITH BRIDGE HOUSES, OR OTHERWISE.

Port of Survey WEST HARTLEPOOLDate of Survey DURING CONSTRUCTIONName of Surveyor THOMAS. E. SOWDEN

Ship's Name.

SS. KIWITEANumber in Register Book **39658**

Port of Registry and Nationality.

**WELLINGTON
BRITISH.**

Official Number.

151597

Gross Tonnage.

✓

Date of Build.

1925

Particulars of Classification.

**+100 A1
CLASS CONTEMPLATED.
(Revised Rules)**

Registered dimensions from Ship's Register.	LENGTH.	BREADTH.	DEPTH.	UNDER DECK TONNAGE.
	280.0	44.3	18.9	1949.15
Length on LOADLINE.	280.0	Frame Depth 7 Ceiling FITTED Peak Rule „ 5 Sheer +24 Tanks INC'D 2x2 72 = .33 To Tanks 19.08 SPARRING FITTED Top Rise Aft = 11		
CORRECTED DIMENSIONS.	280.0	43.97	19.14	1960.15 1961.09

Co-efficient of fineness.....

.88 .824Any modification necessary }
[Para. 4 (a) to (e)]***.02 C.D.B.
.81 .80**

Co-efficient as corrected

Sheer { Stem..... **60** } **93** ÷ 2 = **46.5**...Mean
at { Sternpost ... **33** }Sheer at $\frac{1}{8}$ of the length from { Stem **33** } **51.4** ÷ 2 = **25.62**...Mean
Sternpost **18.4** ÷ 55 = **46.59**Gradual mean Sheer **46.55**Standard mean Sheer [Table, Para. 18] **38.00** CorrectionDifference..... **8.55** ÷ 4 = **2.14**§ If limited as Para. 18 (f) **- 2.14**Rise in Sheer { At front of bridge house..... ✓
from amidships [Para. 18 (e)] { At after end of forecastle ✓Fall in Sheer }
Para. 18 (d) } ÷ 2 =

Length uncovered Correction

ALLOWANCE FOR DECK ERECTIONS :—

Freeboard, Table C.....	1'-8 7/4
Correction for Length, if required (Para. 12, 13, and 14)	+ 1'-0 1/2
Freeboard by Table A, corrected for sheer, and for length, if required (Para. 12, 13, and 14) }	4'-4 1/2
Difference	2'-7 1/4
Percentage as below.....	33.04
	10.33

Correction for R. Q. Dk. if engine and boiler openings not covered by bridge house (Para. 11) ✓

Allowance for Deck Erections **-10 1/4 10.3**

	Length.	Length allowed.	Height.
Forecastle.....	29-4 1/2	29.37 ✓	7-6
Bridge House TRUNK I 144 x 246 x 24 x 8 528 x 144		29.27 ✓	2-9
† Raised Qr. Dk TRUNK II 26 x 246 x 20 1/4 x 8 528 x 144		4.50 ✓	2-9
Poop.....	80-7 1/2	80.62 ✓	7-6
Total	280.0	143.76	= 513
Length of Ship		280.0	
Corresponding percentage } (Para. 11, 12, 13, and 14)			33.04%

FREEBOARD recommended amidships from centre of Disc to top of Statutory Deck Line, **W** (Steel) Deck :—

Fresh Water Line	above centre of Disc
Indian Summer Line	„	„	„	„	„	„	„	„	...
Winter Line	below	„	„	„	„	„	„	„	...
Winter North Atlantic Line	„	„	„	„	„	„	„	„	...

24 AUG 1925

Moulded Depth as measured..... **21-1 1/2**Addition for Keel below base line for draught record..... **1 1/2** inches.

CORRECTION FOR LENGTH.

Length of Ship on Loadline.....	280 ✓
Length in Table	253.5 ✓
Difference	26.5 ✓
Correction for 10ft., Table A.	1.2 Table C. .6
× Difference divided by 10	3.18 (if required.) 1.59 ✓
If $\frac{1}{10}$ ths length covered divide by 2	+ 3 1/4 ✓ + 1 1/2 ✓

CORRECTION FOR IRON DECK.

Proportion covered, if less than $\frac{1}{10}$ ths length covered ✓
Thickness of usual wood deck, less stringer **3 1/2** ✓

CORRECTION FOR ROUND OF BEAM.

Breadth at Gunwale amidships.....	44 ✓
Round of Beam	11 ✓
Normal round.....	11 ✓
Difference	✓ ÷ 2 =
Proportion of Deck uncovered (Para. 19)	✓

Freeboard, Table A	4'-3 1/2
Correction for Sheer	- 2 1/4
Correction for Length	4'-1 1/4
Allowance for Deck Erections	+ 3 1/4
Correction for Round of Beam.....	4'-4 1/2
Correction for fall in Sheer (if any).....	- 10 1/4
Correction for Iron Deck (if required)	3'-6 1/4
Additions for non-compliance with provisions of } Para. 11 (d) and (e) †	- 3 1/2
Other Corrections (if any)	3'-3 2 3/4

Winter Freeboard	3'-3 2 3/4
Summer Freeboard (2 1/2 to 3 1/2).....	2'-0 11 3/4
Indian Summer Freeboard	2'-0 8 3/4
N. A. Winter Freeboard	3'-5 1/4

Correction necessary because clearside amidships, measured in accordance with the Statute is not taken at the intersection of the ~~wood~~ steel deck with side. **1 3/4** ✓

Winter Freeboard from deck line	3'-4 1/2
Summer „ „ „ „	3'-1 1/2
Indian Summer „ „ „ „	2'-10 1/2
N. A. Winter „ „ „ „	3'-8 1/2

Winter Freeboard from deck line **3-1 1/2** ✓

Fresh Water Line	above centre of Disc
Indian Summer Line	„	„	„	„	„	„	„	„	...
Winter Line	below	„	„	„	„	„	„	„	...
Winter North Atlantic Line	„	„	„	„	„	„	„	„	...

† State dimensions of freeing port area on back of this form.

The Surveyor should state whether the fall in sheer as reported is measured relatively to the draught line of keel or to the water line. If measured relatively to water line the vessel's draught at time of survey, and also the usual load draft forward and aft should be reported.

† If the frames, skin planking, or ceiling are of unusual thickness the breadth of vessel to inside of ceiling should be reported if possible.
† In vessels obtaining an allowance for deck erections under Para. 11 where the sheer drops abaft amidships the height of the R.Q.D. is to be taken from the level of the top of the amidship beam.
§ In flush-decked vessels the total standard mean sheer means the sheer measured at the stem and sternpost. In vessels having poops and forecastles, it means the sheer measured at points distant $\frac{1}{8}$ of the vessel's length from stem and sternpost.

2020
Lloyd's Register
Foundation
RECEIVED

8610-002268-0198

Do all the Frames extend to the top height in the Poop? Yes Raised Quarter Deck? ✓ Bridge House? ✓ Forecastle? ✓

To what height do the Reverse Frames extend? B.A. FRAMING

Has the Poop or Raised Quarter Deck an efficient Iron Bulkhead at the fore end? Yes

Give particulars of the means for closing the openings in Bulkhead SHIFTING BOARDS FULL HEIGHT IN QUATER CHANNELS

Is the Poop or Raised Quarter Deck connected with the Bridge House? ✓ Has the Bridge House an efficient Bulkhead at the fore end? ✓

Give particulars of the means for closing the openings in Bulkhead ✓

What is the thickness of the Bridge Front plating? ✓ and Coaming plate? ✓

Give scantlings and spacing of the Stiffeners ✓

Are bracket plates fitted at each end of the Stiffeners? ✓ Are hor'l. brackets fitted connecting Bridge Bulk'd. with Bulwarks? ✓

Has the Bridge House an efficient Iron Bulkhead at the after end? ✓

How are the openings closed? ✓

Is the Forecastle at least as high as the main or top-gallant rail? Yes Has the Forecastle an efficient Iron or Wood Bulk'd. at after end? Yes

Are the Engine and Boiler openings covered by a Brill Poop, Brill } Yes
 Quarter Deck, or enclosed by a Strong Iron or Steel Deckhouse?

If the openings are not so protected are the exposed parts of the Casings efficiently constructed? ✓

Give thickness of plating; scantlings and spacing of Stiffeners ✓

What is the height of the exposed Casings? ✓ Are suitable means provided for closing all openings in them in bad weather? Yes

Are the Weather Deck Hatchways efficiently constructed and at least equal to the } AS APPROVED.
 requirements of Section 28 of the Rules for 1904-5? Give particulars below:—

Position and Size.	No. 1 Tr. D. 19' 4 1/2" x 18'		No. 2 Tr. D. 18' x 24"		No. 3 D.		No. 4 D.		No. 5 D.	
Item.	Ship.	Rule.	Ship.	Rule.	Ship.	Rule.	Ship.	Rule.	Ship.	Rule.
COAMING. Height above top of DECK	30"		30"		30"		30"		30"	
Thickness { Sides.....	4 1/2"		4 1/2"		4 1/2"		4 1/2"		4 1/2"	
{ Ends.....	4 1/2"		4 1/2"		4 1/2"		4 1/2"		4 1/2"	
SHIFTING BEAMS OR WEB PLATES. Number										
{ Section and Scantlings										
{ Material										
* FORE AND AFTERS. Number										
{ Section and Scantlings										
{ Material										
HATCHES Thickness										
Remarks.....										

* The depth of Fore and Afters should be stated from the underside of the hatches in all cases.

(If the sill of the lowest side scuttle will be less than 6 inches above the Indian Summer Load Line if assigned under the tables, state vertical distance from top of deck at side amidships to lower edge of lowest side scuttle.)

The following information is to be given in all Cases of vessels dealt with under Paras. 11, 12 (under 15 feet Moulded depth) and under Shelter Deck Rules.

What is the thickness of the Bridge Sheerstrake? ✓ Strake between Main and Bridge Sheerstrakes? ✓


Delete the words { The Crew are, are not, berthed in the bridge house.
 that do not apply { The arrangements to enable them to get backwards and forwards from their quarters are, are not satisfactory.

Length of Bulwarks in well 170' x 4' = 680

Area of Freeing Ports required by Para. 11 (e) each side of vessel = AS APPROVED Sq. ft.

Ft. Tenths. Ft. Tenths. No. } Freeing Ports = SEE LETTER M. N. 25-3-25
2.87 x 1.83 x 6 } (each side of vessel)

Total deficiency or excess = ✓ Sq. ft.



Show hereon line of Floors or Tank Top with position of any Breaks in same; also height of Peak Tank tops, &c., &c.

State any special features in the construction of the Vessel Self trimming Collier; Trunk deck; Machinery etc.

Builder's name and yard number Messrs. W. Gray & Co. No. 975 (Copies of approved plans are in London office)

Names of sister vessels SS 'KARTIE' " " No. 974

Owners The Union Steamship Co. of New Zealand.

" Address ✓

Fee £ 7 : 0 : 0

To be applied for with J. E. Form. Received by me See J. E. Report



© 2020

Lloyd's Register Foundation