

pt. 11b.  
9610  
WRITTEN

REG NEW YORK JUN 25 1921

# Lloyd's Register of Shipping.

SURVEYS FOR FREEBOARD.—STEAM SHIPS.

TUE JUL 12 1921

Index No. 30071  
(For London Office only.)

1490

Particulars relating to all steam ships either flush decked, or with top gallant forecastles, short poops and bridge houses disconnected, or with two gallant forecastles having long poops, or raised quarter decks connected with bridge houses, or otherwise.

Port of Survey

Boston

Date of Survey

While Building

Name of Surveyor

Wm Stewart

| Ship's Name                                 | Port of Registry and Nationality. | Official Number. | Gross Tonnage. | Date of Build.      | Particulars of Classification.          |
|---|-----------------------------------|------------------|----------------|---------------------|---|
| S.S. ILLINOIS<br>TEXAS S.S. G. #31          | Baltic Arthur<br>U. S. A.         | 221400           | 6702           | 1921                | + 100 A1.<br>Carrying Petroleum in Bulk |
| Number in Register Book                     |                                   |                  |                |                     |   |
| Registered dimensions from Ship's Register. | LENGTH.                           | BREADTH.         | DEPTH.         | UNDER DECK TONNAGE. |   |
|   | 416.8                             | 56.1             | 32.7           | 6117.11             |   |
| Length on LOADLINE.                         | Average                           | Frame Depth 9.2  | Ceiling + 20'  | Peak } not included |   |
|   | 415.                              | Rule .....       | 6.5            | Sheer + 51'         |   |
|   |                                   |                  | 2.7            | Tanks } 113.57      |   |
|   |                                   |                  |                | C.D.B. 846.7.1.48   |   |
| RECTED DIMENSIONS.                          | 2x2.7 = .45                       | ho sparring + 33 |                |                     |   |
|   | 415.                              | 55.98            | 33.41          | 6302.16             |   |

NOTE.—If the depth is measured when vessel is afloat, the details of measurement should be reported.

o-efficient of fineness..... 81 ✓  
Any modification necessary { Para. 4 (a) to (e)\* } ✓  
o-efficient as corrected ..... 81 ✓

Sheer { Stem ..... 98 } 148 ÷ 2 = 74 Mean 70.9  
at Sternpost ..... 50 36 18.5  
Sheer at  $\frac{1}{2}$  of the length from { Stem ..... 54 } 77 ÷ 2 = 38.5 Mean 57.5  
Sternpost ..... 23 36 18.5  
Gradual mean Sheer ..... Allowing 70 - ÷ 55 = 70  
Standard mean Sheer [Table, Para. 18] ..... 51.5 Correction 51.5  
Difference ..... 18.5 ÷ 4 = 4.625  
If limited as Para. 18 (f) ..... - 4 3/4

Rise in Sheer { At front of bridge house ..... Gradual Sheer  
from amidships } At after end of forecastle ..... 48

Fall in Sheer { Para. 18 (d) } ÷ 2 =  
Length uncovered ..... Covered by bridge Correction

ALLOWANCE FOR DECK ERECTIONS :—  
Freeboard, Table C ..... 5 - 4.66  
Correction for Length, if required (Para. 12, 13, and 14) ..... 1.68  
Freeboard by Table A, corrected for sheer, and for length, if required (Para. 12, 13, and 14) ..... 5 - 9.34  
Difference ..... 3 - 0.56  
Percentage as below..... 26.49%

Correction for R. Q. Dk. if engine and boiler openings not covered by bridge house (Para. 11)

Allowance for Deck Erections ..... 9.87

|  | Length. | Length allowed. | Height. |
|--|---------|-----------------|---------|
| Forecastle.  | 33' 0"  | 33' 0"          | 8' 0"   |
| Bridge House                                       | 34' 6"  | 33' 0"          | 8' 0"   |
| Raised Qr. Dk.                                     |         |                 |         |
| Poop   | 107' 0" | 107' 0"         | 8' 0"   |
| Total  |         | 145             |         |
| Length of Ship                                     |         |                 | - 417   |
| Corresponding percentage (Para. 11, 12, 13, or 14) | 26.49%  |                 |         |

FREEBOARD recommended amidships from centre of Disc to top of Statutory Deck Line, Wood (Iron) Deck :—

13.7.21  
Fresh Water Line above centre of Disc  
Indian Summer Line " " "  
Winter Line below " "  
Winter North Atlantic Line " " "

Frames skin planking, or cabling are of unusual thickness the breadth of vessel to inside ceiling should be reported if possible. Vessels obtaining an allowance for deck erections under Para. 11 where the sheer drops abeam amidships the height of the R.Q.D. is to be taken from the level of the top of the amidship beam. In vessels having poops and forecastles, the total standard mean sheer means the sheer measured at the stem and stern-post. In vessels having poops and forecastles, it means the sheer measured at points distant one-third of the vessel's length from stem and stern-post.

CORRECTION FOR LENGTH.  
Length of Ship on Loadline ..... 415 ✓  
Length in Table ..... 394 ✓  
Difference ..... 21 ✓  
Correction for 10ft., Table A ..... 1.6 ✓ Table C. 8  
× Difference divided by 10 ..... 3.36 (if required.) 1.68 -  
If  $\frac{1}{10}$ ths length covered divide by 2 ..... + 3.24 + 1.34 -

CORRECTION FOR IRON DECK.  
Proportion covered, if less than  $\frac{7}{10}$ ths length covered ..... 417  
Thickness of usual wood deck, less stringer (4 - 66) = 3.34 - 1/2

CORRECTION FOR ROUND OF BEAM.  
Breadth at Gunwale amidships ..... 54 - 6  
Round of Beam ..... 14 in 56 - 0  
Normal round .....  
Difference ..... ÷ 2 = .....  
Proportion of Deck uncovered (Para. 19) .....  
8 - 11 - 16 ✓ 8 - 11 1/4 ✓  
4.62 ✓ 4 3/4 ✓  
8 - 6.54 ✓ 8 - 6 1/2 ✓  
3.36 ✓ + 3 1/4 ✓  
8 - 9.90 ✓ 8 - 9 3/4 ✓  
9.57 ✓ 9 1/2 ✓  
8 - 0.33 ✓ 8 - 0 1/4 ✓

NOTE.—The round of beam should be reported on the full breadth of vessel at the gunwale.

Freeboard, Table A ..... 8 - 11 - 16 ✓ 8 - 11 1/4 ✓  
Correction for Sheer ..... 4.62 ✓ 4 3/4 ✓  
8 - 6.54 ✓ 8 - 6 1/2 ✓  
Correction for Length ..... 3.36 ✓ + 3 1/4 ✓  
Allowance for Deck Erections ..... 8 - 9.90 ✓ 8 - 9 3/4 ✓  
9.57 ✓ 9 1/2 ✓  
8 - 0.33 ✓ 8 - 0 1/4 ✓  
Correction for Round of Beam .....  
Correction for fall in Sheer (if any) .....  
Correction for Iron Deck (if required) ..... - 1/2 ✓  
Additions for non-compliance with provisions of Para. 11 (d) and (e) + 10 3/4 ✓  
Other Corrections (if any) .....  
7 - 10 3/4 ✓  
7 - 4 3/4 ✓  
6 - 10 3/4 ✓  
+ 10 3/4 ✓

Winter Freeboard .....  
Summer Freeboard .....  
Indian Summer Freeboard .....  
N. A. Winter Freeboard .....  
Correction necessary because clearside amidships, measured in accordance with the Statute is not taken at the intersection of the wood or iron deck with side.

Winter Freeboard from deck line .....  
Summer " " " .....  
Indian Summer " " " .....  
N. A. Winter " " " .....  
8 - 0 1/2 ✓  
7 - 6 1/2 ✓  
7 - 0 1/2 ✓

Winter Freeboard from deck line .....  
Summer " " " .....  
Indian Summer " " " .....  
N. A. Winter " " " .....  
8 - 0 1/2 ✓  
7 - 6 1/2 ✓  
7 - 0 1/2 ✓  
Y - 6 1/2 ✓  
6 6 ✓  
6 6 ✓  
State dimensions of freeing port area on back of this form.  
The Surveyor should state whether the fall in sheer as reported is measured relatively to the straight line of keel or to the water line. If measured relatively to water line the vessel's draft at time of survey, and also the usual load draft forward and aft should be reported.

002320-002329-0096

© 2020  
Lloyd's Register Foundation

29.8.21

Do all the Frames extend to the top height in the Poop? Yes  
 To what height do the Reverse Frames extend?  
 Has the Poop or Raised Quarter Deck an efficient Iron Bulkhead at the fore end?  
 Give particulars of the means for closing the openings in Bulkhead  
 Is the Poop or Raised Quarter Deck connected with the Bridge House? No  
 Has the Bridge House an efficient Bulkhead at the fore end? Yes  
 Give particulars of the means for closing the openings in Bulkhead Hinged iron doors permanently attached to bulkhead.  
 What is the thickness of the Bridge Front plating? 40" and Coaming plate?  
 Give scantlings and spacing of the Stiffeners L 9" x 3 1/2" x .60 Spaced 30" apart  
 Are bracket plates fitted at each end of the Stiffeners? Yes  
 Are hor'l. brackets fitted connecting Bridge Bulk'd. with Bulwarks? No bulwarks  
 Has the Bridge House an efficient Iron Bulkhead at the after end? Yes  
 How are the openings closed? Hinged doors of iron permanently attached to bulkhead.  
 Is the Forecastle at least as high as the main or top-gallant rail? Yes  
 Has the Forecastle an efficient Iron or Wood Bulk'd. at after end? No open  
 Are the Engine and Boiler openings covered by a Bridge, Poop, Raised Quarter Deck, or enclosed by a Strong Iron or Steel Deckhouse? By the Poop.  
 If the openings are not so protected are the exposed parts of the Casings efficiently constructed?  
 Give thickness of plating; scantlings and spacing of Stiffeners  
 What is the height of the exposed Casings?  
 Are suitable means provided for closing all openings in them in bad weather? Yes  
 Are the Weather Deck Hatchways efficiently constructed and at least equal to the requirements of Section 28 of the Rules for 1904-5? Give particulars below:—

| Position and Size.   | Ship. | Rule. |
|--|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| COAMING.<br>Height above top of DECK<br>Thickness { Sides...<br>Ends....               |       |       |       |       |       |       |       |       |       |       |
| SHIFTING BEAMS OR WEB PLATES.<br>Number { Section and Scantlings ....<br>Material .... |       |       |       |       |       |       |       |       |       |       |
| * FORE AND AFTERS.<br>Number { Section and Scantlings ....<br>Material ....            |       |       |       |       |       |       |       |       |       |       |
| HATCHES Thickness ....<br>Remarks.....   |       |       |       |       |       |       |       |       |       |       |

\* The depth of Fore and Afters should be stated from the underside of the hatches in all cases

(If the sill of the lowest side scuttle will be less than 6 inches above the Indian Summer Load Line if assigned under the tables, state vertical distance from top of deck at side amidships to lower edge of lowest side scuttle.)

The following information is to be given in all Cases of vessels dealt with under Paras. 11, 12 (under 15 feet Moulded depth) and under Shelter Deck Rules.  
 What is the thickness of the Bridge Sheerstrake?

Delete the words { The Crew are, are not, berthed in the bridge house.  
 that do not apply { The arrangements to enable them to get backwards and forwards from their quarters are, are not satisfactory.



Length of Bulwarks in well

Area of Freeing Ports required by Para. 11 (e) each side of vessel = Sq. ft.

Ft. Tenths. Ft. Tenths. No. } Freeing Ports = Sq. ft.

x                   x                   } (each side of vessel)

Total deficiency or excess = Sq. ft.



Show hereon line of Floors or Tank Top with position of any Breaks in same; also height of Peak Tank tops, &c., &c.

State any special features in the construction of the Vessel Yantek: Long. Fr.: Sister ship to S.S. "REAPER"

Boston Report No 1430: F.W. load line requested as per displacement scale forwarded with report on S.S. "Divigo"; Boston 1123: Tonnage taken to top of 15" floors by American Law.

Owners The Texas Co.

" Address

17 Battery Place, New York City.

for \$ 90  $\frac{00}{100}$  #

Received by me

will be charged with Foundation



Lloyd's Register  
Foundation