Rpt. 11b.

Preliminary.

Index No. _____ (For London Office only.)

Lloyd's Register of Shipping.

SURVEYS FOR FREEBOARD.—STEAM SHIPS.

PARTICULARS RELATING TO ALL STEAM SHIPS EITHER FLUSH DECKED, OR WITH TOP GALLANT FORECASTLES, SHORT POOPS AND BRIDGE HOUSES DISCONNECTED, OR WITH TOP GALLANT FORECASTLES HAVING LONG POOPS, OR RAISED QUARTER DECKS CONNECTED WITH BRIDGE HOUSES, OR OTHERWISE.

Port of Survey _____

Date ~~of Survey~~ 17.11.25

Name of Surveyor _____

Ship's Name.	Port of Registry and Nationality.	Official Number.	Gross Tonnage.	Date of Build.	Particulars of Classification.
C. Hill & Sons S.S. No.					100 A1

Number in Register Book _____

	Length.	Breadth.	Depth.	Under Deck Tonnage.
~~Registered~~ dimensions from ~~Ship's Register~~.	128'-9"	20'-2"	8'-9"	
Length on Loadline.		Frame Depth Rule „ 3"	Ceiling Sheer	Peak Tanks
Corrected Dimensions.	128.75			

Moulded Depth as measured..... 8'-9"

Addition for Keel below base line for draught record..... 5½ ...inches.

NOTE.— If the depth is measured when vessel is afloat, the details of measurement should be reported.

Co-efficient of fineness..... (Block coefficient given as above .80).

Any modification necessary [Para. 4 (a) to (e)]*

Co-efficient as corrected ..... Assumed .82

Sheer at { Stem..... 30 / Sternpost ... 16¾ } 46.75 ÷ 2 = 23.37 ...Mean

Sheer at ⅛ of the length from { Stem 15½ / Sternpost 8½ } 240 ÷ 2 = 12.0 ...Mean ÷ 55.2182

Gradual mean Sheer 12.0

Standard mean Sheer [Table, Para. 18] 13.73

Difference..... 1.73 ÷ 4 = .43 Correction

§ If limited as Para. 18 (f) ..... +½"

Rise in Sheer from amidships [Para. 18 (e)] { At front of bridge house..... / At after end of forecastle ..... }

Fall in Sheer Para. 18 (d) ÷ 2 =

Length uncovered ..... Correction

Allowance for Deck Erections :—

Freeboard, Table C.....	0'– 2¼"
Correction for Length, if required (Para. ~~12, 13, and~~ 14)	+ 1"
	0' – 3¼"
Freeboard by Table A. corrected for ~~sheer, and for~~ length, if required (Para. ~~12, 13, and~~ 14)	1' – 5"
Difference	1' – 1¾"
Percentage as below.....	23.58%
	3.24

Correction for R. Q. Dk. if engine and boiler openings not covered by bridge house (Para. 11)

Allowance for Deck Erections ..... – 3¼"

	Length.		Length allowed.		Height.
Forecastle.....	15.5 × ⅜	=	7.75		3.0
Bridge House	.....		.....		.....
† Raised Qr. Dk.....	39.7		39.70		3.25
Poop.....	.....		.....		.....
Total	55.2 / 128.75	= .429	47.45 / 128.75	= .3685 = 2.948 eighths	
Length of Ship					
Corresponding percentage (Para. ~~11, 12, 13, or~~ 14)	23.58%				

Correction for Length

Length of Ship on Loadline.....	128.75		
Length in Table	105.00		
Difference	23.75		
Correction for 10ft., Table A.	.8	Table C.	.4
× Difference divided by 10	1.9	(if required.)	.95
If $\frac{6}{10}$ths length covered divide by 2	+2"		+1"

Correction for Iron Deck.

Proportion covered, if less than $\frac{7}{10}$ths length covered ..... .429

Thickness of usual wood deck, less stringer ..(3"-¼")..... 2¾" / 1.18 — 1¼"

Correction for Round of Beam.

NOTE. — The round of beam should be reported on the full breadth of vessel at the gunwale.

Breadth at Gunwale amidships..... 20.17

Round of Beam ..... 5"

Normal round..... 5"

Difference ..... ÷ 2 =.....

Proportion of Deck uncovered (Para. 19) .....

Freeboard, Table A	1'-3"
Correction for Sheer	+ 0½"
	1'-3½"
Correction for Length	+ 2"
	1'- 5½"
Allowance for Deck Erections	– 3¼"
	1'- 2¼"
Correction for Round of Beam.....	
Correction for fall in Sheer (if any).....	
Correction for Steel Deck (if required)	– 1¼"
	1'– 1"
Additions for non-compliance with provisions of Para. 11 (d) and (e) ‡	
Other Corrections (if any)	

Winter Freeboard	1'-1"
Summer Freeboard ..... 1½"	0'-11½"
~~Indian Summer Freeboard~~	
~~N. A. Winter Freeboard~~	
Correction necessary because clearside amidships, measured in accordance with the Statute is not taken at the intersection of the ~~wood or~~ steel deck with side.	0¾"
Winter Freeboard from deck line	1'– 1¾"
Summer „ „ „ „	1'– 0¼"
~~Indian Summer~~ „ „ „ „	
~~N. A. Winter~~ „ „ „ „	

FREEBOARD recommended amidships from centre of Disc to top of Statutory Deck Line, ~~Wood~~ (Steel) Deck :— ... ... 1'– 0½"

Fresh Water Line	above centre of Disc	2"
~~Indian Summer Line~~	„ „ „	
Winter Line	below „ „	1½"
~~Winter North Atlantic Line~~	„ „ „	

* If the frames, skin planking, or ceiling are of unusual thickness the breadth of vessel to inside of ceiling should be reported if possible.

† In vessels obtaining an allowance for deck erections under Para. 11 where the sheer drops abaft amidships the height of the R.Q.D. is to be taken from the level of the top of the amidship beam.

§ In flush-decked vessels the total standard mean sheer means the sheer measured at the stem and stern-post. In vessels having poops and forecastles, it means the sheer measured at points distant one-eighth of the vessel's length from stem and stern-post.

‡ State dimensions of freeing port area on back of this form.

¶ The Surveyor should state whether the fall in sheer as reported is measured relatively to the straight line of keel or to the water line. If measured relatively to water line the vessel's draft at time of survey, and also the usual load draft forward and aft should be reported.

2m,12,24. T.

©2020 Lloyd's Register Foundation

C02340-002351-0157