

MULTITUBULAR BOILERS MAIN, AUXILIARY, OR DONKEY.

Manufacturers of Steel *Witkowitz* Bergbau- und Eisenhütten Gewerkverein

(Letter for Receiver)

(Received at London Office)

19

No. _____ Port Middlesbrough. Date 7th. January 19 30.

We request that the Marine Type Boiler numbered as below to be made for Messrs. Aktiebolaget Gotaverken, Messrs. Riley Bros (Boilermakers) Ltd Gothenburg. Stockton-on-Tees. may be Specially Surveyed while building.

We hereby engage to pay Special Survey Fees as follows, viz.:-

For boilers up to 250 Nominal Horse Power, two shillings per Horse Power. For boilers over 250 Nominal Horse Power, two shillings per Horse Power for the first 250 Horse Power and one shilling per Horse Power above 250. The Nominal Horse Power to be reckoned at 15 square feet of heating surface. No fee to be less than £4 4s.

MEM.—In exceptional cases an additional charge will be made according to the services performed, and in all cases where travelling expenses are incurred by the Surveyors in connexion with the above services, they are to be defrayed by the parties interested.

Boiler No. 5978/9/80/1.

This request is made upon the terms of the Rules and Regulations of Lloyd's Register of Shipping, which provide that:—

While the Committee use their best endeavours to ensure that the functions of the Society are properly executed, it is to be understood that neither the Committee nor the Society are under any circumstances whatever to be held responsible for any inaccuracy in any report or certificate issued by the Society or its Surveyors, or in any entry in the Register Book or other publication of the Society, or for any error of judgment, default, or negligence of the Surveyors, or other Officers or Agents of the Society.

RILEY BROS. (BOILERMAKERS) LIMITED.

Signature

To the Secretary,

Lloyd's Register of Shipping,

71, Fenchurch Street, London E.C. (3)

SECRETARY,

© 2020

Lloyd's Register
Foundation

Boilers to combustion chamber tops: Material

Steel

Tensile strength

28/32

centre

7 1/8" (double)

Length as per Rule

2' 5"

Distance apart

8"

Combustion chamber plates: Material



© 2020

Lloyd's Register Foundation