

Rpt. 13.

No. 28890

REPORT ON ELECTRIC FITTINGS.

(OTHER THAN FOR THE PROPULSION OF THE VESSEL)

Received at London Office 14 OCT 1924

Date of writing Report 10 When handed in at Local Office 13 OCT 1924 Port of SUNDERLAND

No. in Survey held at SUNDERLAND Date, First Survey 31 July Last Survey 16 Aug 1924
Reg. Book. (Number of Visits.....)on the S.S. "JAMES DUNFORD" Tons { Gross 1196
Net 712

Built at Southwick Yard, Sunderland By whom built Swan Hunter & Wigham Richardson Yard No. 1243. When built 1924.

Owners The Dunford Steamship Co Ltd Port belonging to Newcastle

Electric Light Installation fitted by Swan Hunter & Wigham Richardson Ltd. Contract No. 1243 When fitted 1924

System of Distribution

Pressure of supply for Lighting 110 volts, Heating — volts, Power — volts.

Direct or Alternating Current, Lighting

If alternating current system, state frequency of periods per second —

Has the Automatic Governor been tested and found efficient when the whole load is suddenly thrown on or off Yes.

Generators, do they comply with the requirements regarding overload Yes, are they compound wound Yes.

are they over compounded 5 per cent. Yes, if not compound wound state distance between each generator —

Where more than one generator is fitted are they arranged to run in parallel —, is an adjustable regulating resistance fitted in series with each shunt field Yes.

Are all terminals accessible and clearly marked Yes, are they so spaced or shielded that they cannot be accidentally earthed, or short circuited Yes.

Position of Generators

Are the lubricating arrangements of the generators as per Rule Yes

is the ventilation in way of the generators satisfactory Yes, are they clear of all inflammable material Yes.

if situated near unprotected woodwork or other combustible material, state distance of same horizontally from or vertically above the generators — and —, are the generators protected from mechanical injury and damage from water, steam or oil Yes.

are their axis of rotation fore and aft Yes.

Earthing, are the bedplates and frames of the generating plant efficiently earthed Yes, are the prime movers and

their respective generators in metallic contact Yes.

Main Switch Boards, where placed

In Engine Room.

If the generators and main switchboard are not placed in the same compartment, is each generator provided with

a fuse on each insulated pole as near as possible to the terminals of the generator, additional to that provided on the main switchboard

Switchboards, are they placed in accessible positions, free from inflammable gases and acid fumes Yes.

are they protected from mechanical injury and damage from water, steam or oil Yes, if situated near unprotected

woodwork or other combustible material, state distance of same horizontally from or vertically above the switchboards — and —,

are they constructed wholly of durable, incombustible non-absorbent materials Yes, is all insulation of high dielectric strength and of

permanently high insulation resistance Yes, if semi-insulating material is used, are all conducting parts connected to one pole

insulated from the slab with mica or micanite and the slab similarly insulated from its framework Yes, and is the

frame effectively earthed Yes. Are the following fittings as per Rule, viz.: — spacing or shielding of live parts

Yes, accessibility of all parts Yes, absence of fuses on back of board Yes, proportion of omnibus

bars Yes, individual fuses to voltmeter, pilot or earth lamp Yes, connections of switches Yes.

Main Switchgear, description of switchgear for each generator and each outgoing circuit, and arrangement of equalizer switches

Double Pole Switches with Fuses for Dynamo Mains.

Single Pole " " " " Outgoing Circuits.

Instruments on main switchboard 1 ammeters 1 voltmeters — synchronising device for paralleling purposes.

Earth Testing, state what means are provided at the main switchboard for indicating the state of the insulation of the system Earth Lamps.

coupled to earth through switches & fuses.

Switches, Circuit Breakers and Fusible Cut-outs, do these comply with the requirements of the Rules Yes.

Section and Distribution Boards, is the construction, protection, insulation, material, and position of these as per rule Yes.



© 2020

Lloyd's Register
Foundation

002498-002505-0081

Insulation of Cables, state type of cables, single or twin Single are the cables insulated and protected as per Tables III or IV of the Rules. Yes.

Fall of Pressure, state maximum between bus bars and any point of the installation under maximum load Four Volts.

Cable Sockets and other connections, are the ends of all cables having a sectional area of 0.007 square inch and above provided with soldering sockets Yes.

Paper Insulated Cables. If cables are paper covered, is the dielectric at the exposed ends of the conductor protected from moisture by being suitably sealed with insulating compound Yes.

Cable Runs, are the cables fixed as far as possible in accessible positions not exposed to drip or accumulation of water or oil, or to high temperature from boilers, steam pipes, uptakes or other hot objects, or to avoidable risk of mechanical damage Yes.

Support and Protection of Cables, state how the cables are supported and protected Lead covered cables clipped direct to Bulkheads in Accommodation. Braided & Compounded Cables in Conduit along Bulkhead. Lead covered & Armoured Cables in Engine & Boiler Rooms.

If cables are run in wood casings, are the casings and caps secured by screws Yes., are the cap screws of brass Yes., are the cables run in separate grooves Yes. If armoured and lead covered cables are secured by metal clips, are the clips spaced as per Table VI Yes.

Refrigerated Chambers, if lights are fitted, are the cables and fittings in accordance with the special requirements None made

Joints in Cables, state if any, and how made, insulated, and protected None made

Watertight Glands and Deck Tubes, are all cables passing through decks and watertight bulkheads provided with deck tubes or watertight glands Yes.

Bushes in Beams and Non-watertight Positions, where unarmoured cables pass through beams and non-watertight partitions, are the holes efficiently bushed Yes. state the material of which the bushes are made Rubber.

Earthing Connections, state what earthing connections are fitted and their respective sectional areas are their connections made as per Rule.

Alternative Lighting, are the groups of lights in the propelling machinery space arranged as per Rule Yes.

Emergency Supply, state position and method of control of the emergency supply and how the generator is driven none fitted

Navigation Lamps, are these separately wired Yes., controlled by separate switch and separate fuses Yes.

are the fuses double pole Yes., are the switches and fuses grouped in a position accessible only to the officers on watch Yes.

has each navigation lamp an automatic indicator as per Rule Yes., are separate screens provided for the use of oil and electric side lights Yes.

are separate oil lanterns provided for the mast head lights and side lights Yes.

Fittings, are all fittings on weather decks, in stokeholds and engine rooms and wherever exposed to drip or condensed moisture, watertight Yes.

are any fittings placed in spaces in which goods are liable to be stacked in close proximity to them; if so, how are they protected none

are any fittings placed in spaces where inflammable or explosive dust or gases are liable to be present, if so, how are they protected none

how are the cables led where are the controlling switches situated

Searchlight Lamps, No. of None, whether fixed or portable None, are their fittings as per Rule None

Are Lamps, other than searchlight lamps, No. of None, are their live parts insulated from the frame or case None, are their fittings as per Rule None

Motors, are their working parts readily accessible None, are the coils self-contained and readily removable for replacement None

are the brushes, brush holders, terminals and lubricating arrangements as per Rule None, are the motors placed in well-ventilated compartments in which inflammable gases cannot accumulate and clear of all inflammable material None

are they protected from mechanical injury and damage from water, steam or oil None are their axis of rotation fore and aft None

if situated near unprotected woodwork or other combustible material, are the motors of the totally enclosed, pipe ventilated, forced draught, drip or flame proof type None

if not of this type, state distance of the combustible material horizontally or vertically above the motors None and None

Control Gear and Resistances, are the generator field and motor speed regulators, starters and controllers constructed as per Rule None

Lightning Conductors, where lightning conductors are required, are these fitted as per Rule None

Ships carrying Oil having a Flash Point less than 150° F. Have the special requirements of the Rules been complied with regarding switches, joint boxes, section and distribution boards, protection of cables, method of distribution, lead of cables, lights and fittings None

If portable lamps for use in dangerous spaces are supplied, are they of a type approved by the Home Office None

PARTICULARS OF GENERATING PLANT.									
DESCRIPTION OF GENERATOR.	No. of	RATED AT				DRIVEN BY.	WHERE DRIVEN BY AN INTERNAL COMBUSTION ENGINE.		
		Kilowatts.	Volts.	Ampères.	Revs. per Min.		Fuel Used.	Flash Point of Fuel.	
MAIN	1	5	110	45	430	Single cylinder Open type Engine (Steam).			
AUXILIARY									
EMERGENCY									
ROTARY TRANSFORMER									

LIGHTING AND HEATING CONDUCTORS.									
Ref. No.	DESCRIPTION.	No. of Conductors.	Effective Area of each Conductor. Sq. Ins.	COMPOSITION OF STRAND.		Total Maximum Current. Ampères.	Approximate Length. (Lead and Return.) Feet.	Insulated with	HOW PROTECTED.
				No.	Diameter.				
	MAIN GENERATOR	2	.04	19	.052	30	40	Rubber	Lead covered.
	AUXILIARY GENERATOR								
	EMERGENCY GENERATOR								
	ROTARY TRANSFORMER								
	AUXILIARY SWITCHBOARDS								
C.	ENGINE ROOM	2	.0045	7	.029	5.0	30	Rubber	Lead covered & Armoured.
	BOILER ROOM								
B.	Fore & aft Accom.	2	.007	7	.036	10	20	Rubber	Lead covered & V.I. in Conduit to Fore.
A.	Midship Accom. & Navigation	2	.007	7	.036	10.2	25	"	"
	WIRELESS								not fitted
	SEARCHLIGHT	2	.0015	1	.044	1.2	300	Rubber	V.I. in Conduit
	MASTHEAD LIGHT	2	.0015	1	.044	1.2	50	"	Lead covered
	SIDE LIGHTS	2	.0015	1	.044	.6	50	"	"
	COMPASS LIGHTS	2	.0015	1	.044	1.2	200	"	V.I. in Conduit
Stem	PORT LIGHTS	2	.0015	1	.044	1.2	200	"	"
	CARGO LIGHTS	2	.003	3	.036	5.0	150	"	"
	ARC LAMPS								
	HEATERS								

MOTOR CONDUCTORS.									
Ref. No.	DESCRIPTION.	No. of Motors.	Effective Area of each Conductor. Sq. Ins.	COMPOSITION OF STRAND.		Total Maximum Current. Ampères.	Approximate Length. (Lead and Return.) Feet.	Insulated with	HOW PROTECTED.
				No.	Diameter.				
	BALLAST PUMP								
	MAIN BILGE LINE PUMPS								
	GENERAL SERVICE PUMP								
	EMERGENCY BILGE PUMP								
	SANITARY PUMP								
	CIRC. SEA WATER PUMPS								
	CIRC. FRESH WATER PUMPS								
	AIR COMPRESSOR								
	FRESH WATER PUMP								
	ENGINE TURNING GEAR								
	ENGINE REVERSING GEAR								
	LUBRICATING OIL PUMPS								
	OIL FUEL TRANSFER PUMP								
	WINDLASS								
	WINCHES, FORWARD								
	WINCHES, AFT								
	STEERING GEAR								
	WORKSHOP MOTOR								
	VENTILATING FANS								

All Conductors are of annealed copper conforming to British Standard Specification No. 7.
The Insulated Conductors are guaranteed to withstand the immersion and resistance tests specified in the Rules.
The foregoing is a correct description.

SWAN. HUNTER. & WISHAM RICHARDSON, LTD.

Electrical Engineers.

Date

6th Oct 1924

COMPASSES.

Distance between electric generators or motors and standard compass 65 ft

Distance between electric generators or motors and steering compass 60 ft

The nearest cables to the compasses are as follows:—

A cable carrying 28 Ampères — feet from standard compass — feet from steering compass.

A cable carrying 5 Ampères 3 feet from standard compass 3 feet from steering compass.

A cable carrying — Ampères — feet from standard compass — feet from steering compass.

Have the compasses been adjusted with and without the electric installation at work at full power. Yes.

Has the effect of switching on and off circuits, motors and other electro-magnetic apparatus within the vicinity of the compasses been noted. Yes.

The maximum deviation due to electric currents was found to be Nil degrees on all courses course in the case of the standard compass, and Nil degrees on all course in the case of the steering compass.

For

SWAN. HUNTER & WISHAM RICHARDSON, LTD.

Builder's Signature.

Date

4th Oct 1924

Is this installation a duplicate of a previous case no If so, state name of vessel —

General Remarks (State quality of workmanship, opinions as to class, &c.)

It is submitted that
this vessel is eligible for
THE RECORD. Elec. light.

JWD
15/10/24

Total Capacity of Generators 5 Kilowatts

The amount of Fee ... £ 5

When applied for,

18 Aug 1924

When received,

20 Aug 1924

Travelling Expenses (if any) £

Committee's Minute

Assigned

1m.32. Transfer.
(The Surveys are requested not to write on or below the space for Committee's Minute.)



© 2020

Lloyd's Register
Foundation