

# Lloyd's Register of Shipping.

## SURVEYS FOR FREEBOARD.

(COMPUTATION FOR STEAMER, SAILING SHIP, TANKER.)

Ship's Name <b>"BRITISH PATIENCE"</b>	Official Number <b>168451</b>	Nationality and Port of Registry <b>BRITISH LONDON</b>	Gross Tonnage <b>8097.17</b>	Date of Build <b>1943</b>	Port of Survey <b>GLASGOW</b>
Moulded Dimensions: Length <b>460.645</b> Breadth <b>61.0</b> Depth <b>33.25</b>					Date of Survey <b>WHILST BUILDING</b>
Moulded displacement at moulded draught = 85 per cent. of moulded depth <b>17697</b> tons					Surveyor's Signature <b>W. J. Pyle</b>
Coefficient of fineness for use with Tables <b>.780</b>					Particulars of Classification <b>100A1 CARRYING PETROLEUM IN BULK (CONTEMPLATED)</b>

Depth for Freeboard (D).	Depth correction.	Round of Beam correction.
Moulded depth ... <b>33.25</b>	(a) Where D is greater than Table depth (D - Table depth) R = <b>(33.31 - 30.71) 3 = +7.80"</b>	Moulded Breadth (B) <b>61.0</b>
Stringer plate ... <b>.78</b> ... <b>.06</b>	(b) Where D is less than Table depth (if allowed) (Table depth - D) R = <b>✓</b>	Standard Round of Beam = $\frac{B \times 12}{50} = \frac{732}{50} = 14.64$
Sheathing on exposed deck <b>NONE</b>		Ship's Round of Beam = <b>15"</b>
T $\left(\frac{L-S}{L}\right) =$		Difference <b>.36</b>
Depth for Freeboard (D) = <b>33.31</b>	If restricted by superstructures <b>✓</b>	Restricted to <b>✓</b>
		Correction = $\frac{\text{Diff}}{4} \times \left(1 - \frac{S_1}{L}\right) = \frac{.36}{4} \times .5721 = .05"$

## DEDUCTION FOR SUPERSTRUCTURES.

	Mean Covered Length (S)	Equivalent Enclosed Length (S <sub>i</sub> )	Height	Height Correction	Effective Length (E)
Poop enclosed <b>Equi.</b> ...	<b>98.48</b>	<b>98.48</b>	<b>7'-6"</b>	<b>✓</b>	<b>98.48</b>
.. overhang ...	<b>3'-6"</b>				
R.Q.D. enclosed ...					
.. overhang ...					
Bridge enclosed <b>Equi.</b> ...	<b>45.19</b>	<b>45.19</b>	<b>7'-6"</b>	<b>✓</b>	<b>45.19</b>
.. overhang aft ...	<b>2'-6"</b>	<b>1.87</b>			<b>1.87</b>
.. overhang forward ...	<b>2'-6"</b>				
F'cle enclosed ...	<b>51.58</b>	<b>51.58</b>	<b>7'-6"</b>	<b>✓</b>	<b>51.58</b>
.. overhang ...					
Trunk aft ...					
.. forward ...					
Tonnage opening aft ...					
.. forward ...					
Total ...	<b>197.75</b>	<b>197.12</b>			<b>197.12</b>

Standard Height of Superstructure **7.5'**

" " R.Q.D. **✓**

Deduction for complete superstructure **42.00"**

Percentage covered  $\frac{S}{L} = \frac{197.12}{460.645} = 42.93$

" "  $\frac{S_i}{L} = \frac{197.12}{460.645} = 42.79$

Percentage from Table, Line **Tanker** **33.79**  
(corrected for absence of forecastle (if required)) **✓**

Percentage from Table, Line B. **✓**  
(corrected for absence of forecastle (if required)) **✓**

Interpolation for bridge less than 2L (if required) **✓**

Deduction = **42.00 x .3379 = -14.19**

## SHEER CORRECTION.

Station	Standard Ordinate	S	M	Product	Actual Ordinate	Effective Ordinate	S	M	Product
A.P. ...	<b>56.06</b>	<b>1</b>	<b>56.06</b>	<b>60.31</b>	<b>60.31</b>	<b>1</b>	<b>60.31</b>	<b>60.31</b>	
$\frac{1}{2}L$ from A.P. ...	<b>24.95</b>	<b>4</b>	<b>99.80</b>	<b>26.94</b>	<b>26.94</b>	<b>4</b>	<b>107.76</b>	<b>107.76</b>	
$\frac{3}{4}L$ " ...	<b>6.165</b>	<b>2</b>	<b>12.33</b>	<b>6.71</b>	<b>6.71</b>	<b>2</b>	<b>13.42</b>	<b>13.42</b>	
Amidships ...	<b>-</b>	<b>4</b>	<b>-</b>	<b>-</b>	<b>-</b>	<b>4</b>	<b>-</b>	<b>-</b>	
$\frac{3}{4}L$ from F.P. ...	<b>12.33</b>	<b>2</b>	<b>24.66</b>	<b>12.47</b>	<b>12.47</b>	<b>2</b>	<b>24.94</b>	<b>24.94</b>	
$\frac{1}{2}L$ " ...	<b>49.90</b>	<b>4</b>	<b>199.60</b>	<b>50.59</b>	<b>50.59</b>	<b>4</b>	<b>202.36</b>	<b>202.36</b>	
F.P. ...	<b>112.13</b>	<b>1</b>	<b>112.13</b>	<b>114</b>	<b>114.00</b>	<b>1</b>	<b>114.00</b>	<b>114.00</b>	
Total ...			<b>504.58</b>				<b>522.79</b>		

Mean actual sheer aft = **60.31**  
Mean standard sheer aft = **60.31**

Mean actual sheer forward = **107.76**  
Mean standard sheer forward = **107.76**

Length of enclosed superstructure forward of amidships = **197.12**  
aft of " = **197.12**

Correction =  $\frac{\text{Difference between sums of products}}{18} \left( \frac{.75 - S}{2L} \right) = \frac{18.21}{18} \left( \frac{.75 - .2147}{.5353} \right) = -.54"$   
If limited on account of midship superstructure. **✓**

If limited to maximum allowance of  $1\frac{1}{2}$  ins. per 100 ft. **✓**

Deduction for Tropical Freeboard.	Deduction for Fresh Water.	TABULAR FREEBOARD corrected for Fresh Deck (if required)	<b>77.86</b>
Addition for Winter and Winter North Atlantic Freeboard.	Displacement in salt water at summer load water line	Correction for coefficient $\frac{.780 + .68}{1.36} = 1.46/1.36$	<b>83.59</b>
Depth to Freeboard Deck = <b>33.31</b>	$\Delta = 16.880$	Depth Correction ... <b>7.80</b>	
Summer freeboard = <b>6.37</b>	Tons per inch immersion at summer load water line	Deduction for superstructures ... <b>-14.19</b>	
Moulded draught (d) = <b>26.94</b>	T = <b>58.05</b>	Sheer correction ... <b>.54</b>	
Deduction for Tropical freeboard and addition for Winter freeboard = $\frac{d}{4}$ inches = <b>6.74 = 6<math>\frac{3}{4}</math>"</b>	Deduction = $\frac{\Delta}{40T}$ inches = <b>7.27</b>	Round of Beam correction ... <b>.05</b>	
Addition for Winter North Atlantic Freeboard (if required) = <b>6.74 + 4.61 = 11.35 = 11<math>\frac{1}{4}</math>"</b>	= <b>7<math>\frac{1}{4}</math>"</b>	Correction for Thickness of Deck amidships ... <b>-</b>	
		Other corrections, scantlings, etc. ... <b>-</b>	
		<b>7.80 14.78 - 6.98</b>	
		Summer Freeboard = <b>76.61</b>	

SUMMER FREEBOARD amidships from Centre of Disc to top of Deck Line, **STEEL**, Steel, Deck :-

Tropical Fresh Water Line above Centre of Disc ...	<b>14"</b>	Tropical Fresh Water Freeboard ...	<b>6'-4<math>\frac{1}{2}</math>"</b>
Fresh Water Line " " ...	<b>7<math>\frac{1}{4}</math>"</b>	Fresh Water " " ...	<b>5'-2<math>\frac{1}{2}</math>"</b>
Tropical Line " " ...	<b>6<math>\frac{3}{4}</math>"</b>	Tropical " " ...	<b>5'-9<math>\frac{1}{4}</math>"</b>
Winter Line below " " ...	<b>6<math>\frac{3}{4}</math>"</b>	Winter " " ...	<b>5'-9<math>\frac{3}{4}</math>"</b>
Winter North Atlantic Line " " ...	<b>11<math>\frac{1}{4}</math>"</b>	Winter North Atlantic " " ...	<b>6'-11<math>\frac{1}{4}</math>"</b>
			<b>7'-3<math>\frac{3}{4}</math>"</b>



A new form should be prepared if any alterations that affect the freeboard have been made. If no such alterations have been made, the Surveyor should endorse the form on this side with his signature and the date.

Poop:  $2\frac{2}{3} \times 5'-6"$   $94'-9\frac{3}{4}"$   
 $3'-8"$   
 $98'-5\frac{3}{4}"$   
 Bridge:  $2\frac{2}{3} \times 3'-11\frac{1}{4}"$   $42'-6\frac{3}{4}"$   
 $2'-7\frac{1}{2}"$   
 $45'-2\frac{1}{4}"$

EXTERNAL DISPLACEMENT AT 27'-0" DRAFT = 16807 TONS  
 " " " 28'-0" " = 17506 "  
 FREEBOARD REQUEST IS ENCLOSED HEREWITH

TONS PER INCH 58.01  
 " " " 58.43

Trade of ship INTERNATIONAL

Names of sister ships BRITISH VIGILANCE (H&W's N° 11165) & BRITISH MERIT (H&W's N° 1117)

Builder's name and yard number HARLAND & WOLFFS N° 11665.

Owners BRITISH TANKERS LTD

Fee £ 19-0-0.



© 2020

Lloyd's Register  
Foundation