

REPORT ON STEAM RECIPROCATING ENGINE MACHINERY.

Received at London Office. 31 OCT 1944 21 JUN 1945

Date of writing Report 26. 10. 1944 When handed in at Local Office 19 Port of Nottingham.

No. in Survey held at Derby. Date, First Survey 22. 9. 43 Last Survey 6. 9. 1944
Reg. Book (Number of Visits 26.)

On the Transport Scout 30846 (6 Dec 1940)

Yard No. 1297 Tons { Gross 4457
Net 2430

When built 1945

Engines made at Derby By whom made Geo. Fletcher & Co. Ltd. Engine No. 2131 When made 1944.

Boilers made at - By whom made - Boiler No. - When made -

Registered Horse Power - Owners - Port belonging to -

Nom. Horse Power as per Rule - Is Refrigerating Machinery fitted for cargo purposes - Is Electric Light fitted -

Trade for which vessel is intended -

Engines, &c.—Description of Engines Inverted. Triple Expansion. Revs. per minute 185.

Dia. of Cylinders $18\frac{1}{2} \times 31 \times 38\frac{1}{2} \times 38\frac{1}{2}$ Length of Stroke 30 No. of Cylinders 4 No. of Cranks 4

Crank shaft, dia. of journals as per Rule Appd. as fitted $10\frac{1}{2}$ Crank pin dia. $10\frac{1}{2}$ Crank webs Mid. length breadth $16\frac{3}{4}$ Mid. length thickness $6\frac{1}{2}$ Thickness parallel to axis $6\frac{1}{2}$ Thickness around eye-hole $4\frac{7}{8}$

Intermediate Shafts, diameter as per Rule - as fitted - Thrust shaft, diameter at collars as per Rule - as fitted -

Tube Shafts, diameter as per Rule - as fitted - Screw Shaft, diameter as per Rule - as fitted - Is the { tube } shaft fitted with a continuous liner { screw }

Bronze Liners, thickness in way of bushes as per Rule - as fitted - Thickness between bushes as per Rule - as fitted - Is the after end of the liner made watertight in the propeller boss -

If the liner is in more than one length are the junctions made by fusion through the whole thickness of the liner -

If the liner does not fit tightly at the part between the bearings in the stern tube, is the space charged with a plastic material insoluble in water and non-corrosive -

If two liners are fitted, is the shaft lapped or protected between the liners - Is an approved Oil Gland or other appliance fitted at the after end of the tube at - If so, state type - Length of Bearing in Stern Bush next to and supporting propeller -

Propeller, dia. - Pitch - No. of Blades - Material - whether Moveable - Total Developed Surface - sq. feet

Feed Pumps worked from the Main Engines, No. - Diameter - Stroke - Can one be overhauled while the other is at work -

Bilge Pumps worked from the Main Engines, No. - Diameter - Stroke - Can one be overhauled while the other is at work -

Feed Pumps { No. and size - Pumps connected to the { No. and size -
How driven - Main Bilge Line How driven -

Ballast Pumps, No. and size - Lubricating Oil Pumps, including Spare Pump, No. and size -

Are two independent means arranged for circulating water through the Oil Cooler - Suctions, connected to both Main Bilge Pumps and Auxiliary Bilge Pumps:—In Engine and Boiler Room -

In Pump Room - In Holds, &c. -

Main Water Circulating Pump Direct Bilge Suctions, No. and size - Independent Power Pump Direct Suctions to the Engine Room Bilges, No. and size -

Are all the Bilge Suction Pipes in holds and tunnel well fitted with strum-boxes -

Are the Bilge Suctions in the Machinery Space led from easily accessible mud-boxes, placed above the level of the working floor, with straight tail pipes to the bilges -

Are all Sea Connections fitted direct on the skin of the ship - Are they fitted with Valves or Cocks -

Are they fixed sufficiently high on the ship's side to be seen without lifting the stokehold plates - Are the Overboard Discharges above or below the deep water line -

Are they each fitted with a Discharge Valve always accessible on the plating of the vessel - Are the Blow Off Cocks fitted with a spigot and brass covering plate -

What Pipes pass through the bunkers - How are they protected -

What pipes pass through the deep tanks - Have they been tested as per Rule -

Are all Pipes, Cocks, Valves, and Pumps in connection with the machinery and all boiler mountings accessible at all times -

Is the arrangement of Valves and their connections such as to prevent the possibility of water passing from the sea or from water tanks into the cargo or machinery spaces, or from one compartment to another - Is the Shaft Tunnel watertight - Is it fitted with a watertight door - worked from -

MAIN BOILERS, &c.—(Letter for record -) Total Heating Surface of Boilers -

Which Boilers are fitted with Forced Draft - Which Boilers are fitted with Superheaters -

No. and Description of Boilers - Working Pressure 225 lb./sq. in.

IS A REPORT ON MAIN BOILERS NOW FORWARDED? No.

IS A DONKEY BOILER FITTED? - If so, is a report now forwarded? -

Can the donkey boiler be used for domestic purposes only -

PLANS. Are approved plans forwarded herewith for Shafting 4. 2. 41. Main Boilers - Auxiliary Boilers - Donkey Boilers -

(If not state date of approval)

Superheaters - General Pumping Arrangements - Oil fuel Burning Piping Arrangements -

SPARE GEAR.

Has the spare gear required by the Rules been supplied Yes


State the principal additional spare gear supplied To Admiralty Requirements.

The foregoing is a correct description.

GEORGE FLETCHER & CO. LTD.

Manufacturer.

WORKS MANAGER



© 2020

Lloyd's Register Foundation

002568-002576-0156

Dates of Survey while building
During progress of work in shops - - 22. 9. 43 - 8. 9. 44.
During erection on board vessel - - -
Total No. of visits 26.

Dates of Examination of principal parts—Cylinders 25. 10/44 - 15. 1/44 Slides 25. 10/44 - 15. 1/44 Covers 25. 10/44 - 15. 1/44
Pistons 13. 10/44 - 15. 1/44 Piston Rods 22. 9/44 - 19. 4/44 Connecting rods 22. 9/44 - 19. 4/44
Crank shaft 22. 11/43 Thrust shaft - Intermediate shafts -
Tube shaft - Screw shaft - Propeller -
Stern tube - Engine and boiler seatings - Engines holding down bolts -
Completion of fitting sea connections -
Completion of pumping arrangements - Boilers fixed - Engines tried under steam -
Main boiler safety valves adjusted - Thickness of adjusting washers -
Crank shaft material O. H. steel. Identification Mark 18. 11. 43. GAM Thrust shaft material - Identification Mark -
Intermediate shafts, material - Identification Marks - Tube shaft, material - Identification Mark -
Screw shaft, material - Identification Mark - Steam Pipes, material - Test pressure - Date of Test -
Is an installation fitted for burning oil fuel - Is the flash point of the oil to be used over 150° F. -
Have the requirements of the Rules for the use of oil as fuel been complied with -
Is the vessel (not being an oil tanker) fitted for carrying oil as cargo - If so, have the requirements of the Rules been complied with -
If the notation for Ice Strengthening is desired, state whether the requirements in this respect have been complied with -
Is this machinery duplicate of a previous case. Yes If so, state name of vessel No. J 453

General Remarks (State quality of workmanship, opinions as to class, &c. This engine has been built under Special Survey in accordance with the approved plans, the Secretary's letters and the Society's Rules.
The materials and workmanship are good.
The engine has now been despatched to the works of Messrs Harland and Wolff Ltd., Glasgow, for installation on board the vessel No. J. 1866.

The amount of Entry Fee ... £ : : When applied for, 30. 10. 19 44
Special Survey Fee ... £ 22 : 10 :
Donkey Boiler Fee ... £ : :
Travelling Expenses (if any) £ : : When received, 19

ADMIRALTY

A/c rendered from
London 13. 11. 44

A. W. Jones

Engineer Surveyor to Lloyd's Register of Shipping.

Committee's Minute

GLASGOW

19 JUN 1945

Assigned

SEE ACCOMPANYING MACHINERY REPORT.



© 2020

Lloyd's Register
Foundation