


Form No. 14

Lloyd's Register Foundation

Transverse W.T. Bulkheads.

Number		Thickness	Stiffeners		Spacing	Single or Double Frames	Height up Side Deck
Ship	Rule		Horizontal	Vertical			
6	6						
No 7-14		.60-.34	Tunnel Recept. 107 Flat	(Below Flat. 10x31.5 B.A. Above 5x3x32 C.A.	24 30	Single	Poop 0°
37		.40+.36		12x3½x6 B.A. with Reserve Base as approved.	30	Single	0°
61		.40+.36		12x3½x50 B.A. 8½x3½x46 B.A. in way of Transit Recept.	30 30	0°	0°
80		.36+.32		9½x3½x58 B.A.	30	0°	Upper 0°
112		.40+.34		12x3½x66 B.A. 12x3½x50 B.A. with Reserve Base as appd	30	0°	0°
Col. B. 143		.42-.34	W.T. Flat & Stringers	Below Flat 12x3½x60 B.A. above flat 6x3x40 B.A.	24 24	0°	0°

PARTICULARS FOR RECORD in the REGISTER BOOK.—Length of Poop ^{Raised upper deck} ~~218.0~~ ft., Bridge ~~218.0~~ ft., Forecastle ~~218.0~~ ft. (in feet and tenths). When the Poop is joined to the B.D., this should be distinctly stated Joined. Raised upper deck.

No. and Material of Decks (if Iron or Steel) and whether wholly or partially covered with wood, and No. of tiers of Beams (this information is to be given as it should appear in the Register Book) One Deck Steel.

Official No. _____; Signal Letters _____ State if Machinery is fitted aft No.

How are the surfaces preserved from oxidation? Inside Cement in F & A. Peaks & in D.B. in Machs Outside Paint
Space only. Paint.

PARTICULARS OF WATER BALLAST.—State whether the Double bottom is constructed on the cellular system or with girders on floors Cellular System

Where Fitted.	Length.	Water Capacity.	Where Fitted.	Length.	Water Capacity.
	Feet.	Tons.		Feet.	Tons.
Double bottom, aft,	112.5	312	Fore peak tank,	18.17	70
Double bottom, under Engines and Boilers,	✓	✓	After peak tank,	28.0	221
Double bottom, if under Engines only,	20.0	81	Deep tank, aft,	✓	✓
Double bottom, if under Boilers only,	20.0	Dry Tank.	Deep tank, forward,	✓	✓
Double bottom, forward,	154.0	459	Other tanks, if fitted,	✓	✓
Total capacity of double bottom	306.5	852	(If necessary, furnish further information by sketch.)		

* The wells are not to be included in the lengths of the tanks. 6.5

State whether the above have been tested as required by the Rules. Yes

Order for Special Survey No. 5430

Date 25.9.19

No. 541 in builder's yard.

DATES of Surveys held while building

1920. Apr. 28. 29. May 11. 13. 19. 21. 21. June 11. July 5. 15. 19. 28. Aug. 5. 6. 12. 24. 26. Sep. 15. 23.
Oct. 7. 12. 19. 14. 16. 19. 21. 29. 26. 27. 28. 30. Nov. 5. 8. 10. 13. 17. Jan. 19. 27.
Hull: Feb. 3. 7. 10. 16. 18. Mar. 1. 2. 8. 14. 16. Apr. 4. 7. 8.

Total No. of Visits 51

Surveyor's Signature W. E. Gray & Arthur Scullard.