

REPORT ON ELECTRIC FITTINGS.

(OTHER THAN FOR THE PROPULSION OF THE VESSEL)

Date of writing Report 10-3-1931 When handed in at Local Office 10 Port of Rotterdam

No. in Survey held at Rotterdam Date, First Survey 27 Jan 1931 Last Survey 26 Feb 1931
Reg. Book. (Number of Visits 4)

on the SEA STEAM TUG "EBRO" Tons { Gross
Net

Built at ROTTERDAM By whom built P. SMIT, SCHEEPSWERYEN Yard No. 475 When built 1931
EN MACHINEFABRIEK.

Owners SMIT & CO'S INTERNATIONALE SLEEDIENST Port belonging to ROTTERDAM.

Electric Light Installation fitted by N.V. ELECTROTECHN. BUREAU Contract No. _____ When fitted 1931
A. DE HOOP

Is the Vessel fitted for carrying Petroleum in bulk no

System of Distribution TWO WIRE

Pressure of supply for Lighting 110 volts, Heating _____ volts, Power _____ volts.

Direct or Alternating Current, Lighting DIRECT Power _____

If alternating current system, state frequency of periods per second _____

Has the Automatic Governor been tested and found efficient when the whole load is suddenly thrown on or off yes

Generators, do they comply with the requirements regarding rating YES, are they compound wound YES

are they over compounded 5 per cent. YES, if not compound wound state distance between each generator _____

Where more than one generator is fitted are they arranged to run in parallel _____, is an adjustable regulating resistance fitted in series with each shunt field YES

Are all terminals accessible, clearly marked, and furnished with sockets YES, are they so spaced or shielded that they cannot be accidentally earthed, short circuited, or touched YES Are the lubricating arrangements of the generators as per Rule YES

Position of Generators IN ENGINE ROOM

is the ventilation in way of the generators satisfactory YES, are they clear of all inflammable material YES

if situated near unprotected woodwork or other combustible material, state distance of same horizontally from or vertically above the generators _____ and _____, are the generators protected from mechanical injury and damage from water, steam or oil YES

are their axes of rotation fore and aft YES

Earthing, are the bedplates and frames of the generating plant efficiently earthed YES are the prime movers and their respective generators in metallic contact YES

Main Switch Boards, where placed IN ENGINE ROOM

If the generators and main switchboard are not placed in the same compartment, is each generator provided with a fuse on each insulated pole as near as possible to the terminals of the generator, additional to that provided on the main switchboard _____

Switchboards, are they placed in accessible positions, free from inflammable gases and acid fumes YES

are they protected from mechanical injury and damage from water, steam or oil YES, if situated near unprotected woodwork or other combustible material, state distance of same horizontally from or vertically above the switchboards _____ and _____

are they constructed wholly of durable, non-ignitable non-absorbent materials YES, is all insulation of high dielectric strength and of permanently high insulation resistance YES, if semi-insulating material is used, are all conducting parts insulated from the slab

with mica or micanite or other non-hygroscopic insulating material, and the slab similarly insulated from its framework _____, and is the frame effectively earthed YES Are the fittings as per Rule regarding:— spacing or shielding of live parts

YES, accessibility of all parts YES, absence of fuses on back of board YES, proportion of omnibus bars YES, individual fuses to voltmeter, pilot or earth lamp YES, connections of switches YES

Main Switchgear, description of switchgear for each generator and each outgoing circuit, and arrangement of equalizer switches

1 DOUBLE POLE SWITCH AND 2 SINGLE POLE FUSES

Instruments on main switchboard 1 ammeters 1 voltmeters _____ synchronising device for paralleling purposes.


Earth Testing, state what means are provided at the main switchboard for indicating the state of the insulation of the system

EARTH LAMPS

Switches, Circuit Breakers and Fusible Cut-outs, do these comply with the requirements of the Rules YES

Joint Boxes Section and Distribution Boards, is the construction, protection, insulation, material, and position of these as per rule

YES



© 2020

Lloyd's Register Foundation

002725 - 002735 - 0067 2

Cables: Single, twin, concentric, or multicore SINGLE AND TWIN are the cables insulated and protected as per Tables IV or V of the Rules YES

Fall of Pressure, state maximum between bus bars and any point of the installation under maximum load 2.2 VOLT

Cable Sockets and other connections, are the ends of all cables having a sectional area of 0.04 square inch and above provided with soldering sockets YES

Paper Insulated Cables. If cables are paper covered, is the dielectric at the exposed ends of the conductor protected from moisture by being suitably sealed with insulating compound _____

Cable Runs, are the cables fixed as far as possible in accessible positions not exposed to drip or accumulation of water or oil, or to high temperature from boilers, steam pipes, uptakes or other hot objects, or to avoidable risk of mechanical damage YES

Support and Protection of Cables, state how the cables are supported and protected SUPPORTED BY METAL CLIPS, PROTECTED BY ARMOURING AND WHERE NECESSARY BY TUBES.

If cables are run in wood casings, are the casings and caps secured by screws _____, are the cap screws of brass _____, are the cables run in separate grooves _____ . If armoured and lead covered cables are secured by metal clips, are the clips spaced as per Table VIII YES

Refrigerated Chambers, if lights are fitted, are the cables and fittings in accordance with the special requirements _____

Joints in Cables, state if any, and how made, insulated, and protected _____

Watertight Glands and Deck Tubes, are all cables passing through decks and watertight bulkheads provided with deck tubes or watertight glands YES

Bushes in Beams and Non-watertight Partitions, where unarmoured cables pass through beams and non-watertight partitions, are the holes efficiently bushed YES state the material of which the bushes are made LEAD

Earthing Connections, state what earthing connections are fitted and their respective sectional areas _____, are their connections made as per Rule _____

Alternative Lighting, are the groups of lights in the propelling machinery space arranged as per Rule YES

Emergency Supply, state position and method of control of the emergency supply and how the generator is driven _____

Navigation Lamps, are these separately wired YES, controlled by separate switch and separate fuses YES, are the fuses double pole YES, are the switches and fuses grouped in a position accessible only to the officers on watch YES, has each navigation lamp an automatic indicator as per Rule YES

Secondary Batteries, are they constructed and fitted as per Rule _____

Fittings, are all fittings on weather decks, in stokeholds and engine rooms and wherever exposed to drip or condensed moisture, watertight YES, are any fittings placed in spaces in which goods are liable to be stacked in close proximity to them; if so, how are they protected _____, are any fittings placed in spaces where inflammable or explosive dust or gases are liable to be present, if so, how are they protected _____, how are the cables led _____, where are the controlling switches situated _____

Searchlight Lamps, No. of 1, whether fixed or portable FIXED, are their fittings as per Rule YES

Are Lamps, other than searchlight lamps, No. of _____, are their live parts insulated from the frame or case _____, are their fittings as per Rule _____

Motors, are their working parts readily accessible _____, are the coils self-contained and readily removable for replacement _____, are the brushes, brush holders, terminals and lubricating arrangements as per Rule _____, are the motors placed in well-ventilated compartments in which inflammable gases cannot accumulate and clear of all inflammable material _____, are they protected from mechanical injury and damage from water, steam or oil _____, are their axes of rotation fore and aft _____, if situated near unprotected woodwork or other combustible material, are the motors of the totally enclosed, pipe ventilated, forced draught, drip or flame proof type _____, if not of this type, state distance of the combustible material horizontally or vertically above the motors _____ and _____

Control Gear and Resistances, are the generator field and motor speed regulators, starters and controllers constructed and fitted as per Rule YES

Lightning Conductors, where lightning conductors are required, are these fitted as per Rule YES NONE

Ships carrying Oil having a Flash Point less than 150° F. Have the special requirements of the Rules been complied with regarding switches, joint boxes, section and distribution boards, protection of cables, method of distribution, lead of cables, lights and fittings _____

If portable lamps for use in dangerous spaces are supplied, are they of a type approved by the Home Office _____

PARTICULARS OF GENERATING PLANT.

DESCRIPTION OF GENERATOR.	No. of	RATED AT				DRIVEN BY	WHERE DRIVEN BY AN INTERNAL COMBUSTION ENGINE.	
		Kilowatts.	Volts.	Amps.	Revs. per Min.		Fuel Used.	Flash Point of Fuel.
MAIN ...	1	5.6	110	50	480	STEAM ENGINE		
AUXILIARY ...								
EMERGENCY ...								
ROTARY TRANSFORMER								

GENERATOR, LIGHTING AND HEATING CONDUCTORS.

DESCRIPTION.	CONDUCTORS.		COMPOSITION OF STRAND.		TOTAL MAXIMUM CURRENT. AMPERES.		Approximate Length. (Lead and Return.) Feet.	Insulated with	HOW PROTECTED.
	No. per Pole.	Total Effective Area per Pole Sq. Ins.	No.	Diameter. m.m.	In Circuit.	Rule.			
MAIN GENERATOR ...	1	25	7	2.13	42	64	12	RUBBER	LEAD COVERED AND ARMOURED
EQUALISER CONNECTIONS									
AUXILIARY GENERATOR ...									
EMERGENCY GENERATOR									
ROTARY TRANSFORMER MOTOR GENERATOR ...									
ENGINE ROOM ...	1	2.5	1	1.79	6	12	6	"	"
BOILER ROOM ...									
AUXILIARY SWITCHBOARDS									
STEERING GEAR ROOM	1	6	7	1.05	9	30	130	"	"
WHEEL HOUSE	1	4	7	0.86	7	20	146	"	"
ACCOMMODATION ...									
WIRELESS ...	1	6	7	1.05	9	30	72	"	"
SEARCHLIGHT ...	1	6	7	1.05	14	30	70	"	"
MASTHEAD LIGHT ...	1	1.5	1	1.39	1	8	105	"	"
SIDE LIGHTS ...	1	1.5	1	1.39	1	8	46	"	"
COMPASS LIGHTS ...	1	1.5	1	1.39	1	8	12	"	"
POOP LIGHTS ...	1	1.5	1	1.39	1	8	166	"	"
CARGO LIGHTS ...	1	1.5	1	1.39	1	8	82	"	"
ARC LAMPS ...									
HEATERS ...									

MOTOR CONDUCTORS.

DESCRIPTION.	No. of Motors.	CONDUCTORS.		COMPOSITION OF STRAND.		TOTAL MAXIMUM CURRENT. AMPERES.		Approximate Length. (Lead and Return.) Feet.	Insulated with	HOW PROTECTED.
		No. Per Pole.	Total Effective Area per Pole Sq. Ins.	No.	Diameter.	In Circuit.	Rule.			
BALLAST PUMP ...										
MAIN BILGE LINE PUMPS										
GENERAL SERVICE PUMP										
EMERGENCY BILGE PUMP										
SANITARY PUMP ...										
CIRC. SEA WATER PUMPS										
CIRC. FRESH WATER PUMPS...										
AIR COMPRESSOR ...										
FRESH WATER PUMP ...										
ENGINE TURNING GEAR...										
ENGINE REVERSING GEAR										
LUBRICATING OIL PUMPS										
OIL FUEL TRANSFER PUMP...										
WINDLASS ...										
WINCHES, FORWARD ...										
WINCHES, AFT ...										
STEERING GEAR—										
(a) MOTOR GENERATOR...										
(b) MAIN MOTOR ...										
WORKSHOP MOTOR ...										
VENTILATING FANS ...										

All Conductors are of annealed copper conforming to British Standard Specification No. 7.

The Insulated Conductors are guaranteed to withstand the immersion and resistance tests specified in the Rules.

The foregoing is a correct description.

[Handwritten signature]

N.V. ELECTROTECHN. BUREAU A. DE HOOP.

Electrical Engineers.

Date 16-2-31

COMPASSES.

Distance between electric generators or motors and standard compass 50 FEET

Distance between electric generators or motors and steering compass 50 FEET

The nearest cables to the compasses are as follows:—

A cable carrying 0.3 Ampères 2 feet from standard compass 2 feet from steering compass.

A cable carrying Ampères feet from standard compass feet from steering compass.

A cable carrying Ampères feet from standard compass feet from steering compass.

Have the compasses been adjusted with and without the electric installation at work at full power

Has the effect of switching on and off circuits, motors and other electro-magnetic apparatus within the vicinity of the compasses been noted

The maximum deviation due to electric currents was found to be degrees on course in the case of the standard

compass, and degrees on course in the case of the steering compass.

N.V. MACHINEFABRIEK & SCHEEPSWERF
van PERMIT Jr., ROTTERDAM.

[Handwritten signature]

Builder's Signature.

Date

Is this installation a duplicate of a previous case *no* If so, state name of vessel

General Remarks (State quality of workmanship, opinions as to class, &c.)

The electric light installation has been made and fitted in accordance with the Rules and has run satisfactorily during a trial under full working conditions.

It is submitted that this vessel is eligible to remain as CLASSED.

Elec. Light

[Handwritten initials]

20/3/31

[Handwritten initials]

Total Capacity of Generators Kilowatts.

The amount of Fee ... *fl 25000* When applied for, 19.

Travelling Expenses (if any) £ : : *25-3-31* When received, *[Handwritten]*

[Handwritten signature]
Surveyor to Lloyd's Register of Shipping.

Committee's Minute

WED. 8 APR 1931

Assigned

Elec. Light

1m. 9. 20.—Transfer.
(The Surveyors are requested not to write on or below the space for Committee's Minute.)



© 2020

Lloyd's Register Foundation