


SCANTLING

SHELL PLATING.

RIVETING.

STRAKE	AS IN VESSEL				ANY DEPARTURE FROM APPROVED PLANS TO BE NOTED.	EDGES STATE IF JOGGLED.			NO. OF ROWS OF RIVETS	BUTTS.		STRAPPED OR LAPPED
	AMID BREADTH INCHES	SHIP THICKNESS INCHES	FORWARD THICKNESS INCHES	AFT. THICKNESS INCHES		SINGLE OR DOUBLE	RIVETS DIAM. INCHES	SPACING CR TO CR INCHES		RIVETS DIAM. INCHES	SPACING CR TO CR INCHES	
FLAT PLATE KEEL	39	1/2"	7/16	7/16		DOUBLE	3/4	3.6	2	3/4	3.6	STRAPPED
" DBLG. (IF ANY)	✓	✓	✓	✓		✓	✓	✓	✓	✓	✓	✓
BOTTOM PLATING, NO. OF STRAKES	67	7/16	7/16	7/16		"	"	"	"	"	"	LAPPED
BILGE PLATING, NO. OF STRAKES	66	7/16	7/16	3/8		"	"	"	"	"	"	"
SIDE PLATING, NO. OF STRAKES	67 1/2	7/16	7/16	3/8		"	"	"	"	"	"	"
UPPER DECK, SHEER- STRAKE IN WELLS	59	1/2	1/2	1/2		"	"	"	"	"	"	"
UPPER DECK, SHEER- STRAKE IN BRIDGE								3.14" Throughout			3.14"	
STRAKE BELOW SHEER- STRAKE IN WELLS.								See letter 2.4.51			D.H.	
STRAKE BELOW SHEER- STRAKE IN BRIDGE												
POOP SIDE PLATING												
BRIDGE SIDE PLATING								3.14"				
FORECASTLE SIDE PLATING.	75	5/10	5/10	5/16		SINGLE	3/4"	3.6	ONE	3/4	3.6	LAPPED

002725 - 002735 - 0089



© 2020

Lloyd's Register
Foundation