

NOTE.—  
depth is m  
when ve  
afton, the  
of meas  
should be r  
lumb  
cks)

PARTICULARS FOR FREEBOARD.



Nos. 510-11-12 & 13. Name ..... 427.7'

Registered Length..... 57.3'

Registered Breadth..... 27.18' (27.12)

Registered Depth to Tank..... 50.30

Registered tonnage, under deck ..... 425'

Length on Load Line ..... 38.5'

Depth moulded..... 13 1/2'

Camber of Weather deck..... 55' (57.6)

Length of weather deck beam ..... 4'

Rule thickness of wood deck..... 108"

Sheer deck at side forward at perp. through L. Line (in ins.)..... 60"

" " " " aft " " " " " " 53"

" " " 1/8th L. on L.L. from perp. ford..... 33"

" " " " " " " " " aft.....

Length of forecasile.(actual on deck) ..... Height.....

Overhang of forecasile deck abaft bulkhead ..... Height.....

Length of Bridge on deck..... Height.....

Overhang of Bridge deck beyond forward bulkhead.....

" " " " " aft " " " " " " " " " " " "

Length of Poop on deck from aft perp..... Height.....

Overhang of poop deck beyond bulkhead ..... Height.....

Bulkhead at aft end of forecasile.....

Bulkhead at fore end of bridge.....

Stiffening to forward bridge bulkhead ..... Height.....

Bulkhead at fore end of poop..... To Rule.....

Number and size of freeing ports..... 3"

Height of hatch coamings above deck..... To Rule. Covers..... 3"

Sizes of hatches 1. 24.9' x 22.0' 2. 30.0' x 22.0' 3. 30.0' x 22.0' 4. 33.0' x 22.0' 5. 33.0' x 22.0' .....

Number of scuppers..... To Rule.....

Height of lowest side scuttle above base..... 24.25'

Droop in Tank..... None..... Half breadth.....

Deck sheathing..... 3" Oregon Pine on shell & DE.....

Ceiling..... 22 on bridges & under hatches Sparring..... 6" x 2" Whitewood.....

Displacement at..... 26.0' W.L. 13140 Tons

Tons per inch..... 26.0' W.L. 46.6 Tons

Complete Shelter Deck 8'-9" high  
with 6'-0" tonnage opening  
& 2 Bulkheads.