

PARTICULARS OF LONGITUDINAL FRAMING.

FRAMING.	AMIDSHIPS.			ENDS.			AMIDSHIPS.			ENDS.			RIVETING.					
	In Ship.			In Ship.			Per Rule or as approved.			Per Rule or as approved.			Rivets in Longitudinal Frames.		Spacing of Rivets on each side of Transverses and Bulkheads.		Rivets in Brackets to Bulkheads.	
	Ins.	Ins.	Ins.	Ins.	Ins.	Ins.	Ins.	Ins.	Ins.	Ins.	Ins.	Ins.	Ins.	Ins.	Ins.	Inches.	Number.	Diameter.
L or R																		
Between Decks...	8	3 1/2	375				8	3 1/2	375					7/8	6675	3.327	for 6 rivets each side.	
Farthest Continuous No. 1	8	3 1/2	375				8	3 1/2	375								9	7/8"
" 2	8	3 1/2	375				8	3 1/2	375									
" 3	8	3 1/2	375				8	3 1/2	375									
" 4	8	3 1/2	375	Same as			8	3 1/2	375	Same as					10			
" 5	8	3 1/2	375	amidships			8	3 1/2	375	amidships								
" 6	8	3 1/2	40				8	3 1/2	40									
" 7	8	3 1/2	46				8	3 1/2	46						14			
" 8	9	3 1/2	44				9	3 1/2	44									
" 9	9	3 1/2	48				9	3 1/2	48									
" 10	8	3 1/2	375				8	3 1/2	375						8			
" 11	8	3 1/2	375				8	3 1/2	375									
" 12																		
" 13																		
" 14																		
" 15																		
" 16																		
Amidships			27						27									
At Ends																		
Top Longitudinals	8	3 1/2	375	8	3 1/2	375	8	3	375	9	3	375	7/8	6675	3.337	for 8 rivets each side		
Bottom	9	3 1/2	375	8	3 1/2	375	8	3 1/2	375	8	3 1/2	375						
Longitudinals { Amidships			28						28									
{ At Ends...						21						21						
Transverses																		
Depth and Thickness	23-12	40		6	3 1/2	375	000	23-12	40	6	3 1/2	375	000					
Angles	3 1/2	3 1/2	437					3 1/2	3 1/2	44								
Lugs to Shell*	3 1/2	3 1/2	375			logged		3 1/2	3 1/2	38				7/8			Number of rivets in lugs as approved	
Depth and Thickness																		
Angles																		
Lugs to Shell*																		
Depth and Thickness	23 1/2	46						23	46									
Angles	6	6	75	00				9	3 1/2	70	00			7/8			Number of rivets in lugs as approved	
Lugs to Shell*	6	6	46			logged		6	6	46							Double to upper deck in fore hold	
Brackets			46						46								for 4 spaces above lower top in remainder	
Side Frames	133 1/2					84		133 1/2				94						
Plating or liners.																		
Bridge Deck	7	3 1/2	34					7	3	34					36-42			
Fore and Aft																		
Upper	7	3 1/2	34					7	3	34					30-36			
Second																		
Third																		
Transverse																		
Beams																		
Upper chock																		

If framing in peaks (if ordinary), Floors, Centre Girder, Side Girders and Margin Plate and their angle attachments, etc., to be entered in their respective places provided for on the Report Forms.

3:—This slip to be pasted on the fourth page of the Report, and reference to same to be made under framing, etc., on the first page.

002947-003005-0039