

Do all the Frames extend to the top height in the Poop? *Yes* Raised Quarter Deck? *Yes* Bridge House? *Yes* Forecastle? *Yes*
 To what height do the Reverse Frames extend? *Longitudinal framing (Bracketless System)*
 Has the Poop or Raised Quarter Deck an efficient Iron Bulkhead at the fore end? *Yes* *Stiffeners 9 1/2 x 3 1/2 x .66 BA*
 Give particulars of the means for closing the openings in Bulkhead *Shifting boards full height fitted in channels pivoted to*
 Is the Poop or Raised Quarter Deck connected with the Bridge House? *Yes* Has the Bridge House an efficient Bulkhead at the fore end?
 Give particulars of the means for closing the openings in Bulkhead *Hinged Steel W.T. Doors*
 What is the thickness of the Bridge Front plating? *.44* and Coaming plate? *.48*
 Give scantlings and spacing of the Stiffeners *9 x 3 1/2 x .66 BA & 36" N.B.S. SECTIONS*
 Are ^{lugs} bracket plates fitted at each end of the Stiffeners? *Yes* Are hor'l. brackets fitted connecting Bridge Bulk'd. with Bulwarks? *Yes*
 Has the Bridge House an efficient Iron Bulkhead at the after end? *Yes*
 How are the openings closed? *Shifting boards full height fitted in channels pivoted to bulkhead & in addition plate with lock bolts.*
 Is the Forecastle at least as high as the main or top-gallant rail? *Yes* Has the Forecastle an efficient Iron or Wood Bulk'd. at after end? *Yes*
 Are the Engine and Boiler openings covered by a Bridge, Poop, Raised Quarter Deck, or enclosed by a Strong Iron or Steel Deckhouse? *Covered by Poop*
 If the openings are not so protected are the exposed parts of the Casings efficiently constructed? *Yes*
 Give thickness of plating; scantlings and spacing of Stiffeners
 What is the height of the exposed Casings? *Yes* Are suitable means provided for closing all openings in them in bad weather? *Yes*

Are the Weather Deck Hatchways efficiently constructed and at least equal to the requirements of Section 28 of the Rules for 1904-5? Give particulars below:— *Yes*


CARGO HATCH FORM

| Position and Size. | 8'-0" x 7'-0" | | | | | | | | | |
|----------------------------|--|-------------|--|-------|------------------|-------------------------------------|--------------------------|-------------------------|------------------|--------------------|
| Item. | Ship. | Rule. | Ship. | Rule. | Ship. | Rule. | Ship. | Rule. | Ship. | Rule. |
| COAMING | | | | | | | | | | |
| Height above top of DECK | <i>32"</i> | | <i>Main Tank & Summer Tank Hatches</i> | | <i>38 in</i> | <i>Rule 6'-0" x 4'-0"</i> | | | | |
| Thickness | Sides..... | <i>.44</i> | <i>Coamings</i> | | <i>36" x 40"</i> | <i>& stiffened as per Rules</i> | | | | |
| | Ends..... | <i>.44</i> | | | <i>Covers</i> | <i>.60</i> | | | | |
| SHIFTING BEAMS OR FITTINGS | Number | | <i>Fuel Bunker Hatches</i> | | <i>4</i> | <i>2'6" x 4'-0"</i> | <i>2</i> | <i>2'6" x 2'-2 1/2"</i> | | |
| | Section and Scantlings | <i>NONE</i> | <i>Coamings</i> | | <i>36" x 40"</i> | <i>Stiffened as per Rules.</i> | | <i>Coamings</i> | <i>36" x 40"</i> | <i>Covers .50-</i> |
| | Material | | | | <i>Covers</i> | <i>.60</i> | | | | |
| * FORE AND AFTERS. | Number | | <i>Cofferdam Hatches</i> | | <i>6</i> | <i>in</i> | <i>3'-5" x 2'-4 1/2"</i> | | | |
| | Section and Scantlings | <i>NONE</i> | <i>Coamings</i> | | <i>36" x 40"</i> | | | | | |
| | Material | | | | <i>Covers</i> | <i>.50</i> | | | | |
| HATCHES Thickness | <i>STEEL PLATE COVER .30 WITH 5 x 3 x 40 ANGLE STIFFERS SPACED 24"</i> | | | | | | | | | |
| Remarks..... | <i>FITTED WITH HINGES FOR & SECURED WITH TOGGLES SPACED 2'-0" APART.</i> | | | | | | | | | |

* The depth of Fore and Afters should be stated from the underside of the hatches in all cases.
 (If the sill of the lowest side scuttle will be less than 6 inches above the Indian Summer Load Line if assigned under the tables, state vertical distance from top of deck at side amidships to lower edge of lowest side scuttle.)

The following information is to be given in all Cases of vessels dealt with under Paras. 11, 12 (under 15 feet Moulded depth) and under Shelter Deck Rules.

What is the thickness of the Bridge Sheerstrake? _____ Strake between Main and Bridge Sheerstrakes? _____
 Delete the words that do not apply { The Crew are, are not, berthed in the bridge house.
 { The arrangements to enable them to get backwards and forwards from their quarters are, are not satisfactory.
 Length of Bulwarks in well *No BULWARK.* *OPEN RAIL*
 Area of Freeing Ports required by Para. 11 (a) each side of vessel = _____ Sq. ft.
 Ft. Tenths. Ft. Tenths. No. } Freeing Ports (each side of vessel) = _____ Sq. ft.
 Total deficiency or excess = _____ Sq. ft.



Show hereon line of Floors or Tank Top with position of any Breaks in same; also height of Peak Tank tops, &c., &c.
 State any special features in the construction of the Vessel *This vessel is an Oil Tanker & has been built on Joherswood Bracketless System in accordance with App'd Plans of this Section*
 Builder's name and yard number *Lithgown Limited No 820*
 Names of sister vessels *S. S. "YARRAVILLE"; "VOCO"; "PULPIT POINT"; "PLUME";*
 Owners *Vacuum Oil Co. Ltd.*
 Address *London.*