

IS "LETIZIA MONTANARI" REPORT SENOA No. 21150

OF PLATING ascertained by drilling, and comparison of same with the original thicknesses.

The thicknesses are in hundredths of an inch.

NOTE STRAKE ADJACENT TO HATCHWAY  
(P.S.) DOUBLED IN ADDITION TO  
DOUBLE ON STRINGER

AMIDSHIP.				FORWARD.				AFT.				DECK PLATING.			
Thickness by drilling.		Diminution if any.		Original Thickness.	Thickness by drilling.		Diminution if any.	Original Thickness.	Thickness by drilling.		Diminution if any.	ORIGINAL	REMARKS.		
Port.	Std.	Port.	Std.		Port.	Std.			Port.	Std.			Port.	Std.	FSS 46-48
				F.C.E.				POOP				(82)			
				46	45	46	1 0	42	41	42	1 0	(82)			
89	92	11	8	46	42	58	4 -	46	52	48	- -	(76)	60	62	
68	67	9	10	46	44	48	2 -	46	50	58	- -	(66)	48	62	
58	60	6	4	48	42	48	6 0	48	40	46	8 2	(66)	47	58	
63	64	1	0	48	48	48	0 0	48	72	78	- -	(66)	50	66	
60	62	4	2	48	58	56	- -	48	48	48	0 0	(66)	47	70	
73	72	3	4	-				-	72	74	- -	(66)	52		
08	67	8	9	87	STEALERS	STEALERS		52	STEALERS	STEALERS		(66)	54		
65	66	11	10	87				52				(66)	54		
66	66	10	10	87				52				(66)	54		
66	68	10	8	87	80	84	7 3	52	60	79	- -	(66)	54		
97		3		100	cement*			86	cement*			(76)	64	62	
												(82)	64	62	
												(82)	72	63	

cement adhering satisfactory.

STEEL

LINE OF NEW OPENINGS

PORT

Lloyd's Register

ement adhering satisfactorily.

Drillings at ends to be made in the vicinity of the peak bulkheads.

Lloyd's Register  
Foundation

classed +100 A1 and

003706-003711-0265