

Lloyd's Register of Shipping.  
SURVEYS FOR FREEBOARD.  
(COMPUTATION FOR STEAMER, SAILING SHIP, TANKER.)

Ship's Name <i>Marcella</i>	Official Number	Nationality and Port of Registry	Gross Tonnage	Date of Build	Port of Survey
Moulded Dimensions: Length <i>328.5</i> Breadth <i>46.0</i> Depth <i>25.5</i>					Date of Survey <i>24.12.41</i>
Moulded displacement at moulded draught = 85 per cent. of moulded depth _____ tons					Surveyor's Signature
Coefficient of fineness for use with Tables <i>.78 (assumed)</i>					Particulars of Classification

<b>DEPTH FOR FREEBOARD (D).</b> Moulded depth ... .. <i>25.50</i> Stringer plate ... .. <i>.05</i> Sheathing on exposed deck $T \left( \frac{L-S}{L} \right) =$ Depth for Freeboard (D) = <i>25.55</i>	<b>DEPTH CORRECTION.</b> (a) Where D is greater than Table depth (D-Table depth) R = <i>(25.55 - 21.90) x 2.52 = + 9.22</i> (b) Where D is less than Table depth (if allowed) (Table depth-D) R = If restricted by superstructures	<b>ROUND OF BEAM CORRECTION.</b> Moulded Breadth (B) <i>46</i> Standard Round of Beam = $\frac{B \times 12}{50} =$ <i>11.04</i> Ship's Round of Beam = <i>11.50</i> Difference <i>.46</i> Restricted to Correction = $\frac{\text{Diff}^e}{4} \times \left( 1 - \frac{S_1}{L} \right) =$ <i><math>\frac{.46}{4} \times .4734 = -.05</math></i>
---	---	--

<b>DEDUCTION FOR SUPERSTRUCTURES.</b>					Standard Height of Superstructure <i>6.785</i>	
	Mean Covered Length (S)	Equivalent Enclosed Length (S <sub>1</sub> )	Height	Height Correction	Effective Length (E)	" " R.Q.D.
Poop enclosed ... ..	<i>42.50</i>	<i>42.50</i>	<i>7.5</i>	-	<i>42.50</i>	
" overhang ... ..						
R.Q.D. enclosed ... ..						
" overhang ... ..						
Bridge enclosed ... ..	<i>94.00</i>	<i>94.00</i>	<i>7.5</i>	-	<i>94.00</i>	
" overhang aft ... ..						
" overhang forward ... ..						
F'cle enclosed ... ..	<i>36.50</i>	<i>36.50</i>	<i>7.5</i>		<i>36.50</i>	
" overhang ... ..						
Trunk aft ... ..						
" forward ... ..						
Tonnage opening aft ... ..						
" " forward ... ..						
Total ... ..	<i>173.00</i>	<i>173.00</i>			<i>173.00</i>	
					Percentage covered $\frac{S}{L} =$	
					" $\frac{S_1}{L} =$	<i>52.66</i>
					" $\frac{E}{L} =$	
					Percentage from Table, Line A. (corrected for absence of forecastle (if required))	
					Percentage from Table, Line B. <i>38.66</i> (corrected for absence of forecastle (if required))	
					Interpolation for bridge less than .2L (if required)	
					Deduction = <i>37.23 x .3866 = - 14.39</i>	

<b>SHEER CORRECTION.</b>									
Station	Standard Ordinate	S	M	Product	Actual Ordinate	Effective Ordinate	S	M	Product
A.P. ... ..	<i>42.85</i>	1		<i>42.85</i>	<i>30.0</i>	<i>30</i>	1		<i>30.0</i>
$\frac{1}{4}$ L from A.P. ... ..	<i>19.06</i>	4		<i>76.24</i>	<i>8.0</i>	<i>8</i>	4		<i>32.0</i>
$\frac{3}{4}$ L " ... ..	<i>4.71</i>	2		<i>9.42</i>	-	-	2		-
Amidships ... ..	-	4		-	-	-	4		-
$\frac{3}{4}$ L from F.P. ... ..	<i>9.42</i>	2		<i>18.84</i>	<i>12.0</i>	<i>12</i>	2		<i>24.0</i>
$\frac{1}{4}$ L " ... ..	<i>38.12</i>	4		<i>152.48</i>	<i>35.5</i>	<i>35.5</i>	4		<i>142.0</i>
F.P. ... ..	<i>85.70</i>	1		<i>85.70</i>	<i>73.5</i>	<i>73.5</i>	1		<i>73.5</i>
Total ... ..				<i>385.53</i>					<i>301.5</i>
Correction = $\frac{\text{Difference between sums of products}}{18} \left( .75 - \frac{S}{2L} \right) =$					<i><math>\frac{84.03}{18} \left( .75 - \frac{.2633}{48.67} \right) = + 2.27</math></i>				
If limited on account of midship superstructure.									
Mean actual sheer aft					Mean standard sheer aft =				
Mean actual sheer forward					Mean standard sheer forward =				
Length of enclosed superstructure forward of amidships =					L				
" " aft of " =					"				

<b>Deduction for Tropical Freeboard.</b> <b>Addition for Winter and Winter North Atlantic Freeboard.</b> Ft. Depth to Freeboard Deck = <i>25.53</i> Summer freeboard = <i>4.27</i> Moulded draught (d) = <i>21.26</i> Deduction for Tropical freeboard and addition for Winter freeboard = $\frac{d}{4}$ inches = <i>5.31 = 5 1/4</i> Addition for Winter North Atlantic Freeboard (if required) = <i>7 1/4</i>	<b>Deduction for Fresh Water.</b> Displacement in salt water at summer load water line $\Delta =$ Tons per inch immersion at summer load water line T = Deduction = $\frac{\Delta}{40 T}$ inches =	<b>TABULAR FREEBOARD</b> corrected for Flush Deck (if required) Correction for coefficient $\frac{.28 + .05}{1.86} = \frac{.43}{1.86}$ Depth Correction ... .. <i>9.22</i> Deduction for superstructures ... .. <i>- 14.39</i> Sheer correction ... .. <i>2.27</i> Round of Beam correction ... .. <i>- .05</i> Correction for Thickness of Deck amidships ... .. <i>- .19</i> Other corrections, scantlings, etc. ... .. Summer Freeboard = <i>51.20</i>
--	---	---

<b>SUMMER FREEBOARD amidships from Centre of Disc to top of Deck Line, Wood, Steel, Deck :-</b>			
Tropical Fresh Water Line above Centre of Disc ... ..	<i>11"</i>	Tropical Fresh Water Freeboard ... ..	<i>4'-3 1/4"</i>
Fresh Water Line " " ... ..	<i>5 3/4"</i>	Fresh Water " " ... ..	<i>3'-4 1/4"</i>
Tropical Line " " ... ..	<i>5 1/4"</i>	Tropical " " ... ..	<i>3'-9 1/2"</i>
Winter Line below " " ... ..	<i>5 1/4"</i>	Winter " " ... ..	<i>3'-10"</i>
Winter North Atlantic Line " " ... ..	<i>7 1/4"</i>	Winter North Atlantic " " ... ..	<i>4'-8 1/2"</i>



.....

.....

1954

[illegible]

Lloyd's Register  
Foundation