

Lloyd's Register of Shipping.

SURVEYS FOR FREEBOARD.—STEAM SHIPS.

MON. 5 NOV. 1923

Index No. 30822
(For London Office only.)

No. 28677

NEW RULES

PARTICULARS RELATING TO ALL STEAM SHIPS EITHER FLUSH DECKED, OR WITH TOP GALLANT FORECASTLES, SHORT POOPS AND BRIDGE HOUSES DISCONNECTED, OR WITH TOP GALLANT FORECASTLES HAVING LONG POOPS, OR RAISED QUARTER DECKS CONNECTED WITH BRIDGE HOUSES, OR OTHERWISE.

Sir John Priestman 16: ss no 286.

Ship's Name.	Port of Registry and Nationality.	Official Number.	Gross Tonnage.	Date of Build.	Particulars of Classification.
PENHALE	Falmouth British	146388	4071.07	1923 1924	# 100 A.1. (Contemplated)

Number in Register Book

Registered dimensions from Ship's Register.

Length.	Breadth.	Depth.	Under Deck Tonnage.
365.0	51.5	23.80	3721.86
364.12	51.5	23.80	3721.86
364.12	50.75	24.501	3721.86

Co-efficient of fineness..... 82 - .823

Any modification necessary { Para. 4 (a) to (e)]* } .02 -

Co-efficient as corrected 80 -

Sheer { Stem..... 90 } 138 ÷ 2 = 69 ...Mean $\frac{71.81 + 46.41}{2} = 58.61$ 36.125.40 - 71

Sheer at $\frac{1}{2}$ of the length from { Stem 53 Sternpost 26 } 79 ÷ 2 = 39.5 ...Mean

Gradual mean Sheer 69 + 71.81 ÷ 55% = 71.81

Standard mean Sheer [Table, Para. 18] 46.41 - Correction

Difference 23.99 ÷ 4 = 5.99 -

§ If limited as Para. 18 (f) -6 -

Rise in Sheer { At front of bridge house.....
from amidships [Para. 18 (e)] At after end of forecastle

¶ Fall in Sheer { Para. 18 (d) } ÷ 2 =

Length uncovered ✓ Correction

ALLOWANCE FOR DECK ERECTIONS:

Freeboard, Table C..... 3' 0 1/2 -

Correction for Length, if required (Para. 12, 13, and 14) + 3 1/2

Freeboard by Table A. corrected for sheer, and for length, if required (Para. 12, 13, and 14) } 3 - 3 3/4 -

Difference 6 - 2 1/4 -

Percentage as below..... 28.59 x 34.5 = 9.86 -

100

Correction for R. Q. Dk, if engine and boiler openings not covered by bridge house (Para. 11) }

Allowance for Deck Erections - 7 1/2 " 9 3/4 -

Length. Length allowed. Height.

Forecastle..... 31.0 31.0 7 0 1/2

Bridge House 102.1 102.08 7 0 1/2

† Raised Qr. Dk..... 102.1 102.08 7 0 1/2

Poop..... 31.3 31.25 7 0 1/2

Total 164.33 - 14513 -

Length of Ship 364.12

Corresponding percentage { Para. 11, 12, 13, or 14 } 28.59% -

FREEBOARD recommended amidships from centre of Disc to top of Statutory Deck Line, ~~Wood~~ (Steel) Deck:

Fresh Water Line above centre of Disc

Indian Summer Line " " " ...

Winter Line below " " " ...

Winter North Atlantic Line " " " ...

If the frames, skin planking, or ceiling are of unusual thickness the breadth of vessel to inside

In vessels obtaining an allowance for deck erections under Para. 11 where the sheer drops abait amid-

ships the height of the R.Q.D. is to be taken from the level of the top of the amidship beam.

In flush-decked vessels the total standard mean sheer means the sheer measured at the stem and stern-

post. In vessels having poops and forecastles, it means the sheer measured at points distant

one-eighth of the vessel's length from stem and stern-post.

J.W. = 8.900 - 5.81

38.31 x 40

004556-004563-0024

© 2020 Lloyd's Register Foundation

RECEIVED

MARKING FORM 10 NOV 1923

RECEIVED

Do all the Frames extend to the top height in the Poop?	Yes.	Raised Quarter Deck?	✓	Bridge House?	yes	Forecastle?	yes
To what height do the Reverse Frames extend?	Bulk angle framing						
Has the Poop or Raised Quarter Deck an efficient Iron Bulkhead at the fore end?	yes.						
Give particulars of the means for closing the openings in Bulkhead	none						
Is the Poop or Raised Quarter Deck connected with the Bridge House?	✓	Has the Bridge House an efficient Bulkhead at the fore end?					
Give particulars of the means for closing the openings in Bulkhead	Steel hinged door						
What is the thickness of the Bridge Front plating?	.40	and Coaming plate?	.44				
Give scantlings and spacing of the Stiffeners	9 x 3½ x 50	bolt angle stiffener @ 30" apart					
Are bracket plates fitted at each end of the Stiffeners?	Lugged	Are hor'l. brackets fitted connecting Bridge Bulk'd. with Bulwarks?	yes				
Has the Bridge House an efficient Iron Bulkhead at the after end?	yes						
How are the openings closed?	With storm boards full height in riveted channels.						
Is the Forecastle at least as high as the main or top-gallant rail?	yes	Has the Forecastle an efficient Iron or Wood Bulk'd. at after end?	yes				
Are the Engine and Boiler openings covered by a Bridge, Poop, Raised Quarter Deck, or enclosed by a Strong Iron or Steel Deckhouse?	Covered by a Bridge						
If the openings are not so protected are the exposed parts of the Casings efficiently constructed?							
Give thickness of plating; scantlings and spacing of Stiffeners							
What is the height of the exposed Casings?		Are suitable means provided for closing all openings in them in bad weather?					
Are the Weather Deck Hatchways efficiently constructed and at least equal to the requirements of Section 28 of the Rules for 1904-5? Give particulars below:		yes					
FORE DECK → AFTER DECK							
Position and Size.	N°1 - 25'-0" x 18'-0"	N°2 - 31'-3" x 18'-0"	N°3 - 10'-5" x 16'-0"	N°4 - 29'-2" x 18'-0"	N°5 - 25'-0" x 18'-0"		
Item.	Ship.	Rule.	Ship.	Rule.	Ship.	Rule.	Ship.
COAMING Height above top of DECK	3'-6"	3'-6"	3'-6"	2'-6"	3'-6"	3'-6"	3'-6"
Thickness { Sides.....	.44	.44	.44	.44	.44	.44	.44
Thickness { Ends.....	.44	.44	.44	.44	.44	.44	.44
SHIFTING BEAMS OR WEB PLATES.	Number	4	4	5	1	5	4
	Section and Scantlings	16½-8¼ x 36	16½-8¼ x 36	7½	12½ x 8¼ x 36	7½	7½
	Material	4 x 3 x 44	4 x 3 x 44	11	3½ x 3½ x 42	11	11
	Steel.	Steel	Same as N°1	Steel	Steel	Same as N°1	Same as N°1
* FORE AND AFTERS.	Number						
	Section and Scantlings						
	Material						
HATCHES Thickness	3	3	3	3	3	3	3
Remarks.....	Food.	Food	Food	Food	Food	Food	Food

* The depth of Fore and Afters should be stated from the underside of the hatches in all cases.

(If the sill of the lowest side scuttle will be less than 6 inches above the Indian Summer Load Line if assigned under the tables, state vertical distance from top of deck at side amidships to lower edge of lowest side scuttle.)

The following information is to be given in all Cases of vessels dealt with under Paras. 11, 12 (under 15 feet Moulded depth) and under Shelter Deck Rules.

What is the thickness of the Bridge Sheerstrake?

Strake between Main and Bridge Sheerstrakes?

Delete the words { The Crew are, are not, berthed in the bridge house.

that do not apply { The arrangements to enable them to get backwards and forwards from their quarters are, are not satisfactory.



Length of Bulwarks in well Fore deck 100 ft. After deck 100 ft.

Area of Freeing Ports required by Para. 11 (e) each side of vessel = 70.08 Sq. ft.

Ft. Tenths. Ft. Tenths. No. = 70.00 Sq. ft.

Fore deck	4.0	x	1.46	x	6	Freeing Ports (each side of vessel)	=	70.00	Sq. ft.
After sk.	4.0	x	1.46	x	6				

Total deficiency or excess = .08 Sq. ft.



Show hereon line of Floors or Tank Top with position of any Breaks in same; also height of Peak Tank tops, &c., &c.

State any special features in the construction of the Vessel

Poop Bridge Forecastle

{ Draft Scale, Tons per
attached herewith

Builder's name and yard number Sir John Priestman & Co. Ltd. 112 No 286,

Names of sister vessels

Owners R. B. Chellens Ship. Nav. Co. Ltd. (7 Shearman Mgr.)

" Address 47 Stewart street, Cardiff.

Fee £ 10:
Will be charged on completion

Received by me See F. G. Report.

© 2020

Lloyd's Register
Foundation