

PARTICULARS OF PROTECTION TO OPENINGS, ETC.

HATCHWAYS ON FREEBOARD AND SUPERSTRUCTURE DECKS										
Description of Hatchway	BRIDGE DK					Fore Peak	Bridge	Saddle	T. DK	In Steering
	N ^o 1.	N ^o 2.	N ^o 3.	N ^o 4.	N ^o 5.	F'cle	Bunkers	back	Trimming	House
Dimensions of Hatchway	25'-0" x 18'-0"	31'-3" x 18'-0"	10'-5" x 16'-0"	29'-2" x 18'-0"	25'-0" x 18'-0"	4'-0" x 3'-0"	10'-4" x 3'-0"	5'-6" x 15'-0"	6'-0"	
COAMINGS	Height above Deck	3'-6"	3'-6"	2'-6"	3'-6"	3'-6"	9" BA	2'-6"	10" BA	2'-0" x 3'-6"
	Thickness	.44	.44	.44	.44	.44	.44	.44	.44	9" OA
	Stiffeners	7 x 3 BA	7 x 3 BA	7 x 3 BA	7 x 3 BA	7 x 3 BA				Coaming
	Brackets, Stays	2	3	1	3	2				Coaming
HATCH BEAMS	Number	4	5	1	5	4				
	Spacing									
	Scantling and Sketch	16 1/2 x 8 1/4 x 36 Angles 4 x 3 x 44	as N ^o 1	plate 12 1/2 x 8 1/4 x 44 angles 3 1/2 x 3 1/2 x 42	as N ^o 1	as N ^o 1				
	Bearing Surface	3"	3"	3"						
FORE AND AFTERS	Number									
	Spacing									
	Unsupported Lengths									
	Scantling* and Sketch	none	none	TDK 10'-5" x 16'-0" 9" BA cover 1 beam plate 14" x 42 angles 3 1/2 x 3 1/2 x 42	none	none				
	Bearing Surface			3"						
HATCH COVERS	Material	Wood								
	Thickness	2 1/2"	2 1/2"	2 1/2"	2 1/2"	2 1/2"	2 1/2"	2 1/2"	2 1/2"	2 1/2"
	How fitted	Ft A	Ft A	Ft A	Ft A	Ft A	Thwart	Thwart	Ft A	Thwart
	Bearing Surface	3"	3"	3"	3"	3"	3"	3"	3"	3"
Spacing of Cleats	24"	24"	24"	24"	24"	20"	23"	24"	24"	24"
Number of Tarpaulins	2	2	2	2	2	1	2	2	2	2
<p>*Are wood fore and afters steel shod at all bearing surfaces? <input checked="" type="checkbox"/></p> <p>Are battens and wedges efficient and in good condition? <input checked="" type="checkbox"/></p> <p>Are tarpaulins in good condition and in accordance with rule requirements? <input checked="" type="checkbox"/></p> <p>Are lashings provided in accordance with rule requirements? <input checked="" type="checkbox"/></p>										

Particulars of fiddle, funnel and ventilator coamings:— Fiddle gratings covered with hinged steel plates.
 Engine Room skylight of steel strongly constructed.
 Funnel & fiddle ventilator coamings efficient.

Particulars of Flush Bunker Scuttles:— none

Particulars of Companionways:— Hinged steel doors to storeroom from Bridge Dk & Bunkers in Bridge Space manipulated both sides.

Particulars of Ventilators in exposed positions on freeboard and superstructure decks:—
 F'cle Dk. 1 @ 7" dia 18" high - Bridge 2 @ 9" dia 30" high - Wood plug or canvas covers provided for all ventilators.
 2 @ 6" " 12" " - aft Dk 4 @ 18" " 36" "
 1 @ 4" " 4" " -
 F. Dk. 4 @ 18" " 36" " - Poop. 7 @ 6" " 18" "

Particulars of Air Pipes in exposed positions on freeboard, raised quarter, or superstructure decks:—
 F'cle Dk. 1 @ 2 1/2" dia to F'Pk - aft Dk. 2 @ 2 1/2" dia 28" high - Efficient closing appliances fitted
 Bridge Dk. 6 @ 3" " 11" high - Poop. 1 @ 3 1/2" " 12" " - no covers provided
 F. Dk. 3 @ 2 1/2" " 28" "

Particulars of Gangway Cargo and Coaling Ports:— none