

Lloyd's Register of Shipping.

SURVEYS FOR FREEBOARD.

(COMPUTATION FOR STEAMER, ~~SAILING SHIP~~, TANKER.)

Index. No. *35984*
(For London Office only).*No. 28070.*

Ship's Name <i>mp. KYLE FISHER.</i> <i>MARINA</i>	Official Number <i>163925</i>	Nationality and Port of Registry <i>BRITISH</i> <i>MARIEHAMN</i> <i>Danish.</i>	Gross Tonnage <i>not yet measured</i> <i>603.68</i> <i>608.72</i>	Date of Build <i>1938/</i> <i>1939</i>	Port of Survey <i>Helsingør</i>
Moulded Dimensions: Length <i>160'0"</i> Breadth <i>28'6"</i> Depth <i>12'10"</i>					Date of Survey <i>Building</i>
Moulded displacement at moulded draught = 85 per cent. of moulded depth <i>1004</i> tons					Surveyor's Signature <i>J. H. H. H.</i>
Coefficient of fineness for use with Tables <i>.707</i>					Particulars of Classification <i>+100 A1</i> <i>Contingent.</i>

Depth for Freeboard (D). <i>R.Q.D.</i>	Depth correction.	Round of Beam correction.
Moulded depth ... <i>12'10" 83 16 10</i>	(a) Where D is greater than Table depth (D - Table depth) R = <i>(12.86 - 10.67) 1.23 = + 2.69"</i>	Moulded Breadth (B) <i>28'6"</i>
Stringer plate ... <i>40'03 .36</i>	(b) Where D is less than Table depth (if allowed) (Table depth - D) R = <i>2.19</i>	Standard Round of Beam = $\frac{B \times 12}{50}$ = <i>6.84"</i>
Sheathing on exposed deck $T \left(\frac{L-S}{L} \right) =$	If restricted by superstructures	Ship's Round of Beam = <i>6"</i>
Depth for Freeboard (D) = <i>12.86</i>		Difference <i>.84 difference</i>
		Restricted to
		Correction = $\frac{\text{Diff}^{\circ}}{4} \times (1 - \frac{S_1}{L})$ = <i>.84 x .2748 = + .06</i>

DEDUCTION FOR SUPERSTRUCTURES.

	Mean Covered Length (S)	Equivalent Enclosed Length (S ₁)	Height	Height Correction	Effective Length (E)	
Poop enclosed ...	<i>45'3 1/2</i>	<i>45.29</i>	<i>7'3"</i>		<i>45.29</i>	Standard Height of Superstructure <i>6'00"</i>
.. overhang ...	<i>75</i>					.. " R.Q.D. <i>3'40"</i>
R.Q.D. enclosed ...	<i>53'9"</i>	<i>53.75</i>	<i>4'0"</i>		<i>53.75</i>	Deduction for complete superstructure <i>22'00"</i>
.. overhang ...						Percentage covered $\frac{S}{L} =$ <i>73.13</i>
Bridge enclosed...						.. " $\frac{S_1}{L} =$ <i>72.52</i>
.. overhang aft " $\frac{E}{L} =$ <i>72.52</i>
.. overhang forward						Percentage from Table, Line A. <i>66.10</i>
Fore enclosed <i>open</i>	<i>17'11 1/2</i>	<i>16.98</i>	<i>7'3"</i>		<i>16.98</i>	(corrected for absence of forecastle (if required))
.. overhang ...						Percentage from Table, Line B.
Trunk aft ...						(corrected for absence of forecastle (if required))
.. forward ...						Interpolation for bridge less than 2L (if required)
Tonnage opening aft ...						Deduction = <i>22 x .6610 = - 14.54"</i>
.. " forward						
Total ...	<i>117.00</i>	<i>116.02</i>			<i>116.02</i>	

SHEER CORRECTION.

Station	Standard Ordinate	S	M	Product	Actual Ordinate	Effective Ordinate	S	M	Product	
A.P. ...	<i>26.00</i>	1		<i>26.00</i>	<i>33"</i>	<i>75.43</i>	1		<i>75.43</i>	Mean actual sheer aft = <i>excess</i>
1/4 L from A.P. ...	<i>11.57</i>	4		<i>46.28</i>	<i>15"</i>	<i>33.56</i>	4		<i>134.24</i>	Mean standard sheer aft = <i>excess</i>
1/2 L " ...	<i>2.86</i>	2		<i>5.72</i>	<i>4 1/2"</i>	<i>8.30</i>	2		<i>16.60</i>	Mean actual sheer forward = <i>excess</i>
Amidships ...		4					4			Mean standard sheer forward = <i>excess</i>
3/4 L from F.P. ...	<i>5.72</i>	2		<i>11.44</i>	<i>7 1/2"</i>	<i>7.50</i>	2		<i>15.00</i>	Length of enclosed superstructure forward of amidships = <i>7.1L</i>
1/4 L " ...	<i>23.14</i>	4		<i>92.56</i>	<i>29"</i>	<i>29.00</i>	4		<i>116.00</i>	.. " aft of .. = <i>.5L</i>
F.P. ...	<i>52.00</i>	1		<i>52.00</i>	<i>66 1/2"</i>	<i>66.50</i>	1		<i>66.50</i>	
Total ...				<i>234.00</i>					<i>423.77</i>	

Correction = $\frac{\text{Difference between sums of products}}{18} \left(\frac{75 - S}{2L} \right) = \frac{189.77 - 36.57}{18} = -4.05"$
If limited on account of midship superstructure.

Actual Raised Quarter Deck Height *4.00*
Standard " " " " *3.40*
.. " " " " *.60*
.. " " " " *excess 7.20*

Mean actual sheer aft = *excess*
Mean standard sheer aft = *excess*
Mean actual sheer forward = *excess*
Mean standard sheer forward = *excess*

Length of enclosed superstructure forward of amidships = *7.1L*
.. " aft of .. = *.5L*

Deduction for Tropical Freeboard.
Addition for Winter and Winter North Atlantic Freeboard.

RAISED QUARTER
Depth to Freeboard Deck = *16.86* Ft.
Summer freeboard = *4.25*
Moulded draught (d) = *12.61*

Deduction for Tropical freeboard and addition for
Winter freeboard = $\frac{d}{4}$ inches = *3.15 = 3 1/4"*

Addition for Winter North Atlantic Freeboard (if required) = *5 1/4"*

Deduction for Fresh Water.

Displacement in salt water at summer load water line
 $\Delta =$ *1200*
Tons per inch immersion at summer load water line
 $T =$ *9.6*
Deduction = $\frac{\Delta}{40T}$ inches
= *3.13*
= *3 1/4"*

TABULAR FREEBOARD corrected for Flush Deck (if required)

Correction for coefficient $\frac{7074.68}{1.36} = \frac{1.387}{1.36}$

	+	-
Depth Correction ...	<i>2.69</i>	
Deduction for superstructures ...		<i>14.54</i>
Sheer correction ...		<i>2.40</i>
Round of Beam correction ...	<i>.06</i>	
Correction for Thickness of Deck amidships	<i>48.00</i>	
Other corrections, scantlings, etc. ...		
	<i>50.75</i>	<i>16.94</i>
Summer Freeboard =	<i>51.05</i>	

SUMMER FREEBOARD amidships from Centre of Disc to top of Deck Line, Wood, Steel, Deck:

Tropical Fresh Water Line above Centre of Disc	<i>4 1/4"</i>	<i>108 m/m</i>	Tropical Fresh Water Freeboard	<i>4'3"</i>	<i>1295 m/m</i>
Fresh Water Line	<i>3 1/4"</i>	<i>83 m/m</i>	Fresh Water	<i>3'10 3/4"</i>	<i>1187 m/m</i>
Tropical Line	<i>1"</i>	<i>25 m/m</i>	Tropical	<i>3'11 3/4"</i>	<i>1212 m/m</i>
Winter Line below	<i>3 1/4"</i>	<i>83 m/m</i>	Winter	<i>4'2"</i>	<i>(LIMITED) 1270</i>
Winter North Atlantic Line	<i>5 1/4"</i>	<i>133</i>	Winter North Atlantic	<i>4'6 1/4"</i>	<i>1378</i>
				<i>4'8 1/4"</i>	<i>1428</i>

28 APR 1939

Kyle Fisher

A new form should be prepared if any alterations that affect the freeboard have been made. If no such alterations have been made, the Surveyor should endorse the form on this side with his signature and the date.

$$\begin{array}{l} \text{Sheer at Loop front} \\ \text{Excess raised gr. dk. height} \end{array} \quad \begin{array}{l} 7'' \\ \frac{7.20}{14.20} \times \left(\frac{80}{34.71} \right)^2 \end{array} = 75.43'' \text{ virtual sheer @ A.P.}$$

$$\begin{array}{l} \text{Sheer @ AP} \quad 33 \\ \text{Loop height} \quad 87 \\ \hline 120 \\ \text{Stand. S. Q. D. ht.} \quad 40.8 \\ \hline 79.2 \end{array}$$

Trade of ship *Coasting Trade.*

Names of sister ships *✓*

Builder's name and yard number *Muns & Haan & Beulemans Thensden Yard N° 205.*

Owners *James Fisher & Sons.*

Fee *f 96.00*



© 2020

Lloyd's Register
Foundation