

Lloyd's Register of Shipping.

SURVEYS FOR FREEBOARD.

(COMPUTATION FOR STEAMER, SAILING SHIP, TANKER.)

Ship's Name <u>Puriri</u>	Official Number <u>273</u>	Nationality and Port of Registry <u>Harbour of New York</u>	Gross Tonnage <u>1860</u>	Date of Build <u>11.2.38</u>	Port of Survey <u>11.2.38</u>
Moulded Dimensions: Length <u>186.0</u> Breadth <u>35.0</u> Depth <u>14.0</u>					Surveyor's Signature <u>[Signature]</u>
Moulded displacement at moulded draught = 85 per cent. of moulded depth _____ tons					Particulars of Classification <u>10000 with 161</u>
Coefficient of fineness for use with Tables <u>assumed .78</u>					<u>Completed</u>

Depth for Freeboard (D). Moulded depth ... <u>assumed 11.95</u> Stringer plate ... <u>.04</u> Sheathing on exposed deck $T \left(\frac{L-S}{L} \right) =$ $\frac{.92}{11.95} =$ Depth for Freeboard (D) = <u>11.99</u>	Depth correction. (a) Where D is greater than Table depth (D - Table depth) R = (b) Where D is less than Table depth (if allowed) (Table depth - D) R = $(12.04 - 11.99) \times 1.43 = -.07$ If restricted by superstructures	Round of Beam correction. Moulded Breadth (B) Standard Round of Beam = $\frac{B \times 12}{50} =$ Ship's Round of Beam = <u>assumed nominal</u> Difference Restricted to Correction = $\frac{\text{Diff}^2}{4} \times \left(1 - \frac{S_1}{L} \right) =$ <u>N/A</u>
--	--	---

DEDUCTION FOR SUPERSTRUCTURES.

	Mean Covered Length (S)	Equivalent Enclosed Length (S _i)	Height	Height Correction	Effective Length (E)
Poop enclosed ...	<u>104.25</u>				
.. overhang ...	<u>106.08</u>				
R.Q.D. enclosed ...					
.. overhang ...					
Bridge enclosed ...					
.. overhang aft ...					
.. overhang forward ...					
F'cle enclosed ...	<u>31.50</u>				
.. overhang ...	<u>33.83</u>				
Trunk aft ...					
.. forward ...					
Tonnage opening aft ...	<u>139.91</u>				
.. forward ...	<u>135.75</u>				
Total ...					

Standard Height of Superstructure ... <u>6.0</u> ✓
.. R.Q.D. ...
Deduction for complete superstructure ... <u>24.6</u> ✓
Percentage covered $\frac{S}{L} =$ <u>75.22</u> ✓
.. $\frac{S_i}{L} =$ <u>72.78</u> ✓
.. $\frac{E}{L} =$
Percentage from Table, Line A. <u>66.67</u> <u>69.42</u> ✓
(corrected for absence of forecastle (if required))
Percentage from Table, Line B.
(corrected for absence of forecastle (if required))
Interpolation for bridge less than .2L (if required) <u>17.08</u> ✓
Deduction = $24.6 \times \frac{66.67}{100} =$ <u>16.40</u>

SHEER CORRECTION.

Station	Standard Ordinate	S	M	Product	Actual Ordinate	Effective Ordinate	S	M	Product
A.P. ...		1					1		
$\frac{1}{8}$ L from A.P. ...		4					4		
$\frac{2}{8}$ L " ...		2					2		
Amidships ...		4					4		
$\frac{2}{8}$ L from F.P. ...		2					2		
$\frac{1}{8}$ L " ...		4					4		
F.P. ...		1					1		
Total ...									

Correction = $\frac{\text{Difference between sums of products}}{18} \left(\frac{.75 - \frac{S}{2L}}{2L} \right) =$ N/A

If limited on account of midship superstructure.

If limited to maximum allowance of $1\frac{1}{2}$ ins. per 100 ft.

Deduction for Tropical Freeboard. Addition for Winter and Winter North Atlantic Freeboard. Depth to Freeboard Deck = <u>11.99</u> Summer freeboard = <u>29.42</u> Moulded draught (d) = <u>11.50</u> Deduction for Tropical freeboard and addition for Winter freeboard = $\frac{d}{4}$ inches = Addition for Winter North Atlantic Freeboard (if required) =	Deduction for Fresh Water. Displacement in salt water at summer load water line $\Delta =$ Tons per inch immersion at summer load water line $T =$ Deduction = $\frac{\Delta}{40T}$ inches =	TABULAR FREEBOARD corrected for Flush Deck (if required) Correction for coefficient $\frac{.78 + .68}{1.36} = \frac{1.46}{1.36}$ <table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th></th> <th>+</th> <th>-</th> </tr> <tr> <td>Depth Correction ...</td> <td></td> <td><u>17</u></td> </tr> <tr> <td>Deduction for superstructures ...</td> <td></td> <td><u>16.40</u></td> </tr> <tr> <td>Sheer correction ...</td> <td></td> <td><u>7.08</u></td> </tr> <tr> <td>Round of Beam correction ...</td> <td></td> <td></td> </tr> <tr> <td>Correction for Thickness of Deck amidships ...</td> <td></td> <td></td> </tr> <tr> <td>Other corrections, scantlings, etc. ...</td> <td></td> <td></td> </tr> <tr> <td>Summer Freeboard =</td> <td></td> <td><u>58.2</u></td> </tr> </table>		+	-	Depth Correction ...		<u>17</u>	Deduction for superstructures ...		<u>16.40</u>	Sheer correction ...		<u>7.08</u>	Round of Beam correction ...			Correction for Thickness of Deck amidships ...			Other corrections, scantlings, etc. ...			Summer Freeboard =		<u>58.2</u>
	+	-																								
Depth Correction ...		<u>17</u>																								
Deduction for superstructures ...		<u>16.40</u>																								
Sheer correction ...		<u>7.08</u>																								
Round of Beam correction ...																										
Correction for Thickness of Deck amidships ...																										
Other corrections, scantlings, etc. ...																										
Summer Freeboard =		<u>58.2</u>																								

SUMMER FREEBOARD amidships from Centre of Disc to top of Deck Line, Wood, Steel, Deck:—

Tropical Fresh Water Line above Centre of Disc	Tropical Fresh Water Freeboard
Fresh Water Line " "	Fresh Water " "
Tropical Line " "	Tropical " "
Winter Line below " "	Winter " "
Winter North Atlantic Line " "	Winter North Atlantic " "