

With or Without Disconnected Erections.

STEEL STEAMER.

Received at London Office

FRI. JUL. 30 1920

Date of completion of report 24th July 1920
Survey held at South Shields

State if Report is also sent on the Machinery of the Vessel Yes

Port of Newcastle

No. 73372

Date, First Survey 18th February

Last Survey 19th July

1920

On the (State if Single, Twin, or Triple Screw) single screw steamer "HEATHER KING" ex "KILGARVEN"

Rig Schooner

TONNAGE under Tonnage Deck 491.32

CLASS 100 A1

FEET.

Master Shaw

Year of appointment (1) As Master in service of owner of present vessel: 1920 (2) As Master of this vessel: 1920

Do. between Tonnage Dks. and 3rd and 4th Dk.

Breadth (greatest moulded) 29.83

Total under Upper Dk.

Depth, at middle of length from top of keel to top of upper deck beams at side 16.50

Do. of Poop

Transverse Number 46.33

Do. of R.Q.Dk.

Do. of Bridge House 57.18

Do. of Forecastle

Do. of Houses on Dk. 12.47

Do. of excess of Hatchways 29.50

Do. above Crown of Engine Room 31.25

Gross Tonnage 621.72

Less Crew Space 45.15

Less above Crown of Engine Room 291.59

TONNAGE FOR FEES 45.15

Less Engine Room 10.82

Less Ventilation Spaces 274.16

Destined Voyage Coasting

If Surveyed while Building, Afloat, & in Dry Dock Yes

Feet.	Inches.	BREADTH—	Feet.	Inches.	DEPTH, ACTUAL—	Top of Floors to top of Upper Dk. Beams	Feet.	Inches.	No. of Decks with flat laid
170	0	Moulded	29	10	Do.	do.	15	8½	One
						Second Dk. Beams			No. of Tiers of Beams
									One

GENERAL REMARKS—(continued).

[Faint handwritten notes and sketches, including diagrams of ship sections and structural details.]

PARTICULARS FOR RECORD in the REGISTER BOOK.—Length of Poop ☒ ft., R.Q.D. ☐ ft., Bridge 50 ft., Forecastle ☒ ft. and
(in feet and tenths). When the Poop is joined to the B.D., this should be distinctly stated
No. and Material of Decks (if Iron or Steel) and whether wholly or partially covered with wood, and No. of tiers of Beams (this information is to be given as it
should appear in the Register Book). 10th (ste) ☒
Official No. 143510 ; Signal Letters
How are the surfaces preserved from oxidation? Inside Cement & paint Outside paint
State if Machinery is fitted aft ☒ no

PARTICULARS OF WATER BALLAST.—State whether the Double bottom is constructed on the cellular system or with girders on floor.

Where Fitted.	Length. Feet.	Water Capacity. Tons.	Where Fitted.	Length. Feet.	Water Capacity. Tons.
Double bottom, aft,			Fore peak tank,	0 01 12	
Double bottom, under Engines and Boilers.			After peak tank,		9 20
Double bottom, if under Engines only, Seed water	26	20	Deep tank, aft,		
Double bottom, if under Boilers only,			Deep tank, forward,		
Double bottom, forward,			Other tanks, if fitted,		
		20	(If necessary, furnish further information by sketch.)		

* The wells are not to be included in the lengths of the tanks.

Order for Special Survey No.
Date
No. 733 in builder's yard.
Days of Surveys held while building Feb. 12-20. Mar. 3-4. 9-10-24-25-26. Apr. 13-14-26. May 4-7-11-13-14-21-27. Jun. 1-9-12. Jul. 5-7-9-12-13-14-16-19
Surveyor's Signature J. Macdonald. By B. Tiltman
Total No. of Visits 30

