

REPORT ON ELECTRICAL EQUIPMENT.

(OTHER THAN FOR THE PROPULSION OF THE VESSEL)

25 FEB 1944
Received at London Office

Date of writing Report... 15th Feb 1944 When handed in at Local Office... 25 FEB 1944 Port of... IPSWICH

No. in Survey held at... LOWESTOFT Date, First Survey... 10 Nov. 1943 Last Survey... Feb. 14th 1944
Reg. Book. (Number of Visits... 11)

on the... N.A.V. "CHATTENDEN" Tons { Gross 322.02
Net 144.09

Built at... LOWESTOFT By whom built... RICHARDS IRONWORKS Yard No. 311 When built... 1944

Owners... ADMIRALTY Port belonging to...

Electrical Installation fitted by... MAHN EGERTON & CO. LTD. NORWICH Contract No. ✓ When fitted... 1944

Is vessel fitted for carrying Petroleum in bulk... NO Is vessel equipped with D.F. ✓ E.S.D. ✓ Gy.C. ✓ Sub.Sig. ✓

Have plans been submitted and approved... YES System of Distribution... TWO WIRE Voltage of supply for Lighting... 110

Heating... ✓ Power... ✓ Direct or Alternating Current, Lighting... DIRECT Power... ✓ If Alternating Current state periodicity... ✓ Prime Movers,

has the governing been tested and found as per Rule when full load is suddenly thrown on and off... YES Are turbine emergency governors fitted with a

trip switch as per Rule... ✓ Generators, are they compound wound... YES are they level compounded under working conditions... YES,

if not compound wound state distance between generators... ✓ and from switchboard... ✓ Where more than one generator is fitted are they

arranged to run in parallel... NO are shunt field regulators provided... YES Is the compound winding connected to the negative or positive pole

NEGATIVE Have machines over 100 kw. been inspected by the Surveyors during manufacture and testing... ✓ Have certificates of

test for machines under 100 kw. been supplied... YES and the results found as per rule... YES Are the lubricating arrangements and the construction

of the generator as per rule... YES Position of Generators... 3 KW. GEN. PORT SIDE ENGINE ROOM, 7 1/2 KW D.G. GEN. STARBOARD SIDE

ENGINE ROOM is the ventilation in way of generators satisfactory... YES are they clear of inflammable material... YES, if situated

near unprotected combustible material state distance from same horizontally... ✓ and vertically... ✓, are the generators protected from mechanical

injury and damage from water, steam and oil... YES, are the bedplates and frames earthed... YES and the prime movers and generators in metallic

contact... YES Switchboards, where are main switchboards placed... E.R. FORWARD BULKHEAD

are they in accessible positions, free from inflammable gases and acid fumes... YES, are they protected from mechanical injury and damage from water, steam

and oil... YES, if situated near unprotected combustible material state distance from same horizontally... ✓ and vertically... ✓, what insulation

material is used for the panels... SINDANYD, if of synthetic insulating material is it an Approved Type... YES, if of

semi-insulating material (slate or marble) are all conducting parts insulated therefrom as per Rule... ✓ Is the frame effectually earthed... YES

Is the construction as per Rule... YES, including accessibility of parts... YES, absence of fuses on the back of the board... YES, individual fuses

to pilot and earth lamps, voltmeters, etc... YES locking of screws and nuts... YES, labelling of apparatus and fuses... YES, fuses on the "dead"

side of switches... YES Description of Main Switchgear for each generator and arrangement of equaliser switches... 30 AMP D.P. KNIFE

SWITCH FOR MAIN SWITCH WITH 15 AMP. D.P. KNIFE SWITCHES FOR OUTGOING

CIRCUITS and for each outgoing circuit...

Are compartments containing switchboards composed of fire-resisting material or lined as per Rule... YES Instruments on main switchboard... ONE

ammeters... ONE voltmeters... ✓ synchronising devices. For compound machines in parallel is the ammeter connected on the pole opposite to the

equaliser connection... ✓ Earth Testing, state means provided... EARTH LAMPS WITH SWITCH & FUSE ON EACH POLE

Switches, Circuit Breakers and Fuses, are they as per Rule... YES, are the fuses an approved type... YES, are all fuses labelled as

per Rule... YES If circuit breakers are provided for the generators, at what overload current did they open when tested... ✓, are the reversed current


protection devices connected on the pole opposite to the equaliser connection... ✓, have they been tested under working conditions, and at what current

did they operate... ✓ Joint Boxes, Section Boards and Distribution Boards, is the construction and position as per Rule... YES

Cables, are they insulated and protected as per the appropriate Tables of the Rules... YES, if otherwise than as per Rule are they of an approved type... ✓,

state maximum fall of pressure between bus bars and any point under maximum load... 1 VOLT, are the ends of all cables having a sectional area of 0.04

square inch and above provided with soldering sockets... YES Are paper insulated and varnished cambric insulated cables sealed at the ends... ✓



The Electrical Equipment is installed in accordance with the approved plans and the requirements of the Rules.
 All Insulated Conductors are guaranteed to have been tested at the maker's works as specified in the Rules.
 The foregoing is a correct description.

C. Wilson & Mann Elect. Co. Ltd.

Electrical Engineers.

Date *19-2-44*

COMPASSES.

Minimum distance between electric generators or motors and standard compass.....
 Minimum distance between electric generators or motors and steering compass.....
 The nearest cables to the compasses are as follows:-
 A cable carrying Amperes feet from standard compass feet from steering compass.
 A cable carrying Amperes feet from standard compass feet from steering compass.
 A cable carrying Amperes feet from standard compass feet from steering compass.
 Have the compasses been adjusted with and without the electric installation at work at full power
 Has the effect of switching on and off circuits, motors and other electro-magnetic apparatus within the vicinity of the compasses been noted
 The maximum deviation due to electric currents was found to be degrees on course in the case of the standard compass, and degrees on course in the case of the steering compass.

AUTOMATIC COMPASS CORRECTOR FITTED

Builder's Signature. Date.....

Is this installation a duplicate of a previous case *YES* ✓ If so, state name of vessel *'EMPIRE SPORTSMAN'*
 Plans. Are approved plans forwarded herewith *NO* If not, state date of approval *17-5-41*
 Certificates. Are certificates of test for motors engaged on essential services and generators forwarded herewith *YES* ✓
 General Remarks (State quality of workmanship, whether insulation tests, etc., have been made, opinions as to class, etc.)

The installation has been installed in accordance with the approved plans & Rule requirements.

The materials & workmanship are sound & of good description.

Insulation tests have been made throughout with satisfactory results.

The installation has been examined under full working conditions & found satisfactory.

NOTE:- *The 7 1/2 K.W. generating set for D.G. is an Admiralty supply, and has not been built under the Society's supervision. The D.G. installation has been installed under Admiralty supervision.*

*Noted
J.E.
1/3/44*

Total Capacity of Generators *3 + 7 1/2* **GEN.** Kilowatts.

The amount of Fee *+25%* £ *6* : *5* : *0* When applied for, **25 FEB 1944**
 Travelling Expenses (if any) £ : : When received,

J.E. Turpie
 Surveyor to Lloyd's Register of Shipping.

FRI. 3. MAR 1944

Committee's Minute

Assigned *See fe machs etc*

5m. 4. 25.—Transfer. (MADE AND PRINTED IN ENGLAND.)
 (The Surveyors are requested not to write on or below the space for Committee's Minute.)



© 2020

Lloyd's Register Foundation