

Lloyd's Register of Shipping.
SURVEYS FOR FREEBOARD.
(COMPUTATION FOR STEAMER, SAILING SHIP, TANKER.)

Index No. _____
(For London Office only.)

Ship's Name DEVERIL	Official Number	Nationality and Port of Registry	Gross Tonnage	Date of Build	Port of Survey
Moulded Dimensions: Length 205.00 Breadth 24.50 Depth 16.00					Date of Survey 18.10.48
Moulded displacement at moulded draught = 85 per cent. of moulded depth _____ tons					Surveyor's Signature G.H.W.
Coefficient of fineness for use with Tables 68					Particulars of Classification

DEPTH FOR FREEBOARD (D). Moulded depth 16.00 Stringer plate02 Sheathing on exposed deck $T \left(\frac{L-S}{L} \right) =$ Depth for Freeboard (D) = 16.02	DEPTH CORRECTION. (a) Where D is greater than Table depth (D - Table depth) R = 16.02 - 13.67 = 2.35 (b) Where D is less than Table depth (if allowed) (Table depth - D) R = If restricted by superstructures	ROUND OF BEAM CORRECTION. Moulded Breadth (B) Standard Round of Beam = $\frac{B \times 12}{50} =$ Ship's Round of Beam = Difference Restricted to Correction = $\frac{\text{Diff}}{4} \times \left(1 - \frac{S_1}{L} \right) = \text{NIL}$
---	--	--

DEDUCTION FOR SUPERSTRUCTURES.					Standard Height of Superstructure _____
Mean Covered Length (S)	Equivalent Enclosed Length (S _i)	Height	Height Correction	Effective Length (E)	" " R.Q.D. _____
Poop enclosed					Deduction for complete superstructure _____
" overhang					Percentage covered $\frac{S}{L} =$
R.Q.D. enclosed					" " $\frac{S_i}{L} =$ ✓
" overhang					" " $\frac{E}{L} =$
Bridge enclosed					Percentage from Table, Line A.
" overhang aft					(corrected for absence of forecastle (if required))
" overhang forward					Percentage from Table, Line B.
F'cle enclosed					(corrected for absence of forecastle (if required))
" overhang					Interpolation for bridge less than .2L (if required)
Trunk aft					Deduction = NIL ✓
" forward					
Tonnage opening aft					
" " forward					
Total					

SHEER CORRECTION.								Mean actual sheer aft =
Station	Standard Ordinate	S M	Product	Actual Ordinate	Effective Ordinate	S M	Product	Mean standard sheer aft =
A.P.		1				1		
$\frac{1}{4}L$ from A.P.		4				4		
$\frac{2}{4}L$ "		2				2		
Amidships		4				4		
$\frac{2}{4}L$ from F.P.		2				2		
$\frac{1}{4}L$ "		4				4		
F.P.		1				1		
Total								
Correction = $\frac{\text{Difference between sums of products}}{18} \left(.75 - \frac{S}{2L} \right) = \text{NIL}$								Mean actual sheer forward =
If limited on account of midship superstructure.								Mean standard sheer forward =
								Length of enclosed superstructure forward of amidships =
								" " aft of " =

Deduction for Tropical Freeboard. Addition for Winter and Winter North Atlantic Freeboard. Depth to Freeboard Deck = 16.02 Summer freeboard = 2.31 Moulded draught (d) = 13.71 Deduction for Tropical freeboard and addition for Winter freeboard = $\frac{d}{4}$ inches = Addition for Winter North Atlantic Freeboard (if required) =	Deduction for Fresh Water. Displacement in salt water at summer load water line $\Delta =$ Tons per inch immersion at summer load water line T = Deduction = $\frac{\Delta}{40 T}$ inches =	TABULAR FREEBOARD corrected for Flush Deck (if required) Correction for coefficient NIL Depth Correction Deduction for superstructures Sheer correction Round of Beam correction Correction for Thickness of Deck amidships Other corrections, scantlings, etc. Summer Freeboard = 27.66
--	---	---

SUMMER FREEBOARD amidships from Centre of Disc to top of Deck Line, Wood, Steel, Deck :-

Tropical Fresh Water Line above Centre of Disc	...	Tropical Fresh Water Freeboard	...
Fresh Water Line	"	Fresh Water	"
Tropical Line	"	Tropical	"
Winter Line below	"	Winter	"
Winter North Atlantic Line	"	Winter North Atlantic	"

009083-009093-0093