
GENERAL REMARKS—(continued).

PARTICULARS FOR RECORD in the REGISTER BOOK.—Length of Poop ☒ ft., R.Q.D. ☒ ft., Bridge ☒ ft., Forecastle 14.2 ft.
(in feet and tenths). When the Poop is joined to the B.D., this should be distinctly stated ☒

No. and Material of Decks (if Iron or Steel) and whether wholly or partially covered with wood, and No. of tiers of Beams (this information is to be given as should appear in the Register Book) See. Sk. wood Sheafed.
Official No. _____; Signal Letters _____ State if Machinery is fitted aft No. See plan.
How are the surfaces preserved from oxidation? Inside Cement. and Paint Outside Paint

PARTICULARS OF WATER BALLAST.—State whether the Double bottom is constructed on the cellular system or with girders on floors no. bottom.

Where Fitted.	*Length. Feet.	Water Capacity. Tons.	Where Fitted.	*Length. Feet.	Water Capacity. Tons.
Double bottom, aft,			Fore peak tank,	<u>19'-0"</u>	<u>36.</u>
Double bottom, under Engines and Boilers,			After peak tank,	<u>8.25</u>	<u>21.</u>
Double bottom, if under Engines only,			Deep tank, aft,		
Double bottom, if under Boilers only,			Deep tank, forward,		
Double bottom, forward,			Other tanks, if fitted,		
	Total capacity of double bottom		(If necessary, furnish further information by sketch.)		

* The wells are not to be included in the lengths of the tanks.

State whether the above have been tested as required by the Rules Yes. and Lights.

Order for Special Survey No. 268

Date 7/4-11.

No. 98 in builder's yard.

DATES of Surveys held while building

1/6. 3-7-19/7. 4-10-15-18/8 5-11-22-25/9. 2/10. 1911.

Total No. of Visits 13.

Surveyor's Signature

© 2021 Register Foundation
L. Leuvenburg