

S.S. "KOSTRENA" RADFIELD

PARTICULARS OF PROTECTION TO OPENINGS, ETC. CONTINUED

		HATCHWAYS ON FREEBOARD AND SUPERSTRUCTURE DECK				
Description of Hatchway		IN F'CLE TO FORE PEAK	IN F'CLE TO CHAIN LOCKER	IN BRIDGE TO SIDE BUNKER	IN BRIDGE TO BUNKER	
Dimensions of Hatchway		LENGTH 3'-7"	2'-0"	8'-0"	6'-0"	
		WIDTH 3'-0"	2'-0"	2'-6"	16'-0"	
COAMINGS	Height above Deck	9" x 3" BA	9" BA	15"	19"	
	Thickness	Sides	.36"	.40"	.40"	
		Ends	.36"	.36"	.40"	.40"
	Stiffeners	NIL	NIL	NIL	NIL	
	Brackets, Stays	NIL	NIL	NIL	NIL	
HATCH BEAMS	Number	NIL	NIL	NIL	NIL	
	Spacing	NIL	NIL	NIL	NIL	
	Scantling and Sketch	NIL	NIL	NIL	NIL	
Bearing Surface						
FORE AND AFTERS	Number	NIL	NIL	NIL	3	
	Spacing	NIL	NIL	NIL	4'-0"	
	Unsupported Lengths	NIL	NIL	NIL	5'-6"	
	Scantling* and Sketch		NIL	NIL	NIL	7"
						 6 SIDES 7" CENTRE FT.
Bearing Surface					WOOD 2 1/4"	
HATCH COVERS	Material	WOOD	WOOD	White pine	WOOD	
	Thickness	2 3/4"	2 3/4"	NIL 2 3/4"	2 1/2"	
	How fitted	TRANS	TRANS		TRANS.	
	Bearing Surface	1 1/2"	1 1/2"		2 1/4"	
Spacing of Cleats		28" SIDES 24" ENDS	NIL	NIL 27"	24"	
Number of Tarpaulins		1			3	

*Are wood fore and afters steel shod at all bearing surfaces? YES YES YES YES

Are battens and wedges efficient and in good condition? YES NIL NIL YES

Are tarpaulins in good condition and in accordance with rule requirements? YES NIL YES YES

Are lashings provided in accordance with rule requirements? NO NIL NIL NONE

