

* Where a long bridge is fitted the thickness of Upper Deck Sheerstrake and Strake below should also be stated clear of same.

Upper Deck { Butts, *2 1/2* riveted for *1/2* length amidship.
Stringer Plate { Straps, single, double or overlapped for *1* length amidship.

Second Deck { Butts, _____ riveted for _____ length amidship.
Stringer Plate { Straps, single or overlapped for _____ length amidship.

Butts of Side Stringers _____ riveted.
Tie Plates _____ riveted.
Inner Bottom Plating, riveting of Edges *Curved Strake* Butts *Double*
Centre Girder Butts, *2 1/2* riveted **Keelson Butts**, _____ riveted.
Frames, riveted through Plates with *7/8* in. Rivets, about *6 1/4* apart.
Rivets, state whether Iron or Steel *Iron*

FRAMES extend in one length from *Centre Girder* to *Tank margin*
REVERSED FRAMES on floors and frames extend from *Centre girders to tank margin*
 State if ordinary or joggled *Joggled*
 State if ordinary or joggled *Joggled*

MASTS, SPARS, &c.

	Material.	Total Length.	DIAMETER AND THICKNESS.				No. of Plates in round.	ANGLES.		RIVETING.	
			At Partners.	Heel.	Hoards.	Head.		Number.	Size.	Seams.	Butts.
LOWER MASTS.....	Fore	<i>Steel 63 ft</i>	<i>2 1/4 x .56</i>	<i>2 0 x .56</i>	<i>1 5/8 x .37</i>	<i>1 7/8 x .37</i>	<i>2</i>	<i>none</i>	<i>single</i>	<i>Double</i>	
	Main	<i>" 35.5 ft</i>	<i>2 1/4 x .56</i>	<i>2 0 x .56</i>	<i>1 5/8 x .22</i>	<i>1 1/4 x .30</i>	<i>2</i>	<i>"</i>	<i>"</i>	<i>"</i>	
	Mizen.										
Boomsprit.											
Booms, Yards and Remainder of	<i>Spars Polymastic</i>										
Rigging, Material and Size, Shrouds	<i>Steel 3 3/4</i>										
Suit of											
Sails, and the following spare sails											

Stays *Steel 4"*

[illegible]

GENERAL REMARKS—(continued).

PARTICULARS FOR RECORD in the REGISTER BOOK.—Length of Poop 28 ft., R.Q.D. ✓ ft., Bridge 85.5 ft., Forecastle 32.25 ft. (in feet and tenths). When the Poop is joined to the B.D., this should be distinctly stated

No. and Material of Decks (if Iron or Steel) and whether wholly or partially covered with wood, and No. of tiers of Beams (this information is to be given as it should appear in the Register Book) One deck, steel, one tier of beams
Official No. 145583; Signal Letters
State if Machinery is fitted aft No
How are the surfaces preserved from oxidation? Inside Paint & cement Outside Paint

PARTICULARS OF WATER BALLAST.—State whether the Double bottom is constructed on the cellular system or with girders on floors					
Where Fitted.		*Length.	Water Capacity.	Where Fitted.	
		Feet.	Tons.		
Double bottom, aft,		99	169	Fore peak tank,	
Double bottom, under Engines and Boilers,		38	120	After peak tank,	
Double bottom, if under Engines only,				Deep tank, aft,	
Double bottom, if under Boilers only,				Deep tank, forward,	
Double bottom, forward,		126	323	Other tanks, if fitted,	
		Total capacity of double bottom	612	(If necessary, furnish further information by sketch.)	

* The wells are not to be included in the lengths of the tanks.

State whether the above have been tested as required by the Rules.

Order for Special Survey No.

Date

No.

in builder's yard.

DATES OF SURVEYS held while building

1919 Nov 26, Dec 23, June 18, 24, July 7, 16, 21, Aug 19, Sept 2, 6, 8, 14, 16, Oct 4, 13, 28, 21, 29
Nov 3, 5, 9, 12, 18, 23, Dec 7, 18, 27, 1921 Jan 18, Feb 3, 8, 15, 22 Mar 3

Surveyor's Signature

G. A. Dryden Toyn

Total No. of Visits 33

© 2021

Lloyd's Register Foundation