

S.S. "WAR BEE"

The butts on sheerstrake and raised quarter deck are triple and quadruple riveted for one-half length. Bottom inside tanks is cement coated. The breadth and thickness of web frames are as shown on approved plans also semi box beams to collision and after peak bulkheads. There is one two-handed pump in engine room which is connected to the main bilge suction which communicates with forward and after holds. There is also one hand pump to after peak.

Chain cable weights	Tons.	Cwt.	Qr.	Lbs.
#50271	8	5	0	8
50272	8	3	3	2

Dates of Visits.

Machinery Report.

1917

March	21st & 23rd
April	4th & 13th
May	9th
June	10th
July	5th & 24th
Aug.	22nd
Sept.	17th
Oct.	1st, 17th, 18th, 19th, 20th, 22nd, 23rd, 24th, 29th, 30th & 31st
Nov.	1st, 2nd, 3rd, 4th, 5th, 6th, 7th, 10th, 16th & 22nd.

1918.

Jan.	10th, 18th & 25th
Feb.	14th & 20th
March	6th, 21st, & 29th
April	4th, 16th, 17th & 26th
May	1st, 10th, 11th, 15th, 16th, 20th, 21st, 22nd, 24th, 25th, 27th, 28th & 29th.
June	1st, 5th, 7th, 12th, 14th, 20th, 21st, 24th, 26th & 27th
July	9th, 13th, 29th & 30th.

(First visit March 21st/17)  
Last " July 30th/18

Lloyd's Register  
Foundation

009780-009788-0129