

Lloyd's Register of Shipping.

SURVEYS FOR FREEBOARD.—STEAM SHIPS.

Index No. *33037 33038*
(For London Office only.) *42394* *233* *228* *768*

PARTICULARS RELATING TO ALL STEAM SHIPS EITHER FLUSH DECKED, OR WITH TOP GALLANT FORECASTLES, SHORT POOPS AND BRIDGE HOUSES DISCONNECTED, OR WITH TOP GALLANT FORECASTLES HAVING LONG POOPS, OR RAISED QUARTER DECKS CONNECTED WITH BRIDGE HOUSES, OR OTHERWISE.

Port of Survey

Date of Survey *31-8-28*

Name of Surveyor

Ships Name. <i>Yokohama Maru</i> <i>177-88 ships</i>	Port of Registry and Nationality.	Official Number.	Gross Tonnage.	Date of Build.	Particulars of Classification. <i>10001 with freeboard (contemplates)</i>
Number in Register Book					

Registered dimensions from Ship's Register.	LENGTH.	BREADTH.	DEPTH.	UNDER DECK TONNAGE.
	<i>510'-0"</i>	<i>66'-0"</i>	<i>41'-0"</i>	
Length on LOADLINE.		Frame Depth Rule	Ceiling Sheer	Peak Tanks
CORRECTED DIMENSIONS.	<i>510.0</i>			

Co-efficient of fineness.....
Any modification necessary }
[Para. 4 (a) to (e)]* }
Co-efficient as corrected *assumed .72*

Sheer { Stem..... }
at { Sternpost ... } $\div 2 =$...Mean

Sheer at $\frac{1}{3}$ of the length from { Stem }
{ Sternpost } $\div 2 =$...Mean

Gradual mean Sheer *assumed 50% even*

Standard mean Sheer [Table, Para. 18] *6.1.00* Correction

Difference..... *30.50* $\div 4 =$ *7.62*

§ If limited as Para. 18 (f) *-7½'*

Rise in Sheer { At front of bridge house..... }
from amidships { }
[Para. 18 (e)] { At after end of forecastle }

Fall in Sheer { }
Para. 18 (d) { } $\div 2 =$...

Length uncovered Correction

ALLOWANCE FOR DECK ERECTIONS :—

Freeboard, Table C.....

Correction for Length, if required (Para. 12, 13, and 14) *flush decked*

Freeboard by Table A. corrected for sheer, and for length, if required (Para. 11, 12, 13, and 14) *assumed*

Difference

Percentage as below.....

Correction for R. Q. Dk. if engine and boiler openings not covered by bridge house (Para. 11) }

Allowance for Deck Erections

Length.	Length allowed.	Height.
Forecastle.....		
Bridge House		
† Raised Qr. Dk.....		
Poop.....		
Total		
Length of Ship		
Corresponding percentage {		
(Para. 11, 12, 13, or 14) }		

FREEBOARD recommended amidships from centre of Disc to top of Statutory Deck Line, Wood (Steel) Deck :—

Fresh Water Line	above centre of Disc
Indian Summer Line	"	"	"	"	"	"	"	"	"
Winter Line	below	"	"	"	"	"	"	"	"
Winter North Atlantic Line	"	"	"	"	"	"	"	"	"

Moulded Depth as measured..... *41'-0"*

Addition for Keel below base line for draught record.....inches.

CORRECTION FOR LENGTH.

Length of Ship on Loadline.....	<i>510</i>
Length in Table	<i>492</i>
Difference	<i>18</i>
Correction for 10ft., Table A.	<i>1.7</i> Table C. -
× Difference divided by 10	<i>3.06</i> (if required.)
If $\frac{1}{10}$ ths length covered divide by 2	<i>+3'</i>

CORRECTION FOR IRON DECK.

Proportion covered, if less than $\frac{1}{10}$ ths length covered

Thickness of usual wood deck, less stringer *8½" wood decking full*

CORRECTION FOR ROUND OF BEAM.

Breadth at Gunwale amidships.....

Round of Beam

Normal round..... *assumed normal*

Difference $\div 2 =$

Proportion of Deck uncovered (Para. 19)

Freeboard, Table A *11'-6½"*

Correction for Sheer *-7½"*

Correction for Length *10'-11"*

Allowance for Deck Erections *+3"*

Correction for Round of Beam..... *11'-2"*

Correction for fall in Sheer (if any).....

Correction for Steel Deck (if required)

Additions for non-compliance with provisions of { }
Para. 11 (d) and (e) † { }

Other Corrections (if any)

Winter Freeboard *11'-2"*

Summer Freeboard *7½"*

Indian Summer Freeboard

N. A. Winter Freeboard

Correction necessary because clearside amidships, measured in accordance with the Statute is not taken at the intersection of the wood or steel deck with side.

Winter Freeboard from deck line	
Summer " " " "	
Indian Summer " " " "	
N. A. Winter " " " "	

Winter Freeboard from deck line *41'-0½"*

Summer " " " " *3½"*

Indian Summer " " " " *41'-4"*

N. A. Winter " " " " *10'-6½"*

..... *30'-9½"*

† If the frames, skin planking, or ceiling are of unusual thickness the breadth of vessel to inside of ceiling should be reported if possible.

† In vessels obtaining an allowance for deck erections under Para. 11 where the sheer drops abaft amidships the height of the R.Q.D. is to be taken from the level of the top of the amidship beam.

§ In flush-decked vessels the total standard mean sheer means the sheer measured at the stem and stern-post. In vessels having poops and forecastles, it means the sheer measured at points distant one-eighth of the vessel's length from stem and stern-post.

† State dimensions of freeing port area on back of this form.

† The Surveyor should state whether the fall in sheer as reported is measured relatively to the straight line of keel or to the water line. If measured relatively to water line the vessel's draft at time of survey, and also the usual load draft forward and aft should be reported.