

# Lloyd's Register of Shipping.

## SURVEYS FOR FREEBOARD.

(COMPUTATION FOR STEAMER, ~~SAILING SHIP~~, TANKER.)Index No. \_\_\_\_\_  
(For London Office only).

36457

Ship's Name <b>"Mari II"</b>	Official Number <b>165994</b>	Nationality and Port of Registry <b>British Glasgow</b>	Gross Tonnage <b>1342</b>	Date of Build <b>1918</b>	Port of Survey <b>Penarth, Cardiff</b>
Moulded Dimensions: Length <b>238.1 ft</b> Breadth <b>37.3 ft</b> Depth <b>20 ft</b>					Date of Survey <b>20th January 1941</b>
Moulded displacement at moulded draught = 85 per cent. of moulded depth <b>3100</b> tons					Surveyor's Signature <b>G. Moffatt</b>
Coefficient of fineness for use with Tables <b>.730</b>					Particulars of Classification <b>Class boat propelled</b>

Depth for Freeboard (D).	Depth correction.	Round of Beam correction.
Moulded depth ... <b>20 ft</b>	(a) Where D is greater than Table depth (D - Table depth) R = $(20.03 - 15.75) \times 1.817 = +7.78"$	Moulded Breadth (B) <b>37.3</b>
Stringer plate ... <b>30"</b>	(b) Where D is less than Table depth (if allowed) (Table depth - D) R = <b>4.28</b>	Standard Round of Beam = $\frac{B \times 12}{50} = 8.88$
Sheathing on exposed deck $T \left( \frac{L-S}{L} \right) =$	If restricted by superstructures <input checked="" type="checkbox"/>	Ship's Round of Beam = <b>8.86</b>
Depth for Freeboard (D) = <b>20.03</b>		Difference <b>Diff</b> <b>.02</b>
		Restricted to <input checked="" type="checkbox"/>
		Correction = $\frac{\text{Diff}}{4} \times (1 - \frac{S_1}{L}) = \frac{.02}{4} \times .6259 = \text{Nil}$

## DEDUCTION FOR SUPERSTRUCTURES.

	Mean Covered Length (S)	Equivalent Enclosed Length (S <sub>1</sub> )	Height	Height Correction	Effective Length (E)
Poop enclosed ... <b>none</b>					
" overhang ... <b>none</b>					
R.Q.D. enclosed ... <b>none</b>					
" overhang ... <b>none</b>					
Bridge enclosed ... <b>54'</b>	<b>57.00'</b>	<b>4'</b>	<b>57.00'</b>		
" overhang aft ... <b>3.25'</b>		<b>4'</b>			
" overhang forward ... <b>none</b>					
F'cle enclosed (see C.11) ... <b>28' 29.78</b>	<b>29.78</b>	<b>4'</b>	<b>29.78</b>		
" overhang ... <b>5' 3.22</b>	<b>1.61</b>	<b>4'</b>	<b>1.61</b>		
Trunk aft ... <b>none</b>					
" forward ... <b>none</b>					
Tonnage opening aft ... <b>none</b>					
" forward ... <b>none</b>					
Total ...	<b>90.00</b>	<b>88.39</b>			<b>88.39</b>

Standard Height of Superstructure **6.00'**

" " R.Q.D. **29.65'**

Deduction for complete superstructure **29.65'**

Percentage covered  $\frac{S}{L} = 38.10$

" "  $\frac{S_1}{L} = 37.41$

" "  $\frac{E}{L} = 37.41$

Percentage from Table, Line A. (corrected for absence of forecastle (if required)) ☒

Percentage from Table, Line B. (corrected for absence of forecastle (if required)) **25.30**

Interpolation for bridge less than .2L (if required) ☒

Deduction =  $29.65 \times .2530 = -7.5"$

## SHEER CORRECTION.

Station	Standard Ordinate	S	M	Product	Actual Ordinate	Effective Ordinate	S	M	Product
A.P. ...	33.63	1		33.63	31	31.00	1		31.00
1/4 L from A.P. ...	14.96	4		59.84	15	15.00	4		60.00
1/2 L " ...	3.70	2		7.40	3	3.00	2		6.00
Amidships ...	-	4		-	0	-	4		-
3/4 L from F.P. ...	7.40	2		14.80	4.5	4.50	2		9.00
1/4 L " ...	29.92	4		119.68	20	20.00	4		80.00
F.P. ...	67.25	1		67.25	58	58.00	1		58.00
Total ...				302.60					244.00

Correction =  $\frac{\text{Difference between sums of products}}{18} \left( .75 - \frac{S}{2L} \right) = \frac{58.60}{18} (.75 - .1905) = +1.82"$

If limited on account of midship superstructure. ☒ If limited to maximum allowance of 1 1/2 ins. per 100 ft. ☒

Deduction for Tropical Freeboard.	Deduction for Fresh Water.	TABULAR FREEBOARD corrected for Flush Deck (if required)	<b>29.63</b>
Addition for Winter and Winter North Atlantic Freeboard.	Displacement in salt water at summer load water line	Correction for coefficient $\frac{.730 + .68}{1.36} = 1.410 / 1.36$	<b>30.72</b>
Depth to Freeboard Deck = <b>10.03</b>	$\Delta = 3170$	Depth Correction ... <b>7.78</b>	
Summer freeboard = <b>2.73</b>	Tons per inch immersion at summer load water line	Deduction for superstructures ... <b>7.50</b>	
Moulded draught (d) = <b>17.30</b>	$T = 14.30 \cdot 17.95$	Sheer correction ... <b>1.82</b>	
Deduction for Tropical freeboard and addition for Winter freeboard = $\frac{d}{4}$ inches = <b>4.32 = 4 1/4"</b>	Deduction = $\frac{\Delta}{40T}$ inches = <b>4.42</b>	Round of Beam correction ... <b>7.50</b>	
Addition for Winter North Atlantic Freeboard (if required) = <b>6 1/4"</b>	= <b>4 1/2"</b>	Correction for Thickness of Deck amidships ... <b>7.50</b>	
		Other corrections, scantlings, etc. ... <b>7.50</b>	
		Summer Freeboard = <b>32.82</b>	

## SUMMER FREEBOARD amidships from Centre of Disc to top of Deck Line, Wood, Steel, Deck:

Tropical Fresh Water Line above Centre of Disc	...	8 3/4"
Fresh Water Line	"	4 1/2"
Tropical Line	"	4 1/4"
Winter Line below	"	4 1/4"
Winter North Atlantic Line	"	6 1/4"

Tropical Fresh Water Freeboard	...	2' - 8 3/4"
Fresh Water	"	2' - 4 1/2"
Tropical	"	2' - 4 1/4"
Winter	"	2' - 4 1/4"
Winter North Atlantic	"	2' - 6 1/4"



A new form should be prepared if any alterations that affect the freeboard have been made. If no such alterations have been made, the Surveyor should endorse the form on this side with his signature and the date.

Forecastle Equivalent Bulkhead

Recess  $6' \times 22 - 2 \times 14.25$ ,  $\frac{132 - 28.5}{32}$

$3.22' =$  working

$\frac{33.00'}{32}$

$29.78 =$  equivalent length

Trade of ship

General - Ocean-going

Names of sister ships

Builder's name and yard number

N. V. Werf Bourad, Haarlem

Owners

Ministry of Shipping (Shamrock Shipping Co. Ltd).

Fee £

10

0

0



© 2021

Lloyd's Register  
Foundation