

Rpt. 4b L.R. 923e

14 OCT 1963

Date of writing report 2.10.63

Received London

Port Köln

No. 858

Survey held at Köln-Deutz

No. of visits In shops 4

First date 12.6.63

Last date 5.8.63

B.N. 1.8369.0.7031

## FIRST ENTRY REPORT ON INTERNAL COMBUSTION MACHINERY

No. in R.B. - Name - Gross tons -

Owners - Managers - Port of Registry -

Hull built at Elmshorn By D.W. Kremer Sohn Yard No. 1102/1103 Year Month

Main Engines made at Köln-Deutz By Klöckner-Humboldt-Deutz A.G. Eng. No. 3529867-874 When 8.63

Gearing made at - By - Gear No. - When -

Aux./donkey boilers made at - By - Blr. Nos. - When -

Machinery installed at - By - When -

Particulars of restricted service of ship, if limited for classification -

Particulars of vegetable or similar cargo oil notation, if required -

If ship is to be classed for navigation in ice, state whether Class 1, 2 or 3 - Is ship an oil tanker? -

Is refrigerating machinery fitted? - If so, is it for cargo purposes? - Type of refrigerant -

Is the refrigerating machinery compartment isolated from the propelling machinery space? - Is the refrigerated cargo installation intended to be classed? -

The following particulars should be given as fully and as clearly as possible. Where the answer is "No" or "None", say so! Ticks and other signs of doubtful meaning are not to be used. Where the wording is not applicable to the installation, a black line should be inserted. If the main engines have been constructed at another port and are covered by a separate report, the particulars given in that report need not be repeated below, but all other relevant particulars must be given and the port and report number should be stated.

No. of main engines - No. of propellers - Brief description of propulsion system -

MAIN RECIPROCATING ENGINES. Licence Name and Type No. one airless injection heavy oil SBA8M 517

No. of cylinders per engine 8 Dia. of cylinders 130 mm stroke(s) 170 mm 2 or 4 stroke cycle 4 Single or double acting single

Maximum BHP per engine approved for this installation 230 at 1350 RPM of engine and 386 RPM of propeller.

Corresponding MIP 10.20 kg/cm<sup>2</sup> For DA engines give MIP top & bottom Maximum cylinder pressure 70 kg/cm<sup>2</sup> Machinery numeral 46

Are the cylinders arranged in Vee or other special formation? - If so, number of crankshafts per engine -

TWO STROKE ENGINES. Is the engine of opposed piston type? - If so, how are upper pistons connected to crankshaft? -

Is the exhaust discharged through ports in the cylinders or through valve(s) in the cylinder covers? - No. and type of mechanically driven scavenge pumps or blowers per engine and how driven -

No. of exhaust gas driven scavenge blowers per engine - Where exhaust gas driven blowers only are fitted, can the engine operate with one blower out of action? -

If a stand-by or emergency pump or blower is fitted, state how driven - No. of scavenge air coolers - Scavenge air pressure at full power - Are scavenge manifold explosion relief valves fitted? -

TWO AND FOUR STROKE ENGINES. Is the engine supercharged? yes Are the undersides of the pistons arranged as supercharge pumps? no No. of exhaust gas driven blowers per engine one No. of supercharge air coolers per engine none Supercharge air pressure at full load 330 mm Hg an engine operate without supercharger? yes

No. of valves per cylinder: Fuel 1 Inlet 1 Exhaust 1 Starting - Safety -

Material of cylinder covers cast iron Material of piston crowns aluminium Is the engine equipped to operate on heavy fuel oil? no

Cooling medium for: Cylinders water Pistons - Fuel valves - Overall diameter of piston rod for double acting engines -

Is the rod fitted with a sleeve? no Is welded construction employed for: Bedplate? no Frames? no Entablature? no Is the crankcase separated from the underside of pistons? no Is the engine of crosshead or trunk piston type? trunk Total internal volume of crankcase 240 ltrs. No. and total area of explosion relief devices none

Are flame guards or traps fitted to relief devices? - Is the crankcase readily accessible? no If not, must the engine be removed for overhaul of bearings, etc? yes Is the engine secured directly to the tank top or to a built-up seating? - How is the engine started? electrically

Can the engine be reversed? no If not, how is reversing obtained? reversing reduction gear type WUö180, 3,5:1

Has the engine been tested working in the shop? yes How long at full power? 6 hours

CRANK &amp; FLYWHEEL SHAFTING. Date of approval of torsional vibration characteristics of the propelling machinery system 7.5.63 State barred speed range(s), if imposed for working propeller - not below 500 rpm For spare propeller - Is a governor fitted? yes Is a torsional vibration damper or detuner fitted to the shafting? yes

Where positioned? opposite flywheel Type friction damper No. of main bearings 9 Are main bearings of ball or roller type? -

Distance between inner edges of bearings in way of crank(s) 137 mm Distance between centre lines of side cranks or eccentrics of opposed piston engines -

Crankshaft type: Built, semi-built, solid. (State which) solid

Diameter of journals 90 mm Diameter of crankpins Centre 85 mm Breadth of webs at mid-throw 130 mm Axial thickness of webs 32.5 mm

If shrunk, radial thickness around eyeholes - Are dowel pins fitted? no Crankshaft material: Journals Pins Cr. steel Minimum Y.P. 70 kg/mm<sup>2</sup>

Diameter of flywheel 520 mm Weight 85 kg Are balance weights fitted? no Total weight - Radius of gyration -

Diameter of flywheel shaft - Material - Minimum approved tensile strength -

Flywheel shaft: separate, integral with crankshaft, integral with thrustshaft. (State which) integral with crankshaft

011544-011554-0054 12

Lloyd's Register  
Foundation







GENERAL REMARKS

State if the machinery has been constructed and/or installed under special survey in accordance with the Rules, approved plans and Secretary's letters. State quality of materials and workmanship and give recommendations for classification, including any special notation to be assigned. Where existing machinery is submitted for classification the circumstances should be explained as fully as possible.

This engine has been constructed under special survey of tested materials and is in accordance with the Secretary's letters, approved plans and Rules Requirements. The materials and workmanship are good and the engine, when tested in the shops under full and overload conditions was found to function satisfactorily. The governor tests were also found satisfactory. This engine, in my opinion, is suitable for main propelling purposes and when satisfactorily installed and reported will be eligible to receive the notation \* LMC (with date).

*H. Dröge*  
Engineer Surveyor to Lloyd's Register of Shipping.

PARTICULARS OF IDENTIFICATION MARKS (Including Port of origin) of important Forgings and Castings. (Copies of certificates should be forwarded with report.)

Conn. RODS

LLOYD'S KLN. 231/1-8 K.B. 22.5.63 ✓

CRANKSHAFT ~~ON ROTOR SHAFT~~

LLOYD'S DSF HS 631 28.3.1963 ✓

FLYWHEEL SHAFT

THRUST SHAFT

GEARING

INTERMEDIATE SHAFTS

SCREW AND TUBE SHAFTS

PROPELLERS

OTHER IMPORTANT ITEMS supercharger: G. Fl. 14.2.63 LR No. 26998 ✓

Is the installation a duplicate of a previous case? yes

If so, state name of vessel KLN. Rpt. 816, Engine No. 3529387-94

Date of approval of plans for crankshaft 15.9.62

Straight shafting -

Gearing -

Clutch -

Separate oil fuel tanks -

Pumping arrangements -

Oil fuel arrangements -

Cargo oil pumping arrangements -

Air receivers -

Aux./donkey boilers -

Dates of examination of principal parts:-

Fitting of stern tube -

Fitting of propeller -

Completion of sea connections -

Alignment of crankshaft in main bearings -

Engine checks & bolts -

Alignment of gearing -

Alignment of straight shafting -

Testing of pumping arrangements -

Oil fuel lines -

Donkey boiler supports -

Steering machinery -

Windlass -

Date of Committee

MONDAY 27 APR 1964

Decision


*See Ham 13425*

Special Survey Fee DM. 308.-

Runn. Test DM. 100.-

Expenses DM. 40.-

Date when A/c rendered 27.9.63, KLN. 6893



Lloyd's Register  
Foundation