

# REPORT ON ELECTRICAL EQUIPMENT.

(OTHER THAN FOR THE PROPULSION OF THE VESSEL)

26 APR 1945  
Received at London Office.....

Date of writing Report 20th April 1945 When handed in at Local Office 25 APR 1945 Port of Sunderland

No. in Survey held at Sunderland Date, First Survey 3rd April Last Survey 22nd April 1945  
Reg. Book. Suppt. and Walsland (Number of Visits.....)

89473 on the S.S. "EMPIRE NAIROBI" Tons { Gross 7395  
Net 5083

Built at Sunderland By whom built Shott Bros., Ltd Yard No. 484 When built 1945

Owners Ministry of War Transport Port belonging to Sunderland

Electrical Installation fitted by Campbell & Shewood, Ltd. Contract No. 484 When fitted 1945

Is vessel fitted for carrying Petroleum in bulk No Is vessel equipped with D.F. Yes E.S.D. Yes Gy.C. No Sub.Sig. No

Have plans been submitted and approved Yes System of Distribution Two wire immersed Voltage of supply for Lighting 110

Heating Power 110 Direct or Alternating Current, Lighting Yes Power Yes If Alternating Current state periodicity Prime Movers,

has the governing been tested and found as per Rule when full load is suddenly thrown on and off Yes Are turbine emergency governors fitted with a

trip switch as per Rule Yes Generators, are they compound wound Yes, are they level compounded under working conditions Yes

if not compound wound state distance between generators Yes and from switchboard Yes Where more than one generator is fitted are they

arranged to run in parallel No, are shunt field regulators provided Yes Is the compound winding connected to the negative or positive pole

negative Have machines over 100 kw. been inspected by the Surveyors during manufacture and testing Yes Have certificates of

test for machines under 100 kw. been supplied Yes and the results found as per rule Yes Are the lubricating arrangements and the construction

of the generators as per rule Yes Position of Generators Engine room starboard side on

rudder stools, is the ventilation in way of generators satisfactory Yes are they clear of inflammable material Yes, if situated

near unprotected combustible material state distance from same horizontally Yes and vertically Yes, are the generators protected from mechanical

injury and damage from water, steam and oil Yes, are the bedplates and frames earthed Yes and the prime movers and generators in metallic

contact Yes Switchboards, where are main switchboards placed Engine room starboard side

above generating sets

are they in accessible positions, free from inflammable gases and acid fumes Yes, are they protected from mechanical injury and damage from water, steam

and oil Yes, if situated near unprotected combustible material state distance from same horizontally Yes and vertically Yes, what insulation

material is used for the panels Economy Bindings, if of synthetic insulating material is it an Approved Type Yes, if of

semi-insulating material (slate or marble) are all conducting parts insulated therefrom as per Rule Yes Is the frame effectually earthed Yes

Is the construction as per Rule Yes, including accessibility of parts Yes, absence of fuses on the back of the board Yes, individual fuses

to pilot and earth lamps, voltmeters, etc. Yes locking of screws and nuts Yes, labelling of apparatus and fuses Yes, fuses on the "dead"

side of switches Yes Description of Main Switchgear for each generator and arrangement of equaliser switches Double pole

quick break knife switch and double pole fuse

and for each outgoing circuit Double pole double throw quick break knife switch

and double pole fuse

Are compartments containing switchboards composed of fire-resisting material or lined as per Rule Yes Instruments on main switchboard Two

ammeters Two voltmeters Two synchronising devices. For compound machines in parallel is the ammeter connected on the pole opposite to the

equaliser connection Yes Earth Testing, state means provided Flange coupled to E through fuses

Switches, Circuit Breakers and Fuses, are they as per Rule Yes, are the fuses an approved type Yes, are all fuses labelled as

per Rule Yes If circuit breakers are provided for the generators, at what overload current did they open when tested Yes, are the reversed current


protection devices connected on the pole opposite to the equaliser connection Yes, have they been tested under working conditions, and at what current

did they operate Yes Joint Boxes, Section Boards and Distribution Boards, is the construction and position as per Rule Yes

Cables, are they insulated and protected as per the appropriate Tables of the Rules Yes, if otherwise than as per Rule are they of an approved type Yes

state maximum fall of pressure between bus bars and any point under maximum load 26.6V., are the ends of all cables having a sectional area of 0.01

square inch and above provided with soldering sockets Yes Are paper insulated and varnished cambric insulated cables sealed at the ends Yes



with insulating compound \_\_\_\_\_ or waterproof insulating tape Yes. Are all the cable runs in accessible positions, not exposed to drip or accumulation of water or oil, high temperatures or risk of mechanical damage. Yes, are cables laid under machines or floorplates Yes, if so, are they adequately protected \_\_\_\_\_ Are cables in machinery spaces, galleys, laundries, etc., lead covered Yes or run in conduit Yes. State how the cables are supported and protected W.E. cables run in heavy galley covered conduit in 'tween decks and meshy spaces, engine and boiler rooms wired in 'Pipitina' cable. L.C. surface wiring in accommodation spaces.

Are all lead sheaths, armouring and conduits effectually bonded and earthed. Yes. Refrigerated chambers, are the cables and fittings as per Rule. Yes

Are all cables passing through decks and watertight bulkheads provided with deck tubes or watertight glands. Yes, where unarmoured cables pass through beams, etc., are the holes effectually bushed. Yes and with what material. Lead Alternative Lighting, are the groups of lights in the engine and boiler rooms arranged as per Rule. Yes Emergency Supply, state position \_\_\_\_\_ and method of control \_\_\_\_\_

Navigation Lamps, are they separately wired. Yes controlled by separate double pole switches. Yes and fuses. Yes Are the switches and fuses in a position accessible only to the officers on watch. Yes, is an automatic indicator fitted. Yes Secondary Batteries, are they constructed and fitted as per Rule \_\_\_\_\_, are they adequately ventilated. \_\_\_\_\_ what is the battery capacity in amper hours \_\_\_\_\_

Fittings, are all fittings on weather decks, in stokeholds and engine rooms and wherever exposed to drip or condensed moisture, weatherproof. Yes Are fittings installed where readily combustible materials or inflammable or explosive dust or gases are likely to be present. Yes, if so, how are they protected \_\_\_\_\_ and where are the controlling switches fitted \_\_\_\_\_, are all fittings suitably ventilated. Yes

are all fittings and accessories constructed and installed as per Rule. Yes Searchlight Lamps, No. of \_\_\_\_\_, whether fixed or portable \_\_\_\_\_ are these fittings as per Rule \_\_\_\_\_ Heating and Cooking, is the general construction as per Rule \_\_\_\_\_

are the frames effectually earthed. \_\_\_\_\_, are heaters in the accommodation of the convection type. \_\_\_\_\_ Motors, are all motors constructed and installed as per Rule. Yes and placed in well-ventilated compartments in which inflammable gases cannot accumulate and free from damage from water, steam and oil. Yes, if situated near unprotected combustible material state minimum distance from same horizontally \_\_\_\_\_ and vertically \_\_\_\_\_ Are motors coupled to oil fuel transfer and unit pressure pumps capable of being stopped from a position accessible in the event of fire in the pump compartment \_\_\_\_\_

Have motors of 100 BHP and over been inspected by the Surveyors during manufacture and testing. \_\_\_\_\_ Have certificates of test for motors under 100 BHP intended for essential services been supplied and the results found as per Rule \_\_\_\_\_ Control Gear and Resistances, are they constructed and fitted as per Rule. Yes Lightning Conductors, where required are they fitted as per Rule \_\_\_\_\_ Ships carrying Oil having a Flash Point less than 150° F. Have all the special requirements of the Rules for such ships been complied with \_\_\_\_\_, are all fuses of the cartridge type \_\_\_\_\_ are they of an approved type. \_\_\_\_\_ Are the fittings for pump rooms, 'tween deck spaces, etc., in accordance with the special requirements for such ships. \_\_\_\_\_ Are the cables lead covered as per Rule. \_\_\_\_\_ Spare Gear, if the vessel is for open sea service have spares been provided as per Rule. Yes, are they suitably stored in dry situations. Yes Insulation Tests, has the insulation resistance of all circuits and apparatus been tested and found satisfactory. Yes

PARTICULARS OF GENERATING PLANT.

DESCRIPTION OF GENERATOR.	No. of	RATED AT				DRIVEN BY	WHERE DRIVEN BY AN INTERNAL COMBUSTION ENGINE.	
		Kilowatts.	Volts.	Ampères.	Revs. per Min.		Fuel Used.	Flash Point of Fuel.
MAIN	2	15	110	136	600	Single cylinder steam engines		
EMERGENCY								
ROTARY TRANSFORMER								

GENERATOR CABLES.

DESCRIPTION.	KILOWATTS.	CONDUCTORS.		MAXIMUM CURRENT IN AMPERES.		APPROX. LENGTH (lead plus return feet).	INSULATED WITH.	HOW PROTECTED.
		No. in Parallel Per Pole.	Sectional Area or No. and Dia. of Strands. Sq. ins. or sq. mm.	In the Circuit.	Rule.			
MAIN GENERATORS	2 x 15	1	19/0.83	136	191	30/100	V.C.	L.C. + B.
" " EQUALISER								
EMERGENCY GENERATOR								
ROTARY TRANSFORMER: MOTOR								
" " GENERATOR								

MAIN DISTRIBUTION CABLES.

DESCRIPTION.	CONDUCTORS.		MAXIMUM CURRENT IN AMPERES.		APPROX. LENGTH (lead plus return feet).	INSULATED WITH.	HOW PROTECTED.
	No. in Parallel Per Pole.	Sectional Area or No. and Dia. of Strands. Sq. ins. or sq. mm.	In the Circuit.	Rule.			
AUX. SWITCHBOARDS AND SECTION BOARDS ...							
Trinship Lig. db.	1	7/0.64	21	46	210	W.E.	In conduit
Engineers' Lig. db.	1	19/0.52	59	64	210	W.E.	In conduit
Aft db.	1	19/0.52	48	64	266	W.E.	In conduit
Comp. Lig. db.	1	19/0.52	62	64	98	W.E.	In conduit

LIGHTING AND HEATING, ETC., CABLES.

WIRELESS	1	7/0.64	9	46	210	W.E.	In conduit + L.C.
NAVIGATION LIGHTS	1	7/0.64	25	31	210	W.E.	In conduit + L.C.
LIGHTING AND HEATING	All supplying to Nav. Lig. db. from Officers' Lig. db.						
Captain's Lig. db.	1	7/0.64	7	31	110	W.E.	L.C.
Officers' Lig. db.	1	7/0.64	14	31	84	W.E.	L.C.
Port Lig. db.	1	7/0.64	70	31	180	W.E.	L.C.
Starboard Lig. db.	1	7/0.64	25	46	112	W.E.	L.C.
Emergency W.T.	1	3/0.26	10	10	150	W.E.	L.C.
Trinship db.	1	7/0.64	70	31	120	W.E.	L.C.
Lower db.	1	7/0.64	12	31	12	W.E.	L.C.
Trinship db.	1	7/0.64	21	31	66	W.E.	In conduit
Trinship db.	1	7/0.64	41	46	379	W.E.	In conduit
Engine Room Lig. db.	1	0.64	24	104	100	M.I.	L.C.

MOTOR CABLES.

ALL IMPORTANT MOTORS TO BE ENUMERATED.	No.	B.H.P.					
Refrig. trap.	1	5	1	19/0.52	41	64	285 W.E. In conduit
Vent. Fan (off aft db.)	1	3	1	7/0.64	26	31	120 W.E. L.C.

The Electrical Equipment is installed in accordance with the approved plans and the requirements of the Rules.  
 All Insulated Conductors are guaranteed to have been tested at the maker's works as specified in the Rules.  
 The foregoing is a correct description.

CAMPBELL & ISHERWOOD, LTD.

Thomas Needs

Electrical Engineers.

Date 21-4-45

COMPASSES.

Minimum distance between electric generators or motors and standard compass 86 feet

Minimum distance between electric generators or motors and steering compass 80 feet

The nearest cables to the compasses are as follows:—

A cable carrying 0.144 Ampères on the feet from standard compass 7 feet from steering compass.

A cable carrying 0.144 Ampères 7 feet from standard compass on the feet from steering compass.

A cable carrying Ampères feet from standard compass feet from steering compass.

Have the compasses been adjusted with and without the electric installation at work at full power *Yes*

Has the effect of switching on and off circuits, motors and other electro-magnetic apparatus within the vicinity of the compasses been noted *Yes*

The maximum deviation due to electric currents was found to be *two* degrees on *any* course in the case of the standard compass, and *two* degrees on *any* course in the case of the steering compass.

FOR SHORT BROTHERS, LIMITED.

Wm. and B. Staley

Builder's Signature.

Date 24.4.45.

Is this installation a duplicate of a previous case *No* If so, state name of vessel \_\_\_\_\_

Plans. Are approved plans forwarded herewith *No* If not, state date of approval 13/3/45

Certificates. Are certificates of test for motors engaged on essential services and generators forwarded herewith *Yes*

General Remarks (State quality of workmanship, whether insulation tests, etc., have been made, opinions as to class, etc.) *The electrical*

*equipment of this vessel has been installed under special survey. The materials used and the workmanship are good. On completion the equipment was run under working conditions with satisfactory results and the insulation resistance of all circuits was measured and found good. This equipment is in my opinion suitable for a steam vessel.*

*Noted*

*Wm 10.5.45*

5th. 4. 39.—Transfer. (MADE AND PRINTED IN ENGLAND.)  
 (The Surveyors are requested not to write on or below the space for Committee's Minute.)

Total Capacity of Generators 30 Kilowatts.

The amount of Fee £ 28 : 2/6 :  
*Incl. Specifn.*  
 Travelling Expenses (if any) £ : :  
 When applied for, 20/4/45  
 When received, 19/4/45

*Sanitson*

Surveyor to Lloyd's Register of Shipping.

Committee's Minute FNL 18 MAY 1945

Assigned *See F.E. machy. sph.*



© 2021

Lloyd's Register Foundation