

29 DEC 1927

Rpt. 4.

No. 7307

REPORT ON STEAM RECIPROCATING ENGINE MACHINERY.

Date of writing Report *Nov 16 1927* When handed in at Local Office *19. 11. 1927* Port of *Glasgow* Received at London Office *23 NOV 1927*

No. in Survey held at *Burntisland* Date, First Survey *1-9-27* Last Survey *Nov 14 1927*

Reg. Book. on the *S.S. City of London* (Number of Visits *8*)

Built at *Burntisland* By whom built *Burntisland S.B.Co.* Yard No. *145* When built *1924*

Engines made at *Coatbridge* By whom made *Beardmore & Co* Engine No. *641* when made *1924*

Boilers made at *Glasgow* By whom made *M^{rs} Rawards* Boiler No. *353* when made *1924*

Registered Horse Power *109* Owners *Brussels S.S.Co. Ltd* Port belonging to *London*

Nom. Horse Power as per Rule *109* Is Refrigerating Machinery fitted for cargo purposes *no* Is Electric Light fitted *yes*

Trade for which Vessel is intended *General cargo between London & Brussels*

ENGINES, &c.—Description of Engines *Triple expansion* Revs. per minute *360*

Dia. of Cylinders *15-25-40* Length of Stroke *24* No. of Cylinders *Three* No. of Cranks *Three*

Crank shaft, dia. of journals *8 1/2* Crank pin dia. *8* Crank webs *5* Mid. length breadth *13 1/2* Thickness parallel to axis *5 1/2*

Intermediate Shafts, diameter *7 1/2* Thrust shaft, diameter at collars *8* Thickness around eye-hole *3 1/2*

Tube Shafts, diameter *8 1/2* Screw Shaft, diameter *9 1/8* Is the shaft fitted with a continuous liner *no*

Bronze Liners, thickness in way of bushes *no liners on screwshaft* Thickness between bushes *as per Rule* Is the after end of the liner made watertight in the propeller boss *yes*

If the liner does not fit tightly at the part between the bearings in the stern tube, is the space charged with a plastic material insoluble in water and non-corrosive *yes*

If two liners are fitted, is the shaft lapped or protected between the liners *yes (United States)* Is an approved Oil Gland or other appliance fitted at the after end of the tube shaft *yes*

Propeller, dia. *10 1/2* Pitch *11-3* No. of Blades *4* Material *B.S.* whether Moveable *no* Total Developed Surface *390* sq. feet

Feed Pumps worked from the Main Engines, No. *2* Diameter *3* Stroke *13 1/2* Can one be overhauled while the other is at work *yes*

Bilge Pumps worked from the Main Engines, No. *2* Diameter *3* Stroke *13 1/2* Can one be overhauled while the other is at work *yes*

Feed Pumps { No. and size *1 @ 6 x 4 1/4 x 6* Pumps connected to the { No. and size *1 General Ballast & Main Engine Pump*

Ballast Pumps, No. and size *1 @ 6 x 6 x 6* Lubricating Oil Pumps, including Spare Pump, No. and size *as per Rule*

Are two independent means arranged for circulating water through the Oil Cooler *yes* Suctions, connected to both Main Bilge Pumps and Auxiliary Bilge Pumps;—In Engine and Boiler Room *2 @ 2 1/2 & 1 @ 3 (special)*

In Holds, &c. *1 @ 3*

Main Water Circulating Pump Direct Bilge Suctions, No. and size *1 @ 4 1/2* Independent Power Pump Direct Suctions to the Engine Room Bilges, No. and size *1 @ 3*

Are all the Bilge Suction Pipes in holds and ~~tunnel~~ fitted with strum-boxes *yes*

Are the Bilge Suctions in the Machinery Space led from easily accessible mud-boxes, placed above the level of the working floor, with straight tail pipes to the bilges *yes*

Are all Sea Connections fitted direct on the skin of the ship *yes* Are they fitted with Valves or Cocks *both*

Are they fixed sufficiently high on the ship's side to be seen without lifting the stokehold plates *yes* Are the Overboard Discharges above or below the deep water line *above*

Are they each fitted with a Discharge Valve always accessible on the plating of the vessel *yes* Are the Blow Off Cocks fitted with a spigot and brass covering plate *yes*

What Pipes pass through the bunkers *none* How are they protected *as per Rule*

What pipes pass through the deep tanks *none* Have they been tested as per Rule *yes*

Are all Pipes, Cocks, Valves, and Pumps in connection with the machinery and all boiler mountings accessible at all times *yes*

Is the arrangement of Valves and their connections such as to prevent the possibility of water passing from the sea or from water tanks into the cargo or machinery spaces, or from one compartment to another *yes* Is the Shaft Tunnel watertight *none* Is it fitted with a watertight door *worked from*

MAIN BOILERS, &c.—(Letter for record *(S)*) Total Heating Surface of Boilers *1955* sq. ft.

Is Forced Draft fitted *no* No. and Description of Boilers *1 S B* Working Pressure *180 lbs*

IS A REPORT ON MAIN BOILERS NOW FORWARDED? *yes*

IS A DONKEY BOILER FITTED? *no* If so, is a report now forwarded? *no*

PLANS. Are approved plans forwarded herewith for Shafting *12-5-27* Main Boilers *yes* Auxiliary Boilers *no* Donkey Boilers *no*

Superheaters *no* General Pumping Arrangements *as per Rule* Oil fuel Burning Piping Arrangements *as per Rule*

SPARE GEAR. State the articles supplied:—
Spare gear checked on board & found in order

The foregoing is a correct description,

FOR WILLIAM BEARDMORE & CO., LIMITED

Manufacturer.



© 2021

Lloyd's Register Foundation

012256-012264-0162

70874

1927 Sept. 21, 28 Oct 5, 10, 20 Nov 3, 14
 During progress of work in shops - - -

1927 Oct. 20, 24 Nov 1, 5, 9, 10, 17, 28 Dec 8, 13, 15
 During erection on board vessel - - -

Total No. of visits (in shops) 8 (on board) 11

Dates of Examination of principal parts—Cylinders 5-10-27 Slides 5-10-27 Covers 5-10-27
 Pistons 5-10-27 Piston Rods 5-10-27 Connecting rods 5-10-27
 Crank shaft 10-10-27 Thrust shaft 20-10-27 Intermediate shafts none fitted
 Tube shaft ✓ Screw shaft 20-10-27 Propeller 20-10-27
 Stern tube 10-10-27 (in shops) Engine and boiler seatings 1-11-27 Engines holding down bolts 28-11-27
 Completion of fitting sea connections 24-10-27
 Completion of pumping arrangements 18-12-27 Boilers fixed 17-11-27 Engines tried under steam 15-12-27
 Main boiler safety valves adjusted 13-12-27 Thickness of adjusting washers P.V. 3/8" S.V. 3/8
 Crank shaft material Steel Identification Mark 220YDS 2080AF Thrust shaft material Steel Identification Mark 220YDS 1695A
 Intermediate shafts, material none fitted Identification Marks 1694ATT Tube shaft, material ✓ Identification Mark ✓
 Screw shaft, material Steel Identification Mark Steam Pipes, material Copper Test pressure 360 Date of Test Renfro
 Is an installation fitted for burning oil fuel NO Is the flash point of the oil to be used over 150°F. ✓
 Have the requirements of the Rules for carrying and burning oil fuel been complied with ✓
 Is this machinery duplicate of a previous case If so, state name of vessel

General Remarks (State quality of workmanship, opinions as to class, &c.) These engines have been built under special survey in accordance with the Rules. The materials and workmanship are good. They have been forwarded to Leith to be installed on board the vessel.

The machinery has now been satisfactorily fitted in the vessel, tried under steam & found satisfactory. The machinery is now in a good & safe working condition which renders the vessel eligible in our opinion to have the notation + L.M.C. 12-27 in the Register Book.

It is submitted that this vessel is eligible for THE RECORD. + LMC 12.27. OG.

JWD
30/11/27

Clive Bell
H. L. Sutherst
Engineer Surveyor to Lloyd's Register of Shipping.

The amount of Entry Fee ... £ 3-0-0 When applied for,
 Special 2/5 ... £ 10-18-0 21-11-19 27 ✓
 Donkey Boiler Fee ... £ 5-9-0
 Travelling Expenses (if any) £ : : 14-1-28 (213-18f)
 When received, 30-3-28 19

Committee's Minute GLASGOW 22 NOV 1927

TUES. 3 JAN 1928

Assigned Defered

Glasgow 19/11/27

Certificate to be sent to

The Surveyors are requested not to write on or below the space for Committee's Minute.

© 2021 Lloyd's Register Foundation
 FRI. 9 MAR 1928