

REPORT ON MACHINERY.

Port of *Greenock*

Received at London Office **JES. 11 SEP 1900**

No. in Survey held at *Greenock* Date, first Survey *20th Sept 1899* Last Survey *1st Sept 1900*
 Reg. Book. *350* on the *Screw Steamer "Emilia"* (Number of Visits *112*) Tons { Gross *3604* Net *2347*
 Master *Pio Francich* Built at *Port Glasgow* By whom built *Russell & Co.* When built *1900*
 Engines made at *Greenock* By whom made *Rankin & Blackmore.* when made *1900.*
 Boilers made at *do* By whom made *do do do* when made *1900.*
 Registered Horse Power Owners *Fratelli Bosulich.* Port belonging to *Trieste*
 Nom. Horse Power as per Section 28 *300* Is Refrigerating Machinery fitted *no* Is Electric Light fitted *no.*

ENGINES, &c.—Description of Engines *Inverted Direct Acting Triple Exp^{ns}* No. of Cylinders *Three* No. of Cranks *Three*
 Dia. of Cylinders *24. 39. 65* Length of Stroke *45* Revs. per minute *40* Dia. of Screw shaft *as per rule 12.6* Lgth. of stern bush *5.2*
 Dia. of Tunnel shaft *as per rule 11.4* Dia. of Crank shaft journals *as per rule 12* Dia. of Crank pins *12 1/4* Size of Crank webs *16 x 8 1/2* Dia. of thrust shaft under collars *12 1/4* Dia. of screw *17.0* Pitch of screw *16.9* No. of blades *Four* State whether moveable *no* Total surface *88 sq.*
 No. of Feed pumps *Two* Diameter of ditto *3 1/2* Stroke *24* Can one be overhauled while the other is at work *yes.*
 No. of Bilge pumps *Two* Diameter of ditto *4 1/2* Stroke *24* Can one be overhauled while the other is at work *yes.*
 No. of Donkey Engines *Two* Sizes of Pumps *12 x 10 & duplex 4 1/4 x 6* No. and size of Suctions connected to both Bilge and Donkey pumps
 In Engine Room *Four 3 1/2* In Holds, &c. *Eight 3 1/2 in holds & one 2 1/2 in tunnel wall.*
 No. of bilge injections *one* sizes *6 valves* ^{5 1/2 pipe} connected to condenser, or to circulating pump *is a separate donkey suction fitted in Engine room & size 3 1/2*
 Are all the bilge suction pipes fitted with roses *yes* Are the roses in Engine room always accessible *yes* Are the sluices on Engine room bulkheads always accessible *—*
 Are all connections with the sea direct on the skin of the ship *yes* Are they Valves or Cocks *Both.*
 Are they fixed sufficiently high on the ship's side to be seen without lifting the stokehold plates *yes* Are the discharge pipes above or below the deep water line *above*
 Are they each fitted with a discharge valve always accessible on the plating of the vessel *yes* Are the blow off cocks fitted with a spigot and brass covering plate *yes*
 What pipes are carried through the bunkers *Bilge* How are they protected *wood casing.*
 Are all pipes, cocks, valves, and pumps in connection with the machinery and all boiler mountings accessible at all times *yes.*
 Are the bilge suction pipes, cocks, and valves arranged so as to prevent any communication between the sea and the bilges *yes.*
 When were stern tube, propeller, screw shaft, and all connections examined in dry dock *before launching* Is the screw shaft tunnel watertight *yes*
 Is it fitted with a watertight door *yes* worked from *top platform*

OILERS, &c.— (Letter for record *S*) Total Heating Surface of Boilers *4,550 sq* Is forced draft fitted *no*
 No. and Description of Boilers *Two cylindrical multitubular* Working Pressure *180 lbs* Tested by hydraulic pressure to *360 lbs.*
 Date of test *11.8.1900* Can each boiler be worked separately *yes* Area of fire grate in each boiler *66 sq* No. and Description of safety valves to each boiler *Two direct spring* Area of each valve *8.3 sq.* Pressure to which they are adjusted *184 lbs.* Are they fitted with easing gear *yes*
 Smallest distance between boilers or uptakes and bunkers or woodwork *12* Mean dia. of boilers *15.5* Length *10.6* Material of shell plates *Steel*
 Thickness *1 1/32* Range of tensile strength *29632* Are they welded or flanged *no* Descrip. of riveting: cir. seams *Lap double long.* seams *2 1/2 treble.*
 Diameter of rivet holes in long. seams *1 3/4* Pitch of rivets *9 1/4* Lap of plates or width of butt straps *19 1/2 straps.*
 Percentages of strength of longitudinal joint ^{rivets .91.} Working pressure of shell by rules *181 lbs* Size of manhole in shell *16 x 12*
 Size of compensating ring *30 x 26 1/2 x 1 3/2* No. and Description of Furnaces in each boiler *Three Deightens* Material *Steel* Outside diameter *50.*
 Length of plain part ^{top} Thickness of plates ^{crown} *19* Description of longitudinal joint *welded* No. of strengthening rings *—*
 Working pressure of furnace by the rules *188 lbs.* Combustion chamber plates: Material *Steel* Thickness: Sides *7/8* Back *7/8* Top *19* Bottom *3/4*
 Pitch of stays to ditto: Sides *7 3/4 x 7 1/2* Back *7 3/4 x 7 1/2* Top *8 x 8.* If stays are fitted with nuts or riveted heads *nuts* Working pressure by rules *182 to 190.*
 Material of stays *Steel* Diameter at smallest part *1 3/4 x 1 1/2* Area supported by each stay *60 to 84 sq* Working pressure by rules *180 to 193* End plates in steam space: Material *Steel* Thickness *1 1/2* Pitch of stays *16 1/4 x 16* How are stays secured *double nuts* Working pressure by rules *183 lbs* Material of stays *Steel*
 Diameter at smallest part *2 3/4* Area supported by each stay *260 sq.* Working pressure by rules *180 lbs* Material of Front plates at bottom *Steel*
 Thickness *7/8* Material of Lower back plate *Steel* Thickness *7/8 x 1 1/2* Greatest pitch of stays *12 1/2 to 14 1/4* Working pressure of plate by rules *297 lbs*
 Diameter of tubes *3 1/2* Pitch of tubes *4 3/8 x 4 3/8* Material of tube plates *Steel* Thickness: Front *3/32 x 7/16* Back *24* Mean pitch of stays *16 to 18 1/2*
 Pitch across wide water spaces *14 1/4* Working pressures by rules *231 lbs* Girders to Chamber tops: Material *Steel* Depth and thickness of girder at centre *9 3/8 x 7 1/4* Length as per rule *32 1/2* Distance apart *8* Number and pitch of Stays in each *Three 5.*
 Working pressure by rules *207 lbs* Superheater or Steam chest; how connected to boiler *—* Can the superheater be shut off and the boiler worked separately *—*
 Diameter *—* Length *—* Thickness of shell plates *—* Material *—* Description of longitudinal joint *—* Diam. of rivet holes *—* Pitch of rivets *—* Working pressure of shell by rules *—* Diameter of flue *—* Material of flue plates *—* Thickness *—*
 Stiffened with rings *—* Distance between rings *—* Working pressure by rules *—* End plates: Thickness *—* How stayed *—*
 Working pressure of end plates *—* Area of safety valves to superheater *—* Are they fitted with easing gear *—*



DONKEY BOILER— No. *1899* Description *Cylindrical Multitubular see Glasgow report No 18238.*
 Made at _____ By whom made _____ When made _____ Where fixed _____
 Working pressure _____ tested by hydraulic pressure to _____ No. of Certificate _____ Fire grate area _____ Description of safety valves _____
 No. of safety valves _____ Area of each _____ Pressure to which they are adjusted _____ If fitted with easing gear _____ If steam from main boilers can enter the donkey boiler *no* Dia. of donkey boiler _____ Length _____ Material of shell plates _____ Thickness _____ Range of tensile strength _____ Descrip. of riveting long. seams _____ Dia. of rivet holes _____ Whether punched or drilled _____ Pitch of rivets _____
 Lap of plating _____ Per centage of strength of joint _____ Rivets _____ Thickness of shell crown plates _____ Radius of do. _____ No. of Stays to do. _____
 Dia. of stays _____ Diameter of furnace Top _____ Bottom _____ Length of furnace _____ Thickness of furnace plates _____ Description of joint _____ Thickness of furnace crown plates _____ Stayed by _____ Working pressure of shell by rules _____
 Working pressure of furnace by rules _____ Diameter of uptake _____ Thickness of uptake plates _____ Thickness of water tubes _____

SPARE GEAR. State the articles supplied:— *a propeller & screw shaft. 12 shaft coupling bolts. 2 top & 2 bottom end bolts & nuts. 2 main bearing do. 6 holding down do. 6 junk ring pins. 6 studs & nuts for cylinder covers. 6 do for valve chest covers. 2 feed & 2 bilge pump valves. 1 feed escape valve & spring. 3 cylinder escape valves & spring. 12 condenser tubes. 1 set safety valve springs. 12 main boiler tubes. 1/2 set fire bars. bolts nuts & iron mounted.*

The foregoing is a correct description,

Ranston Macnamara Manufacturer.

Dates { During progress of work in shops - 1899. *Sep 20. 22. 25. 27. 29. Oct 2. 4. 6. 11. 16. Nov 4. 8. 11. 14. 18. 24. 29. Dec 1. 4. 6. 8. 12. 13. 15. 19. 21. 25. 29. 1900.*
 of Survey { During erection on board vessel - *Jan. 9. 11. 15. 17. 19. 22. 25. 30. Feb. 1. 3. 6. 9. 12. 14. 15. 17. 20. 22. 24. 26. Mar. 2. 6. 8. 13. 16. 21. 23. 26. 30. April 4. 6. 11. 14. 18. 20. 24. 25. 30. May 2. 4. 8. 10. 11. 14. 17. 21. 23. 26. 29. 31. June 29. July 2. 3. 16. 17. 18. 19. 20. 23. 24. 25. 26. 28. 31. Aug. 2. 6. 8. 9. 11. 13. 16. 17. 18. 20. building { Total No. of visits *22. 24. 27. 28. 29. 30. 31. Sep 1. - 112 -* Is the approved plan of main boilers forwarded herewith *yes*
 " " " donkey " " " *yes**

General Remarks (State quality of workmanship, opinions as to class, &c.)
These engines & boilers, have been specially surveyed during construction, workmanship good. shafts examined when being turned, & found apparently sound. main steam pipes tested by hydraulic pressure to 400 lbs. tests satisfactory. The engines & boilers, are satisfactorily fitted in vessel, and have been tested under steam, they are now in good order & safe working condition, and are in our opinion, eligible to be noted in Register Book. L.M.C. 9.00.

It is submitted that this vessel is eligible for THE RECORD. **L.M.C. 9.00.**

C.D.
11.9.00.
11.9.00

The amount of Entry Fee. £ *3* : When applied for,
 Special £ *35* : *5.9.1900.*
 Donkey Boiler Fee £ When received,
 Travelling Expenses (if any) £ *6.9.1900.*

A. C. Heron & R. Elliott
 Engineer Surveyor to Lloyd's Register of British & Foreign Shipping,
 Greenock District.

Committee's Minute *Glasgow. 10 SEP. 1900*

Assigned *L.M.C. 9.00.* MACHINERY CERTIFICATE WRITTEN. *17/9/00*



Greenock

Certificate (if required) to be sent to

(The Surveyors are requested not to write on or below the space for Committee's Minute.)

No. in Reg. Book. *350*
 Master
 Engines ma
 Boilers ma
 Registered
 Nom. Horse
 ENGINE
 Dia. of Cyl
 Dia. of Tunn
 collars
 No. of Feed
 No. of Bilge
 No. of Donk
 In Engine
 No. of bilge in
 Are all the bil
 Are all conn
 Are they fixe
 Are they each
 What pipes a
 Are all pipes
 Are the bilge
 When were st
 Is it fitt
 ONKEY
 OILER
 To. and Des
 Date of test
 Each boiler
 Smallest distan
 thickness *1/2*
 Diameter of ri
 Per centages of
 Size of compens
 Length of plai
 Working pressu
 Pitch of stays t
 Material of sta
 Material *Ste*
 Diameter at s
 thickness *5/8*
 Diameter of tub
 Pitch across
 Thickness of gir
 Working press
 Separately
 es
 F
 Stiffened with
 Working pressu