

# PARTICULARS for RECORD OF DOUBLE BOTTOMS, &c., in LLOYD'S REGISTER.

No. of Report 94

Port

Middlebrough

(Received at London Office,

189

Date

No. in Register Book

On the

S.S. Tansil

Double bottom, aft, length 76 and water capacity in tons 162.

Double bottom, forward, length 86 and water capacity in tons 213

Double bottom, under engines and boilers, length 36 and water capacity in tons 108. If under Engines only, or Boilers only, state which for

Double bottom, constructed on the cellular system, length ✓ and water capacity in tons ✓.

Fore peak tank, water capacity in tons ✓. After peak tank, water capacity in tons ✓.

Midship deep tank, length 30 and water capacity in tons 391.

Other tanks, if fitted, length ✓ and water capacity in tons ✓

The above have all been tested as required by the Rules.

(If necessary, furnish further information by sketch.)

N. M. Williams

Surveyor to Lloyd's Register of British and Foreign Shipping.

(T. & S.—250—27/2/90—Transfer ink.)

Order for Ordinary Survey No. ✓

Date ✓

TES of  
d while  
per Sec

4th. When the ship was complete, and before plating was finally coated or cemented...



RECORD OF DOUBLE BOTTOMS, CO. IN LLOYD'S REGISTER

standing and running rigging  
The Windlass is  
Engine Room Skylights—How constructed?  
What arrangements for headlights in bad weather?  
Coal Bunker Openings—How constructed?  
What arrangements for clearing upper deck of water, in case  
scuppers, &c.—What arrangements for clearing upper deck of water, in case  
Cargo Hatchways—How covered?  
Slate size Main Hatch  
On the plating during the process of rivet  
On the several parts of the frame, when  
placed and before the plating was  
When the beams were in and fastened,  
How are they protected?



© 2019  
Lloyd's Register  
Foundation

MD8731/307

at pipes are carried through the bunkers None

all pipes, cocks, valves, and pumps in connection with the machinery accessible at all times