now Named "Surat"

TI...RS. 17 JAN 1895

3 Decks.

IRON OR STEEL STEAMER.

No. 31201.

State if Report is also sent on the Machinery of the Vessel No

Date of completion of report 15 th Jany. 1895 Port of Newcastle Received at London Office 1 Jany 1895

Survey held at Newcastle Date, First Survey 9 th March 1894 Last Survey 9 th Jany 1895

On the Screw Steamer Johannesburg Rig Schooner

THREE DECKED VESSEL.

CLASS 100 A.1.

Master Fred^k H. Wyse

Year of appointment (1) As Master in service of owner of present vessel: 18 92 (2) As Master of this vessel 18 94

Built at Newcastle upon Tyne

When built 1894 Launched 18th August 1894

By whom built Sir W. G. Armstrong, Mitchell & Co^ys Ltd

Owners British & Colonial Steamship Co^y Ltd

Managers Bucknall Bros (Where necessary to be entered in Reg. Book.)

Residence London

Port belonging to London

Destined Voyage Africa If Surveyed while Building, Afloat, or in Dry Dock

TONNAGE under Tonnage Deck	3822.98
Do. between Tonnage Dk. and 3rd and 4th Dk.	
Total under Upper Dk.	
Do. of Poop	103.61
Do. of Bridge House	136.21
Do. of Forecastle	54.87
Do. of Houses on Dk.	308.43
Do. of excess of Hatchways	17.89
Do. above Crown of Engine Room	
Gross Tonnage	4444.29
Less Crew Space	168.62
Less above Crown of Engine Room	
TONNAGE FOR FEES	4275.67
Less Engine Room	1422.17
Less Navigation Spaces	34.63
Register Tonnage as cut on Beam	2818.97

	FEET.
Half Breadth (moulded)	23.34
Depth from upper part of Keel to top of Upper Deck Beams	31.45
Girth of Half Midship Frame (as per Rule)	52.25
deduct 7 feet	7.00
1st Number	100.07
Length	358.16
2nd Number	35841
Proportions—Breadth to Length	7.7
Depth to Length—Upper Deck to top of Keel	11.3
Main Deck ditto	15.3

LENGTH on Deck as per Rule	Feet. 358	Inches. 2	BREADTH— Moulded	Feet. 46	Inches. 9	DEPTH top of Floors to Upper Deck Beams	Feet. 27	Inches. 10	Power of Engines	Horse. 500	No. of Decks with flat laid 2
						Do. do. Main Deck Beams	19	10			No. of Tiers of Beams 2 & girder fwd.

Dimensions of Ship per Register, Length 360 breadth 47.0 depth 27.7. Moulded depth, ft. 30 ins. 7 To Upper Dk. Round up of Beam, Upper Dk. 12 ins.

FRAMING.	Inches in Ship.	Inches in Ship.	16ths or 20ths in Ship.	Inches per Rule Or as	Inches per Rule as Approved	16ths or 20ths per Rule ved.
FRAME, Angles, or ~~T. Bar~~ Bars for ¾ length amidships	6	3½	10	6	3½	10
Do. for ¼ at each end	6	3½	9	6	3½	9
Do. in way of Double Bottoms at Solid Floors	3½	3½	10	3½	3½	10
" " at intermdt. Bkts.	—	—	—	—	—	—
Distance of Frames from moulding edge to moulding edge, all fore and aft	—	25	—	—	25	—
REVERSED FRAME, Angles	6	3½	10	6	3½	10
DEEP FRAMING, depth of girder	9	—	—	9	—	—
FLOORS, depth and thickness of Floor Plate at mid-line for ¾ length amidships	—	—	—	—	—	—
" in way of Engines and Boilers	—	—	—	—	—	—
" thickness at the ends of vessel	—	—	—	—	—	—
" depth at ¾ the half breadth, as per Rule	—	—	—	—	—	—
" height extended at the Bilges	—	—	—	—	—	—
FLOORS & BRACKETS in Cell Dble Bottoms	—	44	8	—	44	8
" Distance apart	—	25	—	—	25	—
CENTRE GIRDER, in Double bottom, depth and thickness	—	44	10	—	44	10
" " Angles, Top	4	4	9	4	4	9
" " " Bottom	6½	4½	10	6½	4½	10
SIDE GIRDERS, number and thickness	2	8×9		2	8×9	
" " Angles	3½	3½	8	3½	3½	8
MARGIN PLATE, depth (exclusive of flange) and thickness	—	36	10×9	—	36	10×9
" Angles	4	4	9	4	4	9
INNER BOTTOM PLATING, breadth and thickness of Middle Line Strake		36	10		36	10
" " " in Engine and Boiler space	× 9/16	9/16	10	—	—	9/16
" " " Remainder in Holds	6	5/8	3/16	—	—	9/16
BEAMS, Upper Deck, ~~Single Angle~~, Bulb Angle, ~~Plate or Tee Bulb~~	—	—	5/16	—	—	4/16
" Angles on upper edge	9	3½	10	9	3½	10
" Average space	—	—	—	—	—	—
BEAMS, Middle Deck, ~~Single Angle~~, Bulb Angle, ~~Plate or Tee Bulb~~	—	25	—	—	25	—
Angles on upper edge	9	3½	11	9	3½	11
Average space	—	—	—	—	—	—
BEAMS, Lower Deck, Single Angle, Bulb Angle, Plate or Tee Bulb	—	25	—	—	25	—
Angles on upper edge	Deep girder for 9 in length					
" Average space						
BEAMS, Hold, or Orlop, Plate or Tee Bulb						
" Angles on upper edge						
" Average space						
BEAMS, Poop Deck, ~~Angle~~, Bulb Angle, ~~Plate or Tee Bulb~~	9	3½	10	9	3½	10
Angles on upper edge	—	—	—	—	—	—
Average space	—	50	—	—	50	—
BEAMS, Bridge Deck, ~~Angle~~, Bulb Angle, ~~Plate or Tee Bulb~~	9	3½	10	9	3½	10
" Angles on upper edge	—	—	—	—	—	—
" Average space	—	50	—	—	50	—
BEAMS, Forecastle Deck, ~~Angle~~, Bulb Angle, ~~Plate or Tee Bulb~~ Under Bridge	7/8	3	8	7/8	3	8
" Angles on upper edge		3	10		3	10
" Average space	—	25	—	—	25	—
PILLARS, In 'tween Deck, size and spacing	2⅞	50	—	2⅞	50	—
" Hold " "	4⅛	50	—	4⅛	50	—
" Quarter 'tween Dks., " "	2⅞	100	—	2⅞	100	—
" " in Hold " "	4⅛	"	—	4⅛	"	—
WEB-FRAMES, In Fore Body, No. and spacing	—	—	—	—	—	—
" " " brdth. & thickness	—	—	—	—	—	—
" No. of Side Stringers " "	3	24	10	3	24	10
WEB-FRAMES, In E. & B. Space, No. & spacing	5	5 & 6		5	6 & 6	
" " brdth. & thickness and Screen bulkhead		24	10		24	10
WEB-FRAMES, In After Body, No. and spacing	—	—	—	—	—	—
" " brdth. & thickness	—	—	—	—	—	—
" No. of Side Stringers " "	—	—	—	—	—	—
" Size of Angles or Tee Bars to Web-Frames	6½	4½	10	6½	4½	10
BRACKET PLATES to Stringers between Web Frames, depth and thickness	every 3rd	16	9	frame	16	9

FORGINGS or CASTINGS.	Inches in Ship.	Inches per Rule. Or as Approved.
KEEL, Bar or Side Plates, depth and thickness	—	—
STEM, moulding and thickness	11 x 3	11 x 3
STERN-POST for Rudder do. do.	Cast Steel 11 x 4	11 x 4
" for Propeller	Steel 11 x 4	11 x 4
MAIN PIECE of Rudder, diameter at head	9½	9½
" " do. at heel	4¾	4¾

RUDDER, how constructed Cast Steel frame & single plate

Can the Rudder be unshipped afloat? Yes

KEELSONS & STRINGERS.	Inches in Ship.	Inches in Ship.	16ths or 20ths in Ship.	Inches per Rule Or as	Inches per Rule as Approved	16ths or 20ths per Rule ved.
CENTRE LINE KEELSON, Vertical Plate above floors, Through Plate, or Intercostal Plate						
" Rider Plate						
" Bulb Plate to Intercostal Keelson						
" Horizontal Plates on Floors						
" Angles						
SIDE KEELSON, Angles						
" Bulb or Plate above floors, for lng.						
" Intercostal Plate, for length						
" Attached to outside Plating with Angle						
BILGE KEELSON, Angles						
" Bulb or Plate above floors, for lng.						
" Intercostal Plate for length						
" Attached to outside Plating with Angle						
BILGE STRINGER Angles						
" Bulb Plate for length						
" Intercostal Plate for length						
" Attached to outside Plating with Angle						
SIDE STRINGER Angles	6½	4½	10	6½	4½	10
" ~~Bulb or~~ Intercostal Plate, for Whole lng.		24	10	—	24	10
" Attached to outside plating with Angle	3½	3½	9	3½	3½	9
Upper Deck Stringer Plates, br'dth & thickness	5	7/16	12	5	7/16	12
" Angle on ditto	4½ x 4½		11	4½ x 4½		11
" Tie Plates fore and aft, outside Hatchways	iron d^k	10	9/16	—	10	9/16
" Deck.* Iron ~~or Steel~~, for whole lng.	—	7	6/16	—	7	6/16
" Wood Deck. Material & thickness	—	—	—	—	—	—
Middle Deck Stringer Plate, br'dth & thickness	5	7/16	10	5	7/16	10
" Angles on ditto, No. 2	4 x 4 x		9	4 x 4 x		9
" Tie Plates outside Hatchways Steel No.	—		9	—		9
" Diagonal Tie Plates on Bms., No. of prs.	—		—	—		—
" Deck.* ~~Iron or~~ Steel, for whole lng.	—		7	—		7
" Wood Deck. Material & thickness	—		—	—		—
Lower Deck Stringer Plate, br'dth & thickness	—		—	—		—
" Angles on ditto, No.	—		—	—		—
" Tie Plates, outside Hatchways	—		—	—		—
" Deck.* Material and thickness	—		—	—		—
Hold, or Orlop Stringer Plate, br'dth & thckn's	—		—	—		—
" Angles on ditto, No.	—		—	—		—
" Tie Plates outside Hatchways	—		—	—		—
" Deck. Material and thickness	—		—	—		—
Poop Deck Stringer Plate, breadth & thickness	25	7/16		25	7/16	
" Angle on ditto	3 x 3 x	7/16		3 x 3 x	7/16	
" Tie Plates	14	7/16		14	7/16	
" Deck. Material and thickness Teak	3	—		3	—	
Bridge Deck Stringer Plate, br'dth & thickness	38	9/16		38	9/16	
" Angle on ditto	3½ x 3½	9/16		3½ x 3½	9/16	
" Tie Plates	14	8/16		14	8/16	
" Deck. Material and thickness Teak	3	—		3	—	
Forecastle Deck Stringer Plate, b'dth & th'kns	25	5/16		25	5/16	
" Angle on ditto	3 x 3 x	5/16		3 x 3	5/16	
" Tie Plates Iron deck	—	5/16		—	5/16	
" Deck. Material and thickness	—	5/16		—	5/16	

Deep girder for 9 in length

and 3 side Stringers

* If Iron or Steel Deck, state if whole or part, and if Wood Deck is laid thereon.

BULKHEADS.	Number. In Vessel.	Number. Per Rule.	Thickness, 16ths or 20ths.	STIFFENERS. Horizontal. Inches.	STIFFENERS. Vertical. Inches.	STIFFENERS. Spacing Inches.	Single or Double Frames.	Height up.
W. T. BULKHEADS	7	6	8 & 7/16	6 x 3½ x 10/16	6 x 3½ x 10/16	48	Double	upper Deck
PARTITION "	Boiler room Bulkhead as per sketch attached							
LONGITUDINAL "								

Are the outside Plates doubled two spaces of Frames in length? Yes

Form No. 1B.

NWC839-0138

Lloyd's Register Foundation

PLATING.

STRAKES.	AS IN SHIP. Amidship. Breadth.	Amidship. Thickness.	Forward. Thickness.	Aft. Thickness.	PER RULE OR AS APPROVED. Amidship. Breadth.	Amidship. Thickness.
	Inches.	Nths or 20ths	Nths or 20ths	Nths or 20ths	Inches.	Nths or 20ths
Flat Plate Keel (If Bar Keel, state Riveting)	36	18	14	14	36	18
Garboard or A Strake	53	13 full	13 full	13 full	36	14
B "	46	12	10	11	48	12
C "	53	11	10	10	54	11
D "	46	12	10	10	48	12
E "	50	11	9	10	54	11
F "	46	13	11	11	48	13
G "	51	12	9	9	54	12
H "	45	13	10	10	48	13
J "	54	12	9	9	54	12
K "	46	13	10	9	48	13
L "	53	12	9	9	54	12
M "	46	13	10	10	48	13
N "	54	14	9	9	54	14
O "	44	18	11	11	44	18
P "						
Q "	The boss and after Load Plates as per rule					
R "						
Doubling of Flat Plate Keel	24	14	14 full		24	14
Length and thickness of Bilges		14	at ends of Bridge 18	9	each end	
Length and thickness of Sheerstrakes		✓				
Length and thickness of Strake below		✓				
Poop Sides		7/9	7/9	7/9	—	7/9
Bridge Sides		7/9	7/9	7/9	—	7/9
Forecastle Sides		7/9	7/9	7/9	—	7/9

RIVETING.

STRAKES.	EDGES. Single or Double.	Breadth of Lap. Inches.	Rivets, Diam. Inches.	Rivets, Spacing cr. to cr. Inches.	BUTTS. Double or Treble and for what Length.	Rivets, Diam. Inches.	Rivets, Spacing cr. to cr. Inches.	Straps, Breadth. Inches.	Straps, Thickness. Inches.	If Lapped, Breadth. Inches.	If Lapped, For what Length. Feet.
Flat Plate Keel	double	6	1	4	treble whole L	1	3½	19	22	✓	✓
Garboard or A Strake	"	5¼	⅞	3 13/16	"	⅞	3 1/16	✓	✓	9	whole L
B "	"	"	"	"	"	"	"	"	"	"	"
C "	"	"	"	"	"	"	"	"	"	"	"
D "	"	"	"	"	quintuple & treble whole L	"	"	"	"	"	"
E "	"	"	"	"	treble whole L	"	"	✓	✓	11¼	"
F "	"	"	"	"	"	"	"	✓	✓	9	"
G "	"	"	"	"	"	"	"	✓	✓	"	"
H "	"	"	"	"	"	"	"	✓	✓	"	"
J "	"	"	"	"	"	"	"	✓	✓	"	"
K "	"	"	"	"	"	"	"	✓	✓	"	"
L "	"	"	"	"	"	"	"	✓	✓	"	"
M "	"	"	"	"	"	"	"	✓	✓	"	"
N "	"	6	1	4	"	1	3½	✓	✓	"	"
O "	"	"	"	"	"	1	"	19	22	✓	✓
P "											
Q "	The boss and after Load Plates as per rule										
R "											
Doubling of Flat Plate Keel	double	—	1	4	treble	1	3½	19	18	✓	✓
Length and thickness of Bilges											
Length and thickness of Sheerstrakes											
Length and thickness of Strake below											
Poop Sides	single	3/4			double	3/4		9 3/4	7	✓	✓
Bridge Sides	"	"			"	"		"	7/9	✓	✓
Forecastle Sides	"	"			"	"		"	7	✓	✓

Manufacturer's name or trade mark of the Iron or Steel (state process of manufacture of Steel) used for Frames, Floors, Beams, Keelsons, Tie and Stringer Plates, Plating, &c.? Angles by Roman Iron & Co, Plates by John Spencer & Sons, and Consett Iron Co Ltd; Beams by Palmers Co Ltd, and iron by Stockton malleable iron Co Ltd and for Hill & Co

Upper Deck Stringer Plate — **Butts,** treble riveted for whole length amidship. **Straps,** ~~single,~~ double ~~or overlapped~~ for ½ length amidship.

Middle Deck Stringer Plate — **Butts,** treble riveted for at ends length amidship. **Straps,** ~~single,~~ double ~~or~~ overlapped for ½ length amidship.

Butts of Bilge & Side Stringers and Tie Plates, treble & double riveted ~~fluxed~~ square

Inner Bottom Plating, riveting of **Edges** double & single **Butts** Double

Centre Girder Butts, treble riveted **Keelson Butts,** ✓ riveted.

Frames, riveted through Plates with ⅞ in. Rivets, about 6 apart.

Rivets, state whether Iron or Steel iron

FRAMES extend in one length from flange plates to gunwale

REVERSED FRAMES on floors and frames extend from centre line to main & upper deck alternately; all to upper deck from 47 to 128 frames, & in after peak, & to main & forecastle decks alternately

MASTS, SPARS, &c.

	Material.	Total Length.	Diameter and Thickness: At Partners.	Heel.	Hounds.	Head.	No. of Plates in round.	Angles: Number.	Angles: Size.	Riveting: Seams.	Riveting: Butts.
Lower Masts: Fore	Steel	56.0	24 x 15/20	22 x 15/20	✓	20 x 11/20	2	✓	✓	double	treble
Lower Masts: Main	do	66.0	24 x 15/20	22 x 15/20	✓	20 x 11/20	2	✓	✓	"	"
Lower Masts: Mizen											
Bowsprit	✓										

Topmasts, ~~Yards~~ and Remainder of **Spars** baltic pine

Rigging, Material and Size, **Shrouds** Steel wire 6" **Stays** 6"

Sails. one Suit of ~ Sails, and the following spare sails ✓

EQUIPMENT No. 40690 LETTER X. ANCHORS.

Number of Certificate.	Anchors.	Weight, Ex. Stock. Cwts.	qrs.	lbs.	Weight of Stock. Cwts.	qrs.	lbs.	Test, per Certificate. Tons.	cwts.	qrs.	lbs.	Weight Req. by Rule. Cwts.	qrs.	lbs.	Description of Anchor.	Makers.	Where and when tested and Superintendent.
14241	1st Bower	56	0	0	Type Stockless forged Anchors			46	0	0	0	51	3	0	Type Stockless	J. Abbot & Co	L.P.H. Lw. 29/11-94
14225	2nd "	55	3	0				45	16	3	14	51	3	0	do	do	do 14/4-94
14217	3rd "	55	0	0				45	12	0	21	51	3	0	"	"	" 3/5-94
14190	Collective weight	222	0	1				45	7	2	0	44	1	0	"	"	" 15/10-94
												199	2	0			
14065	Stream	12	3	14	3	1	14	14	12	3	7	12	3	0	Rodgers	"	" 15/6-94
14066	Kedge	6	3	0	1	3	0	9	0	0	0	6	2	0	"	"	" 31/8-94
	2nd Kedge																

Marked L.P.H. Lw & Certificates signed C.E. Perrins

CHAIN CABLES.

Number of Certificate.	Fathoms.	Size.	Test per Certificate. Tons.	Weight of Chain Cable: Supplied.	Weight of Chain Cable: Per Rule.	Fathoms and Size per Rule.	Description.	Makers of Cables.	When and where tested, and Superintendent.
6920	135	2 1/16	71 1/5 12 7 12	3542.0	382.1.11	270 - 2 3/16	Stud link	J. Abbot & Co	L.P.H. Lw. 5/7-94
6929	135	2¼	"	356.3.3 11.1.21				"	" 3/8-94
Iron Stream Chain or Steel Wire	90	4½	39	Steel wire		90 - 4½			

HAWSERS AND WARPS.

Material	Fathoms.	Size.	Breaking Test of Steel Wire Towline.	Fathoms and Size Per Rule.
Steel wire Towline	120	4½	39	120 - 4½
Hawser	90	3½	26	90 - 11
Manilla Warp	90	12	—	90 - 9
"	90	8½	—	Nil
"	90	8½	—	"
"	90	8½	—	"

Boats 6 No

Pumps, Number 8 No.; One placed in Engine room Diameter of Barrel and Tail Pipe 6 & 5 & 4 Stoneshot, Aft 2½

Windlass is Harfields Steam Patt. **Capstan** Clarke, Chapmans Patt.

Engine Room Skylights.—How constructed? of iron

What arrangements for deadlights in bad weather? Iron shutters and thick circular glass in each

Coal Bunker Openings.—How constructed? Plate hatchways How are lids secured? Solid hatches Height above deck? 9"

Number of **Scuppers,** and numbers and dimensions of **Freeing Ports, &c.** 7 Scuppers & 7 Ports each side, latter 26 x 17½

Ceiling in Holds, thickness and material ½ round iron 3 x 12/16 solid **Ceiling 'tween Decks,** thickness and material 2" Pitch & Baltic pine in flat

Cargo Hatchways.—How formed? Iron plate combings & Headledges **Hatches,** If strong and efficient? 3" Solid

State size **No. 1 Hatch** (Forward) 18.8 x 15.10 **No. 2 Hatch** 29.0 x 15.10 **No. 3 Hatch** 29.0 x 15.10 **No. 4 Hatch** 18.5 x 15.10

Number of **Web Plates, Shifting Beams** and **Fore** and **Afters** to each Hatch One deep web in Nos 1 2 4 & 2 deep webs in Nos 2 & 3, with 3 fore & afters to each **No. of Breasthooks** 7 **No. of Crutches** 3 x 4 flat & 2 x 6 x 3½

Bulwarks, height above deck and description 3.6 of iron 4/16 Main Rail, material and size Iron bulb mouldings

The above is a correct description.

Builder's Signature (here [illegible]) DIRECTOR

Surveyor's Signature James Gibson

Surveyor to Lloyd's Register of British and Foreign Shipping.

Form No. 12.

Correspondence.—State dates and initials of letters respecting this case (*Reference should be made to any correspondence connected with this case*) M. 1 March/94 M. 6 March; M. 5 March; M. 16 March; M. 21 April; R. 21 April; R. 27 April; ~~M. 28 June~~ and R. 6 Sept. 1894 & M. 31 Dec. 94

Workmanship. Are the butts of plating planed or otherwise fitted? Planed

Is the riveted work properly closed? Yes

Are the liners between the frames and plates solid single pieces? Yes Do the holes for riveting plate to frames, butt straps, or plate to plate, &c., conform well to each other? yes Are the rivet holes well and sufficiently countersunk in the plate and punched from the faying surfaces? yes Do any rivets break into or through the seams or butts of plating? a very few

Are the butts of Plating, Stringers, &c., properly shifted and strapped? Yes

General Remarks (State quality of workmanship, &c.) This vessel has been built of Steel in accordance with the rules and approved tracings of Midship Section Profile &c, on the Girder frame system, and with cellular double bottom throughout, with solid floors to every frame, and the floors centre line & side girders in the Boiler Space and the top of inner bottom throughout, are of iron. The water ballast tank under engines is made water-tight at the centre girder, & the inner bottom fore and aft, and the after peak tested to a head of water as per rule & proved Satisfactory. The tunnel filled & tested to a head of water equal to the ~~load draught~~ (Surveyor's letter 29.1.95) ~~of 33 ft~~, & found quite water-tight; The deck tested with water and the Pumps & Sluice Valves examined & found in good working order The Materials and workmanship being of a good description throughout. additional ~~stiffening~~ fitted to bulkheads in shaft tunnel as per sketch, the horizontal bulb angle at the thwartship end fitted on the aft side of bulkhead and one strong vertical bar on the fore side.

The Surveyor should state the Number of Report and Name of any Sister Vessel.

PARTICULARS FOR RECORD in the REGISTER BOOK.—Length of Poop 38.6 ft., R.Q.D. or Break — ft., Bridge Dk 97.9 ft., F'castle 39.3 ft. (in feet and tenths). When the Poop is joined to the B.D., this should be distinctly stated ✓

No. and Material of Decks (if Iron or Steel) and whether wholly or partially covered with wood, and No. of tiers of Beams (this information is to be given as it should appear in the Register Book) 1 Deck (iron), 1 Deck (Steel), and Girder framed

Official No. ; Signal Letters

How are the surfaces preserved from oxidation? Inside Wailes & Dove's pat. Cement Outside 3 Coats of paint & Paint

PARTICULARS OF WATER BALLAST.—State whether the Double bottom is constructed on the cellular system Cellular bottom throughout

Where fitted.	Length. Feet.	Water Capacity. Tons.	Where fitted.	Length. Feet.	Water Capacity. Tons.
Double bottom, aft,	95.10	295	Fore peak tank,	✓	✓
Double bottom, forward,	141.8	473	After peak tank,	12.6	60
Double bottom, under Engines and Boilers,	58.11	237	Midship deep tank,	✓	✓
Double bottom, if under Engines only,	✓	1005	Other tanks, if fitted, Tunnel Tank	✓	130
Double bottom, if under Boilers only,	✓	✓	(If necessary, furnish further information by sketch.) see Surveyor's letter 29.1.95		

State whether the above have been tested as required by the Rules Yes

Order for Special Survey No. 2597 Date 3 April 1894

Order for Ordinary Survey No. ✓ Date ✓

No. 610 in builder's yard.

Dates of Surveys held while building as per Section 18.

1st. On the several parts of the frame, when in place, and before the plating was wrought 1894 Mar. 9 19 22 29 Apl. 2 4 13 18 20 25 May 2 4 8 11 14 23 25 June 1 5 8 12 13 15 16 19 21 22 July 4 6 9 12 13 16 19 23 24 26 27 30 Aug. 1 3 8 9 10 13 15 16 17 20 22 24 Sept. 3 5 6 7 10 12 13 19 21 25 28 Oct. 2 3 10 13 15 19 21 28 Dec. 6 11 12 13 14 20 21 26 29 Jan. 9

2nd. On the plating during the process of riveting

3rd. When the beams were in and fastened, and before the decks were laid

4th. When the ship was complete, and before the plating was finally coated or cemented

5th. After the ship was launched and equipped

Total No. of Visits 96

The amount of Entry Fee £ 5 : : Fees applied for, 16.1.1895

Special Survey Fee £131 : 18 : Received by me, 20/11/95 18

Travelling Expenses, if any £ : : GBM 28

Certificate to be sent to Newcastle Office

I am of opinion this Vessel should be Classed ✠ 100 A1

With, or without Freeboard, as condition of Class ✓

James Gibson

Surveyor to Lloyd's Register of British and Foreign Shipping.

Committee's Minute

Character assigned 100 A1 Steel

This vessel appears to have been built in accordance with the Rules and the approved plans, and it is submitted she is eligible to be classed 100 A1 (Steel) as recommended.

Laid up
+ RMC 1.95
2 Dks (1 Stl. + 1 Trans + Deep framing 3 Dk Rule
Engine

+ 100 A1 (Steel)
2 Dk (1 Stl. 71 Trans & deep framing 3 Dk Rule
M.B = Cell D.B. a 96 in. F.R 58 ft 142 in. 1005 t. APT 60 t.
F.K. Asp.

The Surveyors are requested not to write on or below the Committee's Minute.

The Surveyor is desired to be requested to state the capacity of the Tunnel Tanks for record on the Register Book.
See Surveyor's reply dated 29-1-95

© 2021 Lloyd's Register Foundation