

Do. of Forecastle (Hours) 9.57 Transverse Number 84.16 When built 1919 Launch
 Do. of Houses on Deck 109.46 Length on deck from fore part of stem to after part of
 Do. of excess of Hatchways 36.48 sternpost 411.50 By whom built Messrs J. L. J. K.
 Do. above Crown of Engine P

how named "Bosworth"

F.E.

Received by Chief Ship Surveyor _____ Received from Chief Ship Surveyor _____

VESSEL'S NAME Steel S.S. "WAR PERIDOT". Rpt. Sld. No. 27456

The remarks of the Chief Ship Surveyor are desired on this case for the consideration of the Classing Committee.

("The endorsement to contain a succinct summary of any repairs that have been required and to show the cause or causes of such repairs, and also to bring out clearly any exceptional features in connection with the case, so that the Classing Committee may have all the salient points presented in the endorsement." - Extract from Sub-Committee's Report, 24/5/92.)

Transverse No. 84.16 Depth "d" 25.33

Framing: Table No. 3 page 16. Description Channels as approved.

Longitudinal No. 34632

Proportions $\frac{\text{Length}}{\text{Depth}} = 11.12$

Shelter Deck Sheerstrake as approved.

The dnton pump has been dispensed with as in Standard vessels. The vessel is now owned by the Canadian Pacific Railway Co. and it is concluded they are agreeable to fit the pump at the termination of the War if requested to do so. A kedge anchor was delivered after the vessel had left the Builders yard, and it has been arranged for this to be placed on board at the first port in the United Kingdom at which she calls.

This vessel appears to have been built in accordance with the Rules and the approved plans, and it is submitted she is eligible to be classed * 100 A.1. (Steel) Shelter Dk. with freeboard," as recommended. The Summer freeboard of 8.11½ from centre of disc to top of statutory deck line at Shelter deck, now marked on the vessel's sides, to be inserted in the classification certificate, and recorded in the Register Book, and further, the remaining freeboards, as shown on the accompanying verification form to be inserted in the certificate of classification.

1 Dk. (Steel) and Shelter Dk. (Steel).

Cell DB 366' 1362t. DTa 26' 997t. FPT 154t. APT 224t.

FK. 6 BH to Shelter Dk. 2 BH to Upper Dk. pt. Cem. Lloyd's A. & C.P. F. on Shelter Dk. 36'.

The Certificate of Classification, to be endorsed "Gerys battens not fitted," and the same notation to be printed in the Register Book.

It should be stated in special reasons list that a kedge anchor requires to be placed on board.

22. 3. 19. Lloyd's Register Foundation

Angles on upper edge		Angles on ditto
Spacing		Tie Plates
BEAMS, Poop Deck, Angle, Bulb Angle, Plate, Tee Bulb or Channel		Deck Material and thickness