

REPORT ON ELECTRICAL EQUIPMENT.

(OTHER THAN FOR THE PROPULSION OF THE VESSEL)

194 OCT 1942

Received at London Office

Date of writing Report 21 AUGUST 1942 When handed in at Local Office 21 AUGUST 1942 Port of VANCOUVER, B.C.

No. in Survey held at ESQUIMALT, B.C. Date, First Survey 24 APRIL Last Survey 27 JUNE 1942
Reg. Book. (Number of Visits 15)

on the STEEL SINGLE SCREW STEAMER "FORT MELEOD" Tons {Gross 7127.10
Net 4260.69

Built at ESQUIMALT, B.C. By whom built YARROWS LTD Yard No. 67 When built 1942

Owners MINISTER OF MUNITIONS & SUPPLY OF CANADA Port belonging to -

Electric Light Installation fitted by YARROWS LTD Contract No. - When fitted 1942

Is the Vessel fitted for carrying Petroleum in bulk No

System of Distribution CONSTANT PRESSURE TWO WIRE, DIRECT CURRENT

Pressure of supply for Lighting 110 volts, Heating - - - volts, Power 110 volts.

Direct or Alternating Current, Lighting DIRECT Power DIRECT

If alternating current system, state frequency of periods per second -

Has the Automatic Governor been tested and found efficient when the whole load is suddenly thrown on or off YES

Generators, do they comply with the requirements regarding temperature rise YES, are they compound wound YES

are they over compounded 5 per cent. NO, if not compound wound state distance between each generator -

Where more than one generator is fitted are they arranged to run in parallel NO, is an adjustable regulating resistance fitted in series with each shunt field YES

Have certificates of test results for machines under 100 kw. been submitted and approved YES - SEE GENERAL REMARKS

Have machines over 100 kw. been inspected by the Surveyors during manufacture and testing UNDER 100 K.W.

Are all terminals accessible, clearly marked, and furnished with sockets YES, are they so spaced or shielded that they cannot be accidentally earthed, short circuited, or touched YES

Are the lubricating arrangements of the generators as per Rule YES

Position of Generators CENTRE OF ENGINE ROOM - STARBOARD SIDE - LOWER PLATFORM, is the ventilation in way of the generators satisfactory YES

are they clear of all inflammable material YES if situated near unprotected

woodwork or other combustible material, state distance of same horizontally from or vertically above the generators - and -

are the generators protected from mechanical injury and damage from water, steam or oil YES, are their axes of rotation fore and aft YES

Earthing, are the bedplates and frames of the generating plant efficiently earthed YES are the prime movers and their respective generators in metallic contact YES

Main Switch Boards, where placed AFT. END. OF ENGINE ROOM - STARBOARD SIDE - AFTWARTSHIPS

ON LOWER PLATFORM. If the generators and main switchboard are not placed in the same compartment, is each generator provided with a fuse on each insulated pole as near as possible to the terminals of the generator, additional to that provided on the main switchboard SAME COMPARTMENT

Switchboards, are they placed in accessible positions, free from inflammable gases and acid fumes YES, are they protected from mechanical injury and damage from water, steam or oil YES

if situated near unprotected woodwork or other combustible material, state distance of same horizontally from or vertically above the switchboards - and -

are they constructed wholly of durable, non-ignitable non-absorbent materials EBONY ASBESTOS

is all insulation of high dielectric strength and of permanently high insulation resistance YES

is it of an approved type YES, if semi-insulating material is used, are all conducting parts insulated from the slab with mica or micanite or other non-hygroscopic insulating material, and the slab similarly insulated from its framework -

is the non-hygroscopic insulating material of an approved type YES

and is the frame effectively earthed YES Are the fittings as per Rule regarding:—spacing or shielding of live parts YES

accessibility of all parts YES, absence of fuses on back of board YES, temperature rise of omnibus bars 2° F.

individual fuses to voltmeter, pilot or earth lamp YES, are moving parts of switches alive in the "off" position NO

are all screws and nuts securing connections effectively locked YES are any fuses fitted on the live side of switches NO

Main Switchgear, description of switchgear for each generator and each outgoing circuit, and arrangement of equalizer switches DOUBLE POLE LINKED SWITCH WITH A FUSE ON EACH POLE FOR EACH GENERATOR AND A D.P.D.T. LINKED SELECTOR SWITCH WITH A FUSE ON EACH POLE FOR EACH OUTGOING CIRCUIT.

Are turbine driven generators fitted with emergency trip switch as per rule - Are cupboards or compartments containing switchboards composed of fire-resisting material or lined with approved material -

Instruments on main switchboard 2 ammeters 2 volt-meters

synchronising device for paralleling purposes. For compound machines is the ammeter connected on the opposite pole to equaliser connection NO EQUALISER CONNECTIONS FITTED

Earth Testing, state what means are provided at the main switchboard for indicating the state of the insulation of the system POSITIVE & NEGATIVE EARTH LAMPS & SWITCHES

Switches, Circuit Breakers and Fusible Cut-outs, do these comply with the requirements of the Rules YES are the fusible cutouts of an approved type YES

have the reversed



© 2020

W188-0158 1/2 Register's Foundation

current protection devices been tested under working conditions. NOT FITTED. Joint Boxes, Section and Distribution Boards, is the construction, protection, insulation, material, and position of these as per rule. YES

Cables: Single, twin, concentric, or multicore SINGLE OR TWIN CORE are the cables insulated and protected as per Tables IV, V, X or XI of the Rules. YES

If the cables are insulated otherwise than as per Rule, are they of an approved type. YES Fall of Pressure, state maximum between bus bars and any point of the installation under maximum load. 4-VOLTS Cable Sockets, are the ends of all cables having a sectional area of 0.04 square inch and above provided with soldering sockets. YES Paper Insulated and Varnished Cambric Insulated Cables.

If conductors are paper or varnished cambric insulated, is the dielectric at the exposed ends of the conductor protected from moisture by being suitably sealed with insulating compound -, or waterproof insulating tape - Cable Runs, are the cables fixed as far as possible in accessible positions not exposed to drip or accumulation of water or oil, or to high temperature from boilers, steam pipes, uptakes or other hot objects, or to avoidable risk of mechanical damage. YES Are cables in machinery spaces, galleys, laundries, bathrooms and lavatories lead covered or run in conduit. LEAD COVERED CONDUIT

Support and Protection of Cables, state how the cables are supported and protected. CLIPPED TO WOODWORK IN ACCOMMODATION BY BRASS CLIPS SPACED AS PER RULE AND RUN IN WOOD CASINGS, ELSEWHERE RUN IN CONDUIT, ALL CABLES PROTECTED BY METAL GUARDS WHERE LIABLE TO DAMAGE.

If cables are run in wood casings, are the casings and caps secured by screws. YES, are the cap screws of brass. YES, are the cables run in separate grooves. - If armoured and lead covered cables are secured by metal clips, are the clips spaced as per Table VIII. YES

Refrigerated Chambers, are the cables and fittings in accordance with the special requirements. -

Joints in Cables, state if any, and how made, insulated, and protected. NONE EXCEPT AT JUNCTION BOXES.

Watertight Glands and Deck Tubes, are all cables passing through decks and watertight bulkheads provided with deck tubes or watertight glands. YES. Bushes in Beams and Non-watertight Partitions, where unarmoured cables pass through beams and non-watertight partitions, are the holes efficiently bushed. YES. state the material of which the bushes are made. LEAD AND HARDWOOD COLLARS.

Earthing Connections, state what earthing connections are fitted and their respective sectional areas. LEAD COVERED CABLES, CONDUIT AND METAL TRAYS EFFECTIVELY EARTHED.

are their connections made as per Rule. YES.

Alternative Lighting, are the groups of lights in the propelling machinery space arranged as per Rule. YES. Emergency Supply, state position and method of control of the emergency supply and how the generator is driven. NOT FITTED.

Navigation Lamps, are these separately wired. YES, controlled by separate switch and separate fuses. YES, are the fuses double pole. YES, are the switches and fuses grouped in a position accessible only to the officers on watch. YES - IN WHEELHOUSE.

has each navigation lamp an automatic indicator as per Rule. YES Secondary Batteries, are they constructed and fitted as per Rule. -

Fittings, are all fittings on weather decks, in stokeholds and engine rooms and wherever exposed to drip or condensed moisture, watertight. YES, are any fittings placed in spaces in which goods are liable to be stacked in close proximity to them; if so, how are they protected. CAST METAL GUARDS.

are any fittings placed in spaces where inflammable or explosive dust or gases are liable to be present, if so, how are they protected. NONE.

how are the cables led

where are the controlling switches situated. -

are all fittings suitably ventilated. -, are all switches and lampholders constructed wholly of non-ignitable, non-absorbent materials. YES.

Heating and Cooking Appliances, are they constructed and fitted as per Rule. YES, are air heaters constructed and fitted as per Rule. NOT FITTED.

Searchlight Lamps, No. of NONE, whether fixed or portable. -, are their fittings as per Rule. -

Arc Lamps, other than searchlight lamps, No. of NONE, are their live parts insulated from the frame or case. -, are their fittings as per Rule. -

Motors, are their working parts readily accessible. YES, are the coils self-contained and readily removable for replacement. YES, are the brushes, brush holders, terminals and lubricating arrangements as per Rule. YES, are the motors placed in well-ventilated compartments in which inflammable gases cannot accumulate and clear of all inflammable material. YES, are they protected from mechanical injury and damage from water, steam or oil. YES are their axes of rotation fore and aft. WHERE POSSIBLE, j situated near unprotected woodwork or other combustible material, are the motors of the totally enclosed, pipe ventilated, forced draught, drip or flame proof type. -

if not of this type, state distance of the combustible material horizontally or vertically above the motors. - and -

have machines of over 100 BHP been inspected by the Surveyors during manufacture and testing. UNDER Control Gear and Resistances, are the generator field and motor speed regulators, starters and controllers constructed and fitted as per Rule. YES Lightning Conductors, where lightning conductors are required, are these fitted as per Rule. NOT FITTED Ships carrying Oil having a Flash Point less than 150°F. Have the special requirements of the Rules been complied with regarding switches, joint boxes, section and distribution boards, protection of cables, method of distribution, lead of cables, lights and fittings. - are all fuses of the filled cartridge type. - are they of an approved type. -

If portable lamps for use in dangerous spaces are supplied, are they of a self-contained, battery-fed type approved by the Home Office. -

Spare Gear, if the vessel is for open sea service have spares been supplied as per Rule. YES

PARTICULARS OF GENERATING PLANT.

DESCRIPTION OF GENERATOR.	No. of	RATED AT				DRIVEN BY	WHERE DRIVEN BY AN INTERNAL COMBUSTION ENGINE.	
		Kilowatts.	Volts.	Amperes.	Revs. per Min.		Fuel Used.	Flash Point of Fuel.
MAIN ...	Two	15	115	130	570	STEAM RECIPROCATING.		
AUXILIARY ...								
EMERGENCY ...								
ROTARY TRANSFORMER								

GENERATOR, LIGHTING AND HEATING CONDUCTORS.

DESCRIPTION.	CONDUCTORS.		COMPOSITION OF STRAND.		TOTAL MAXIMUM CURRENT. AMPERES.		Approximate Length. (Lead and Return.) Feet.	Insulated with	HOW PROTECTED
	No. per Pole.	Total Nominal Area per Pole Sq. Ins.	No.	Diameter.	In Circuit.	Rule.			
MAIN GENERATOR ... No. 1	2	.2	19	.083	130	236	60	RUBBER/INSULATED	LEAD COVERED.
... No. 2	2	.2	19	.083	130	236	40	Do Do.	Do Do.
AUXILIARY GENERATOR ...									
EMERGENCY GENERATOR ...									
ROTARY TRANSFORMER MOTOR GENERATOR ...									
ENGINE ROOM ...	1	.032	7	.077	20	55	50	V.L.R.	DOUBLE BRAIDED IN CONDUIT.
BOILER ROOM ...									
AUXILIARY SWITCHBOARDS									
SECT. BOX "S1" (D1-D2-D3)	1	.104	19	.083	59	118	280	Do	Do Do.
SECT. BOX "S2" (D4-D5-D6-D7-D8)	1	.052	7	.097	72	70	86	Do	Do Do.
" " "D10" (ER. FAN)	1	.020	7	.061	89	44	20	Do	Do Do.
ACCOMMODATION ENGINES "D4"	1	.032	7	.077	17	55	4	Do	Do Do.
" CREW APT. "D7"	1	.032	7	.077	24	55	338	Do	Do Do.
" SALOON "D2"	1	.032	7	.077	17	55	4	Do	Do Do.
" CAPT. BRIDGE "D1"	1	.032	7	.077	20	55	68	Do	Do Do.
WIRELESS ...	1	.032	7	.077	23	70	324	Do	Do Do.
NAVIGATION ...	1	.0081	7	.038	25	27	324	Do	Do Do.
MASTHEAD LIGHT ...	1	.0032	7	.024	3	10	358	Do	Do Do.
SIDE LIGHTS ...	1	.0032	7	.024	6	10	74	Do	Do Do.
COMPASS LIGHTS ...	1	.0032	7	.024	3	10	44	Do	Do Do.
CARGO LIGHTS AFT. "D6"	1	.032	7	.077	14	55	180	Do	Do Do.
CARGO LIGHTS AHEAD "D5"	1	.032	7	.077	17	55	4	Do	Do Do.
DECK LIGHTS FORWARD "D3"	1	.032	7	.077	22	55	200	Do	Do Do.
REFRIG. DISTB. "D9"	1	.012	7	.048	27	34	320	Do	Do Do.

MOTOR CONDUCTORS.

DESCRIPTION.	No. of Motors.	CONDUCTORS.		COMPOSITION OF STRAND.		TOTAL MAXIMUM CURRENT. AMPERES.		Approximate Length. (Lead and Return.) Feet.	Insulated with	HOW PROTECTED
		No. per Pole.	Total Nominal Area per Pole Sq. Ins.	No.	Diameter.	In Circuit.	Rule.			
BALLAST PUMP ...										
MAIN BILGE LINE PUMPS ...										
GENERAL SERVICE PUMP ...										
EMERGENCY BILGE PUMP ...										
SANITARY PUMP ...										
CIRC. SEA WATER PUMPS ...										
CIRC. FRESH WATER PUMPS...										
AIR COMPRESSOR ...										
FRESH WATER PUMP ...										
ENGINE TURNING GEAR ...										
ENGINE REVERSING GEAR ...										
LUBRICATING OIL PUMPS ...										
OIL FUEL TRANSFER PUMP ...										
WINDLASS ...										
WINCHES, FORWARD ...										
WINCHES, AFT... ..										
STEERING GEAR—										
(a) MOTOR GENERATOR ...										
(b) MAIN MOTOR ...										
WORKSHOP MOTOR... ..										
VENTILATING FANS ...	1	1	.003	7	.024	45	10	20	V.L.R.	DOUBLE BRAIDED IN CONDUIT.
ENGINE ROOM FAN	1	1	.008	7	.038	89	27	110	Do	Do Do.
REFRIG. MOTOR.	1	1	.008	7	.038	16	27	20	Do	Do Do.

All Conductors are of annealed copper conforming to British Standard Specification No. 7 (or International Electro-technical Commission Publication No. 28).

The Insulated Conductors are guaranteed to withstand the immersion and resistance tests specified in the Rules.

The foregoing is a correct description.

FOR YARROWS LIMITED

John Cameron

Electrical Engineers.

Date 21 August 1942.

COMPASSES.

Distance between electric generators or motors and standard compass 25 FEET.

Distance between electric generators or motors and steering compass 20 FEET.

The nearest cables to the compasses are as follows:—

A cable carrying .3 Ampères 1.0 feet from standard compass 1.5 feet from steering compass.

A cable carrying .35 Ampères 5 feet from standard compass 3.5 feet from steering compass.

A cable carrying 1.36 Ampères 9.5 feet from standard compass 6 feet from steering compass.

Have the compasses been adjusted with and without the electric installation at work at full power YES

Has the effect of switching on and off circuits, motors and other electro-magnetic apparatus within the vicinity of the compasses been noted YES

The maximum deviation due to electric currents was found to be Nil degrees on ALL course in the case of the standard compass, and Nil degrees on ALL course in the case of the steering compass.

FOR YARROWS LIMITED

John Cameron

Builder's Signature.

Date 21 August 1942.

Is this installation a duplicate of a previous case YES If so, state name of vessel S.S. "FORT ST. JAMES" Ver. Rpt. N° 5718

General Remarks (State quality of workmanship, opinions as to class, &c. The Electrical equipment of this

ship has been installed under special survey in accordance with the approved plans, New York Letters and Society's Rules. The Materials and workmanship are good. The installation has been examined under full working conditions, tested as per Rule and found satisfactory and in our opinion, is eligible to have the Society's Classification without Special Notation. Copies of particulars of ships trials on generators attached. Maker's certificates covering steam auxiliary engines, (driving generators) and generators attached.

As fitted plans of electrical wiring attached.

The Electrical equipment has also been surveyed during construction and installation on behalf of Wartime Merchant Shipping Ltd., to ensure that the terms of the Specification have been fully complied with and this work has been satisfactorily carried out.

Total Capacity of Generators 30 Kilowatts.

The amount of Fee ... \$125.00

Travelling Expenses (if any) \$25.00

When applied for, 3RD JULY 1942
When received, 19

A. J. Boomer
Surveyor to Lloyd's Register of Shipping.

Committee's Minute TUE 10 NOV 1942

Assigned See Ver. Rpt. N° 5776