

Rpt. 13.

REC'D NEW YORK July 29-1919

REPORT ON ELECTRIC LIGHTING INSTALLATION. No. 3339

Received at London Office THURSDAY 1919

Port of Philadelphia Date of First Survey 28th Jan'y Date of Last Survey 22nd July '19 No. of Visits 33
 No. in Reg. Book on the Iron or Steel 1/3 "LUXPALILE" Port belonging to Philadelphia
 Built at Philadelphia By whom American International Corp When built 1919
 Owners United States Shipping Board Owners' Address Washington D.C.
 Yard No. 529 Electric Light Installation fitted by American International Corp When fitted 1919

DESCRIPTION OF DYNAMO, ENGINE, ETC.

Dynamos-two-15 K.W. 125 Volts, compound wound, direct connected, to vertical marine type
 Steam engine, operating at 80-125 lbs. pressure. General Electric Co.
 Capacity of Dynamo 2 of 120 Amperes at each at 125 Volts, whether continuous or alternating current continuous
 Where is Dynamo fixed Flat Starboard side of engine Room Whether single or double wire system is used double wire
 Position of Main Switch Board Dynamo Flat near blkhd. 109 having switches to groups 7 lighting Panels of lights, &c., as below
 Positions of auxiliary switch boards and numbers of switches on each Panel G-Engine and Boiler Room-8-circuits, D-Bridge deck Port -6-circuits; C-Bridge deck starboard-4 circuits; B-Officers Qtrs-9-circuits; A-Forecastle -4- Circuits; Panel F-Poop-6-Circuits; H- Pilot House -6 cir.
 If fuses are fitted on main switch board to the cables of main circuit yes and on each auxiliary switch board to the cables of auxiliary circuits yes and at each position where a cable is branched or reduced in size yes and to each lamp circuit yes
 If vessel is wired on the double wire system are fuses fitted to both flow and return wires or cables of all circuits including lamp circuits yes
 Are the fuses of non-oxidizable metal yes and constructed to fuse at an excess of 125 per cent over the normal current
 Are all fuses fitted in easily accessible positions yes Are the fuses of standard dimensions yes If wire fuses are used
 are permanent instructions fitted on or near each switch board giving particulars of proper size of fuse for each circuit cartridge fuses used
 Are all switches and fuses constructed of incombustible materials and fitted on incombustible bases yes
 Total number of lights provided for 245 arranged in the following groups:-
 A-Forecastle lights each of 13-25 to 200 Watts candle power requiring a total current of 8.0 Amperes
 B-Officers Qtrs lights each of 61-10 to 200 candle power requiring a total current of 28.7 Amperes
 C-Starboard " lights each of 25-25 to 200 candle power requiring a total current of 12.5 Amperes
 D-Port Quarters lights each of 43-25- to 200 candle power requiring a total current of 20.5 Amperes
 E-Poop " lights each of 35-10 to 200 " candle power requiring a total current of 17.7 Amperes
 F-Engine & Boiler Room lights each of 62-25 to 200 " candle power requiring a total current of 33.9 Amperes
 G-Pilot House 1 Mast head light with 1 lamps each of 50 " candle power requiring a total current of 0.5 Amperes
 2 Side light with 1 lamps each of 50 " candle power requiring a total current of 0.8 Amperes
 13 Cargo lights of 200 " candle power, whether incandescent or arc lights Incandescent
 If arc lights, what protection is provided against fire, sparks, &c. Arc light with enclosed carbons for Search light

Where are the switches controlling the masthead and side lights placed Panel H. Wheel House

DESCRIPTION OF CABLES.

Cable Description	Amperes	Wires	W.G. diameter	square inches total sectional area
Main cable carrying 120	120	Stranded, each #00	0.104	
Branch cables carrying 50	50	" wires, each #2	0.052	
Branch cables carrying 35	35	" wires, each #6	0.021	
Branch cables carrying 22	22	" wires, each #10	0.0082	
Leads to lamps carrying 18	18	Solid wires, each #12	0.0051	
Leads to lamps carrying 10	10	" wires, each #14	0.0032	
Cargo light cables carrying 10	10	" wires, each #12	0.0051	

DESCRIPTION OF INSULATION, PROTECTION, ETC.

All lighting wires in galvanized conduit $\frac{1}{4}$ in to $1\frac{1}{2}$ in. dia.
 #00, #2, #6 Rubber Covered tape and Braid code wire
 #10, #12, and #14 " " single braid code wire


Joints in cables, how made, insulated, and protected

In boxes at conduit Junction (Benj. G. I. Boxes)

Are all the joints of cables thoroughly soldered, and the flux used not containing acids or other corrosive substances yes Are all joints in accessible positions, none being made in bunkers, cargo spaces, or spaces which may at any time be used for carrying cargo, stores, or baggage yes

Are there any joints in or branches from the cable leading from dynamo to main switch board no

How are the cables led through the ship, and how protected Galvanized conduit from switchboard to fixture



WISIS-0143

© 2021 Lloyd's Register Foundation

DESCRIPTION OF INSULATION, PROTECTION, ETC.—continued.

Are they in places always accessible yes

What special protection has been provided for the cables in open alleyways or where exposed to weather or moisture
In water tight conduit with locknuts and washers at bulkheads

What special protection has been provided for the cables near galleys or oil lamps or other sources of heat In galvanized iron conduit

What special protection has been provided for the cables near boiler casings galvanized iron conduit

What special protection has been provided for the cables in engine room

How are cables carried through beams Steel conduit in drilled holes through bulkheads, &c. with locknuts and washers

How are cables carried through decks " " with locknuts and washers

Are any cables run through coal bunkers no or cargo spaces yes or spaces which may be used for carrying cargo, stores, or baggage steel conduit with guards

If so, how are they protected in steel conduit

Are any lamps fitted in coal bunkers or spaces which may at times be used for cargo, coals, or baggage not in Cargo Space

If so, how are the lamp fittings and cable terminals specially protected No lamps in Cargo space or coal Bunkers

Where are the main switches and fuses for these lights fitted " " " " " " " "

If in the spaces, how are they specially protected " " " " " " " "

Are any switches or fuses fitted in bunkers " " " " " " " "

Cargo light cables, whether portable or permanently fixed Portable How fixed not fixed

In vessels fitted on the single wire system, how is the dynamo terminal fixed to the hull of vessel double wire system used

How are the returns from the lamps connected to the hull double wire system with no grounds

Are all the joints with the hull in accessible positions " " " " " " " "

Is the installation supplied with a voltmeter yes, and with an amperemeter yes, fixed on Switchboard

VESSELS BUILT FOR CARRYING PETROLEUM.

In vessels built for carrying petroleum, are all switches and fuses fitted in positions not liable to the accumulation of petroleum vapour or gas yes

Are any switches, fuses, or joints of cables fitted in the pump room or companion not oil Carrier

How are the lamps specially protected in places liable to the accumulation of vapour or gas " " "

The copper used is guaranteed to have a conductivity of not less than that of the Engineering Standards Committee's standard, and the wires are protected by tinning from the sulphur compounds present in the insulating material.

Insulation of cables is guaranteed to have a resistance of not less than 600 megohms per statute mile at 60° Fahrenheit after 24 hours' immersion in water, the test being made after one minute's electrification at not less than 500 volts and while the cable is still immersed.

The foregoing statements are a correct description of the Electric Light installation fitted by us on this vessel and we declare that it is at this date in good order and safe working condition.

COMPASSES.

Distance between dynamo or electric motors and standard compass 100 ft.

Distance between dynamo or electric motors and steering compass 110 "

The nearest cables to the compasses are as follows:—

Cable	Amperes	Distance from standard compass	Distance from steering compass
A cable carrying <u>40</u>	<u>6</u>	<u>5</u> feet from standard compass	<u>5</u> feet from steering compass
A cable carrying <u>4</u>	<u>6</u>	<u>5</u> feet from standard compass	<u>5</u> feet from steering compass
A cable carrying <u>2</u>	<u>4</u>	<u>4</u> feet from standard compass	<u>4</u> feet from steering compass

Have the compasses been adjusted with and without the electric installation at work at full power yes

The maximum deviation due to electric currents, etc., was found to be 0 degrees on 0 course in the case of the standard compass and 0 degrees on 0 course in the case of the steering compass.

GENERAL REMARKS.

This electric lighting installation has been well fitted and proved satisfactory on trial

It is submitted that

this vessel is eligible for

THE RECORD. Elec. light.

AWD 26/8/19

Bluelock.
Surveyor to Lloyd's Register of Shipping.

Committee's Minute

Elec Lt

New York JUL 29 1919



© 2021

Lloyd's Register Foundation

THE SURVEYORS ARE REQUESTED NOT TO WRITE ACROSS THIS MARGIN.