

REPORT ON STEAM RECIPROCATING ENGINE MACHINERY.

Received at London Office

Date of writing Report 6-1940 When handed in at Local Office 19 Port of Rotterdam
 To. in Survey held at Schiedam Date, First Survey ? Last Survey 24-4-1940
 Reg. Book. STAD ALKMAAR (Number of Visits 62)
 on the 5/ Tons { Gross 5750
 Net 1940
 Built at Schiedam By whom built N.V. Wilton-Typhoon Yard No. 663 When built 1940
 Engines made at Amsterdam By whom made N.V. Werkspoor Engine No. ? When made 1940
 Makers made at do. By whom made do. Boiler No. 2078/2/80 When made 1940
 Registered Horse Power IHP 2500 Owners Halcyon Lijn N.V. Port belonging to Rotterdam
 n. Horse Power as per Rule 510 Is Refrigerating Machinery fitted for cargo purposes no Is Electric Light fitted Yes
 de for which Vessel is intended ?

GINES, &c.—Description of Engines Triple expansion Sea Amsterdam exp. N. 15909 Revs. per minute 74
 a. of Cylinders ✓ Length of Stroke ✓ No. of Cylinders ✓ No. of Cranks ✓
 ank shaft, dia. of journals as per Rule Crank pin dia. ✓ Crank webs Mid. length breadth ✓ Thickness parallel to axis ✓
as fitted ✓ Mid. length thickness ✓ shrunk Thickness around eye-hole ✓
 ermediate Shafts, diameter as per Rule ✓ Thrust shaft, diameter at collars as per Rule ✓
as fitted ✓ as fitted ✓
 be Shafts, diameter as per Rule ✓ Screw Shaft, diameter as per Rule ✓ Is the { tube } shaft fitted with a continuous liner { ✓
as fitted ✓ as fitted ✓ screw ✓
 nize Liners, thickness in way of bushes as per Rule ✓ Thickness between bushes as per Rule ✓ Is the after end of the liner made watertight in the
as fitted ✓ as fitted ✓ eller boss ✓
 If the liner is in more than one length are the junctions made by fusion through the whole thickness of the liner ✓
 e liner does not fit tightly at the part between the bearings in the stern tube, is the space charged with a plastic material insoluble in water and non-corrosive ✓
 wo liners are fitted, is the shaft lapped or protected between the liners ✓ Is an approved Oil Gland or other appliance fitted at the after end of the tube
✓ If so, state type ✓ Length of Bearing in Stern Bush next to and supporting propeller 16.5" m
 peller, dia. 5700 mm Pitch 5050/2860 No. of Blades 4 Material Stange whether Moveable Solid Total Developed Surface 118.4 sq. feet
 d Pumps worked from the Main Engines, No. 2 Diameter 110 mm Stroke 650 mm Can one be overhauled while the other is at work Yes
 ge Pumps worked from the Main Engines, No. 2 Diameter 110 mm Stroke 650 mm Can one be overhauled while the other is at work Yes
 ed { No. and size 2 Miss 8" x 10 1/2" x 22" Pumps connected to the { No. and size 2. 12" x 10" x 12"
 ps { How driven Steam driven Main Bilge Line { How driven Steam driven
 last Pumps, No. and size 2. 12" x 10" x 12" Lubricating Oil Pumps, including Spare Pump, No. and size ✓
 two independent means arranged for circulating water through the Oil Cooler ✓ Suctions, connected to both Main Bilge Pumps and Auxiliary
 e Pumps;—In Engine and Boiler Room 2 à 3" 2 à 5" om à 2 1/2"
 Pump Room tunnel 1 à 3" 1 à 2 1/2" In Holds, &c. N. 1. 2 à 3" N. 2. 2 à 3" N. 3. 2 à 3"
N. 4. 2 à 3" N. 5. 2 à 3" Deck tank 2 à 3"

n Water Circulating Pump Direct Bilge Suctions, No. and size 1 à 9" Independent Power Pump Direct Suctions to the Engine Room Bilges,
 and size 2 à 5" Are all the Bilge Suction Pipes in holds and tunnel well fitted with strum-boxes Yes
 the Bilge Suctions in the Machinery Space led from easily accessible mud-boxes, placed above the level of the working floor, with straight tail pipes to the bilges Yes
 all Sea Connections fitted direct on the skin of the ship Yes Are they fitted with Valves or Cocks both
 they fixed sufficiently high on the ship's side to be seen without lifting the stokehold plates Yes Are the Overboard Discharges above or below the deep water line above
 they each fitted with a Discharge Valve always accessible on the plating of the vessel Yes Are the Blow Off Cocks fitted with a spigot and brass covering plate Yes
 at Pipes pass through the bunkers none How are they protected ✓
 at pipes pass through the deep tanks ✓ Have they been tested as per Rule ✓
 all Pipes, Cocks, Valves, and Pumps in connection with the machinery and all boiler mountings accessible at all times Yes
 the arrangement of Valves and their connections such as to prevent the possibility of water passing from the sea or from water tanks into the cargo or machinery spaces, or from one
 apartment to another Yes Is the Shaft Tunnel watertight Yes Is it fitted with a watertight door Yes worked from 1st flat deck

IN BOILERS, &c.—(Letter for record ✓) Total Heating Surface of Boilers 4200 ft
 Forced Draft fitted Yes No. and Description of Boilers 3 single ended mult. boilers Working Pressure 14 kg.
 A REPORT ON MAIN BOILERS NOW FORWARDED? Yes Amsterdam
 A DONKEY BOILER FITTED? no If so, is a report now forwarded? ✓
 e donkey boiler intended to be used for domestic purposes only ✓

ANS. Are approved plans forwarded herewith for Shafting ✓ Main Boilers ✓ Auxiliary Boilers ✓ Donkey Boilers ✓
 (If not state date of approval)
 erheaters ✓ General Pumping Arrangements 3-4-33 Oil fuel Burning Piping Arrangements ✓

SPARE GEAR.

the spare gear required by the Rules been supplied Yes
 e the principal additional spare gear supplied screw shaft, propeller, crankshaft, pistons etc.

The foregoing is a correct description.

Manufacturer.



© 2019

Lloyd's Register Foundation

W290-0022

During progress of work in shops - - 1
 ?
 Dates of Survey while building {
 During erection on board vessel - - - ?
 ?
 Total No. of visits - *All notes lost by fire* -

Dates of Examination of principal parts—Cylinders ✓ Slides ✓ Covers ✓
 Pistons ✓ Piston Rods ✓ Connecting rods ✓
 Crank shaft ✓ Thrust shaft ✓ Intermediate shafts ✓
 Tube shaft ✓ Screw shaft ✓ Propeller ✓
 Stern tube *26 Sept '39* Engine and boiler seatings Engines holding down bolts *18 March '40*

Completion of fitting sea connections *26 Sept '39*
 Completion of pumping arrangements *+ March '40* Boilers fixed *+ Feb '40* Engines tried under steam *24-4-40*
 Main boiler safety valves adjusted *+ 25 March '40* Thickness of adjusting washers *P.B. no 3-18 1/2 in. no 1-16 in. no 5-16 in. C.B. no 2-16 in. S.B. no 6-16 in.*
 Crank shaft material ✓ Identification Mark ✓ Thrust shaft material ✓ Identification Mark ✓
 Intermediate shafts, material ✓ Identification Marks ✓ Tube shaft, material ✓ Identification Mark ✓
 Screw shaft, material ✓ Identification Mark ✓ Steam Pipes, material *S.M. steel* Test pressure *40 kg* Date of Test *+ March*

Is an installation fitted for burning oil fuel *coal burning*. Is the flash point of the oil to be used over 150°F. ✓

Have the requirements of the Rules for the use of oil as fuel been complied with ✓

Is the vessel (not being an oil tanker) fitted for carrying oil as cargo ✓ If so, have the requirements of the Rules been complied with ✓

If the notation for Ice Strengthening is desired, state whether the requirements in this respect have been complied with *Yes*

Is this machinery duplicate of a previous case *no* If so, state name of vessel ✓

General Remarks (State quality of workmanship, opinions as to class, &c. *This machinery and boilers have been made and fitted in accordance with the approved plans, Society's Rules and Secretariat letters. Material tested as required. The whole machinery has been tried under full working condition during a trial trip and was found all in good order. I am of opinion that the machinery is eligible to be recorded in the Society's Register with + L M C 4-40. C.T.*

The amount of Entry Fee ... £ : : When applied for,
 Special ... £ *228.00* : *228.15* 19 *40*
 Donkey Boiler Fee ... £ : : When received,
 Travelling Expenses (if any) £ *50.00* : : 19

Committee's Minute

Assigned

FRI. 11 JAN 1946

See minute on file

C.H. Bourne
 Engineer Surveyor to Lloyd's Register of Shipping.



© 2019

Lloyd's Register Foundation