

pressure in cylinders 700 lbs. Diameter of cylinder's 450 mm. Length of stroke 1200 mm. No. of cylinders 2. Is there a bearing between bearings, adjacent to the Crank, measured from inner edge to inner edge. 734 mm. ✓

1E

Chief Engineer Surveyor _____ Received from Chief Engineer Surveyor _____

NAME Dunvegan Castle Rpt. Bel. No. 11806

of the Chief Engineer Surveyor are desired on this case for the consideration of the Classing Committee.

The endorsement to contain a succinct summary of any repairs that have been required and to show the cause or causes of such repairs, and also to bring out clearly any exceptional features in connection with the case, so that the Classing Committee may have all the salient points presented in the endorsement. - Extract from Sub-Committee's Report, 24/5/92.

Chief Engine Oil Engines 2. S.C.O.A.
18 cy. 17 1/16" - 47 1/4"


RETAIN

Boilers fitted with forced draught
Main Shaft. If fitted with a continuous liner Yes.
If fitted with an outside gland of approved type no

This vessel's machinery appears to have been built in accordance with the Rules and the approved plans, and it is submitted she is fit to be classed + Lul. 8.36.

2 0/10 100 lb.

Ymn
4.9.36



© 2020
Lloyd's Register
Foundation

W883 - 0033

High Pressure Air Receivers, 200... Seamless, lap welded or riveted longitudinal joint Yes Material Steel Range of tensile strength 24/28 Tons Working pressure