

No 465 G

Particulars for Freeboard

Twin Screw Motor Ship 385' x 52' x 33'-8" Mid (34'-6" K. to B.)

|                     |          |
|---------------------|----------|
| Length on Waterline | 384.6 ft |
| Breadth Extreme     | 52.3 "   |
| Depth of Hold       | 30.6 "   |
| " Moulded Amidships | 33'-8"   |

|                            |       |
|----------------------------|-------|
| Tonnage Under Deck, about, | 4,950 |
|----------------------------|-------|

|                             |                      |
|-----------------------------|----------------------|
| Sheer at Stem               | 6'-2"                |
| " " $\frac{1}{8}$ from Stem | 3'-5"                |
| " " $\frac{1}{8}$ from Post | 1'-0 $\frac{1}{2}$ " |
| " " Post                    | 2'-4"                |

|                         |     |
|-------------------------|-----|
| Round of Beam           | 12" |
| Rise in Sheer $\propto$ | 2"  |

|                   |        |
|-------------------|--------|
| Extensions - Poop | 30'-6" |
| Bridge            | 84'-0" |
| Forecastle        | 42'-0" |

The above particulars to be verified from  
Board of Trade measurements and from the vessel.



Lloyd's Register

W4100204

(Para. 11, 12, 13, or 14)

FREEBOARD recommended amidships from centre of Disc to top of Statutory Deck Line, ~~Wood~~ (Iron) Deck :-

Fresh Water Line

above centre of Disc